

STATE OF FLORIDA
DEPARTMENT OF TRANSPORTATION

CONTRACT PLANS

FINANCIAL PROJECT ID 240200-2-52-01

(FEDERAL FUNDS)

SEMINOLE COUNTY (77320)

STATE ROAD NO. 429 (WEKIVA PARKWAY SECTION 7A)

TOLL FACILITIES PLANS

INDEX OF TOLL FACILITIES PLANS

SHEET NO. DRAWING NO. SHEET DESCRIPTION


1	GN-001	Key Sheet
2	GN-002	Signature Sheet
1-19	GC-001 - CE-214	Toll Facilities - Site Plans
1-50	AB-001 - AE-133	Toll Facilities - Building Plans
1-36	GG-001 - GE-216	Toll Facilities - Gantry Plans

TOLL FACILITIES PLANS
ENGINEER OF RECORD:


RAJNIKANT J. PATEL, P.E.
PE No.: 51149
AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
Phone (813) 286-1711
CONTRACT NO. C-9855
VENDOR NO. F952661922
CERTIFICATE OF AUTHORIZATION NO. 00008115

		DRAWING NO.
		GN-001
CONSTRUCTION CONTRACT NO.	FISCAL YEAR	SHEET NO.
T5626	18	1

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



THIS DOCUMENT HAS BEEN DIGITALLY
SIGNED AND SEALED BY:



PRINTED COPIES OF THIS DOCUMENT ARE NOT
CONSIDERED SIGNED AND SEALED. THE SIGNATURE
MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
AECOM TECHNICAL SERVICES, INC.
7650 W. COURTNEY CAMPBELL CAUSEWAY
TAMPA, FL 33607-1462
CA NO. 00008115
RAJNIKANT J. PATEL, P.E. NO. 51149

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR
THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.

TOLL FACILITIES PLANS

SHEET NO. DRAWING NO. SHEET DESCRIPTION

1	GN-001	Key Sheet
2	GN-002	Signature Sheet

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Rajnikant J. Patel, P.E. No. 51149	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			DRAWING NO. GN-002 SHEET NO. 2
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	
					SR 429	SEMINOLE	240200-2-52-01	

STATE OF FLORIDA
DEPARTMENT OF TRANSPORTATION

CONTRACT PLANS

FINANCIAL PROJECT ID 240200-2-52-01

(FEDERAL FUNDS)

SEMINOLE COUNTY (77320)

STATE ROAD NO. 429 (WEKIVA PARKWAY SECTION 7A)

INDEX OF TOLL FACILITIES-SITE PLANS

SHEET NO.	DRAWING NO.	BUILDING PERMIT SET	SHEET DESCRIPTION
1	GC-001	A / B	Key Sheet
2	GC-002	----	Signature Sheet
CIVIL PLANS			
3	GC-003	A	Toll Site Layout - Ramp E
4	GC-004	B	Toll Site Layout - Ramp F
5	GC-005	-----	Toll Site Details
6	GC-006	A	Toll Site Grading - Ramp E
7	GC-007	B	Toll Site Grading - Ramp F

ELECTRICAL PLANS

8	CE-101		Electrical Symbols, Legend and Abbreviations
9	CE-102		Electrical General Notes
10	CE-111		Site Electrical Plan at Ramp E
11	CE-112		Enlarged Site Electrical Plan at Ramp E
12	CE-113		Lightning Protection Plan at Ramp E
13	CE-114		Tolling Loop Conduit & Pull Box Details
14	CE-201		Electrical Symbols, Legend and Abbreviations
15	CE-202		Electrical General Notes
16	CE-211		Site Electrical Plan at Ramp F
17	CE-212		Enlarged Site Plan Electrical at Ramp F
18	CE-213		Lightning Protection Plan at Ramp F
19	CE-214		Tolling Loop Conduit & Pull Box Details

* Note:


A = Plans to be submitted for the State Building Permit for Ramp F
B = Plans to be submitted for the State Building Permit for Ramp E

TOLL FACILITIES - SITE PLANS

**TOLL FACILITIES-SITE PLANS
ENGINEER OF RECORD:**

RAJNIKANT J. PATEL, P.E.
PE No.: 51149
AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
Phone (813) 286-1711
CONTRACT NO. C-9855
VENDOR NO. F952661922
CERTIFICATE OF AUTHORIZATION NO. 00008115

		DRAWING NO.
		GC-001
CONSTRUCTION CONTRACT NO.	FISCAL YEAR	SHEET NO.
T5626	18	1



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:




PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM TECHNICAL SERVICES, INC.
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 RAJNIKANT J. PATEL, P.E. NO. 51149

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.


TOLL FACILITIES - SITE PLANS

CIVIL SITE PLANS

<u>SHEET NO.</u>	<u>DRAWING NO.</u>	<u>SHEET DESCRIPTION</u>
1	GC-001	Key Sheet
2	GC-002	Signature Sheet
3	GC-003	Toll Site Layout - Ramp E
4	GC-004	Toll Site Layout - Ramp F
5	GC-005	Toll Site Details
6	GC-006	Toll Site Grading - Ramp E
7	GC-007	Toll Site Grading - Ramp F



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:



PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM Technical Services, Inc.,
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 PETER J. PASTORE, P.E. NO. 77103

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.


TOLL FACILITIES - SITE PLANS

ELECTRICAL SITE PLANS

<u>SHEET NO.</u>	<u>DRAWING NO.</u>	<u>SHEET DESCRIPTION</u>
2	GC-002	Signature Sheet
8	CE-101	Electrical Symbols, Legend and Abbreviations
9	CE-102	Electrical General Notes
10	CE-111	Site Electrical Plan at Ramp E
11	CE-112	Enlarged Site Electrical Plan at Ramp E
12	CE-113	Lightning Protection Plan at Ramp E
13	CE-114	Tolling Loop Conduit & Pull Box Details
14	CE-201	Electrical Symbols, Legend and Abbreviations
15	CE-202	Electrical General Notes
16	CE-211	Site Electrical Plan at Ramp F
17	CE-212	Enlarged Site Plan Electrical at Ramp F
18	CE-213	Lightning Protection Plan at Ramp F
19	CE-214	Tolling Loop Conduit & Pull Box Details


<u>REVISIONS</u>				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Rajnikant J. Patel, P.E. No. 51149	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			DRAWING NO. GC-002 SHEET NO. 2
<u>DATE</u>	<u>DESCRIPTION</u>	<u>DATE</u>	<u>ROAD NO.</u>		<u>COUNTY</u>	<u>FINANCIAL PROJECT ID</u>		
			SR 429		SEMINOLE	240200-2-52-01		

SIGNATURE SHEET
(SITE PLANS)



- NOTES:**
- THIS PLAN TO BE READ IN CONJUNCTION WITH ROADWAY PLANS - Roadway, Drainage, Profiles, cross-sections, Traffic Control Plans, Utility Adjustment Sheets
TOLL FACILITIES - GANTRY PLAN: Gantry Structures and Gantry Electrical
TOLL FACILITIES - BUILDING PLAN: Architectural Plans, Building Structure Plans, Screen Wall, Building Electrical and Mechanical Plans
SIGNING & PAVEMENT MARKINGS PLANS
ITS PLANS
LIGHTING PLANS
 - REINFORCED STEEL STRUCTURES, ANY METALLIC OBJECTS AND LOW OR HIGH VOLTAGE TRANSMISSION CABLES ARE NOT ALLOWED BENEATH ASPHALT GANTRY PAVEMENT (SHADED AREA AS SHOWN IN PLAN VIEW).
 - CONCRETE PADS TO BE MINIMUM 2" HIGHER THAN ADJACENT CONCRETE SIDEWALK WITH 1/2" EXPANSION JOINT AND SEALER ALONG PERIMETER. EXPANSION JOINTS SHALL BE PROVIDED BETWEEN CONCRETE SIDEWALK AND DRILLED SHAFT FOUNDATION, CONCRETE BARRIER WALL AND DRYWALL.
 - LOOPS IN ASPHALT PAVEMENT ARE INSTALLED BY TOLL EQUIPMENT CONTRACTOR (NOT DEPICTED ON PLANS FOR CLARITY).
 - FOR JOINTS BETWEEN CONCRETE SIDEWALK AND CONCRETE STRUCTURES REFER TO INDEX 305.
 - FOR JOINTS BETWEEN CONCRETE SIDEWALK AND ASPHALT PAVEMENT REFER TO DETAIL 'CONC. SIDEWALK/ASPHALT PAVEMENT JOINT DETAIL' DEPICTED ON DRAWING # GC-005.
 - FOR CONCRETE SIDEWALK JOINTS REFER TO INDEX 310.
 - FOR BOLLARD AND CONCRETE PAD DETAIL REFER TO DRAWING NUMBER 'GC-005'.
 - GENERATOR TO BE POSITIONED IN SUCH MANNER THAT AIR INTAKE IS DIRECTED TOWARDS THE BUILDING SIDE AND THE EXHAUST IS DIRECTED TOWARDS TRANSFORMER SIDE FOR THIS PROJECT.
 - SODDING LIMITS - 100 FEET ON EITHER SIDE OF GANTRY LOCATION AND FROM RIGHT-OF-WAY LINES FOR ALL AREAS THAT ARE DISTURBED FROM CONSTRUCTION ACTIVITIES.
 - ITEMS LISTED BELOW, WITHIN THE LIMITS OF GANTRY PAVEMENT SHALL BE PAID UNDER FOLLOWING ROADWAY PAY ITEMS:

110-1-1 CLEARING & GRUBBING	334-1-53 SUPERPAVE ASPH. CONC, TRAFFIC C, PG 76-22
120-1 REGULAR EXCAVATION	337-7-83 ASPHALT CONCRETE FRICTION COURSE, TRAFFIC C, FC-12.5, PG 76-22
120-4 SUBSOIL EXCAVATION	521-1 MEDIAN CONCRETE BARRIER WALL
120-6 EMBANKMENT	521-72-3 SHOULDER CONCRETE BARRIER WALL, RIGID-SHOULDER
160-4 TYPE B STABILIZATION	536 1 1 GUARDRAIL -ROADWAY
285-70-6 OPTIONAL BASE, BASE GROUP 06	570-1-1 PERFORMANCE TURF
285-70-9 OPTIONAL BASE, BASE GROUP 09	
334-1-13 SUPERPAVE ASPHALTIC CONC, TRAFFIC C	
 - ALL WORK AT TOLL SITE, WITHIN THE LIMITS OF GANTRY PAVEMENT AS DESCRIBED IN THE TECHNICAL SPECIAL PROVISION - 'SR 429 (WEKIVA PARKWAY, SECTION 7A)', AND NOT LISTED IN NOTE # 11 SHALL BE PAID AS LUMP SUM UNDER PAY ITEM 735-74-1.



SITE LAYOUT (ENLARGED)
(N.T.S)

LEGEND

	TOLLING PAVEMENT AT GANTRY
	BLDG.- EQUIPMENT BUILDING - 21'-0" X 12'-6"
	GEN.- GENERATOR - 9'-2" X 3'-10"
	FT - FUEL TANK - 11'-0" X 4'-6"
	T - TRANSFORMER - 4'-8" X 4'-8"
	DW - CONDENSATE DRYWELL
	REMOVABLE BOLLARDS

FPID # 240200-2-52-01- SR 429 (WEKIVA PARKWAY, SECTION 7A) INCLUDES TOLL FACILITY AT FOLLOWING LOCATIONS:
 1. NON-ACCESSIBLE, SINGLE SPAN GANTRY AT RAMP E @ STA. 615+80.00
 2. NON-ACCESSIBLE, SINGLE SPAN GANTRY AT RAMP F @ STA. 712+00.00
 (FOR SITE LOCATION MAP REFER TO 'SYMBOLS, LEGEND AND NOTES', DRAWING # AG-100).



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 C.A. No. 8115
 Rajnikant J. Patel, P.E. No. 51149

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


TOLL SITE LAYOUT - RAMP E		DRAWING NO. GC-003
(WEKIVA PARKWAY SECTION 7A)		SHEET NO. 3

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



- NOTES:**
- THIS PLAN TO BE READ IN CONJUNCTION WITH ROADWAY PLANS - Roadway, Drainage, Profiles, cross-sections, Traffic Control Plans, Utility Adjustment Sheets
TOLL FACILITIES - GANTRY PLAN: Gantry Structures and Gantry Electrical
TOLL FACILITIES - BUILDING PLAN: Architectural Plans, Building Structure Plans, Screen Wall, Building Electrical and Mechanical Plans
SIGNING & PAVEMENT MARKINGS PLANS
ITS PLANS
LIGHTING PLANS
 - REINFORCED STEEL STRUCTURES, ANY METALLIC OBJECTS AND LOW OR HIGH VOLTAGE TRANSMISSION CABLES ARE NOT ALLOWED BENEATH ASPHALT GANTRY PAVEMENT (SHADED AREA AS SHOWN IN PLAN VIEW).
 - CONCRETE PADS TO BE MINIMUM 2" HIGHER THAN ADJACENT CONCRETE SIDEWALK WITH 1/2" EXPANSION JOINT AND SEALER ALONG PERIMETER. EXPANSION JOINTS SHALL BE PROVIDED BETWEEN CONCRETE SIDEWALK AND DRILLED SHAFT FOUNDATION, CONCRETE BARRIER WALL AND DRYWALL.
 - LOOPS IN ASPHALT PAVEMENT ARE INSTALLED BY TOLL EQUIPMENT CONTRACTOR (NOT DEPICTED ON PLANS FOR CLARITY).
 - FOR JOINTS BETWEEN CONCRETE SIDEWALK AND CONCRETE STRUCTURES REFER TO INDEX 305.
 - FOR JOINTS BETWEEN CONCRETE SIDEWALK AND ASPHALT PAVEMENT REFER TO DETAIL 'CONC. SIDEWALK/ASPHALT PAVEMENT JOINT DETAIL' DEPICTED ON DRAWING # GC-005.
 - FOR CONCRETE SIDEWALK JOINTS REFER TO INDEX 310.
 - FOR BOLLARD AND CONCRETE PAD DETAIL REFER TO DRAWING NUMBER 'GC-005'.
 - GENERATOR TO BE POSITIONED IN SUCH MANNER THAT AIR INTAKE IS DIRECTED TOWARDS THE BUILDING SIDE AND THE EXHAUST IS DIRECTED TOWARDS TRANSFORMER SIDE FOR THIS PROJECT.
 - SODDING LIMITS - 100 FEET ON EITHER SIDE OF GANTRY LOCATION AND FROM RIGHT-OF-WAY LINES FOR ALL AREAS THAT ARE DISTURBED FROM CONSTRUCTION ACTIVITIES.
 - ITEMS LISTED BELOW, WITHIN THE LIMITS OF GANTRY PAVEMENT SHALL BE PAID UNDER FOLLOWING ROADWAY PAY ITEMS:

110-1-1 CLEARING & GRUBBING	334-1-53 SUPERPAVE ASPH. CONC, TRAFFIC C, PG 76-22
120-1 REGULAR EXCAVATION	337-7-83 ASPHALT CONCRETE FRICTION COURSE, TRAFFIC C, FC-12.5, PG 76-22
120-4 SUBSOIL EXCAVATION	521-1 MEDIAN CONCRETE BARRIER WALL
120-6 EMBANKMENT	521-72-3 SHOULDER CONCRETE BARRIER WALL, RIGID-SHOULDER
160-4 TYPE B STABILIZATION	536 1 1 GUARDRAIL - ROADWAY
285-70-6 OPTIONAL BASE, BASE GROUP 06	570-1-1 PERFORMANCE TURF
285-70-9 OPTIONAL BASE, BASE GROUP 09	
334-1-13 SUPERPAVE ASPHALTIC CONC, TRAFFIC C	
 - ALL WORK AT TOLL SITE, WITHIN THE LIMITS OF GANTRY PAVEMENT AS DESCRIBED IN THE TECHNICAL SPECIAL PROVISION - 'SR 429 (WEKIVA PARKWAY, SECTION 7A)', AND NOT LISTED IN NOTE # 11 SHALL BE PAID AS LUMP SUM UNDER PAY ITEM 735-74-2.



LEGEND


	ROADWAY PAVEMENT AT GANTRY
	BLDG.- EQUIPMENT BUILDING - 21'-0" X 12'-6"
	GEN.- GENERATOR - 9'-2" X 3'-10"
	FT - FUEL TANK - 11'-0" X 4'-6"
	T - TRANSFORMER - 4'-8" X 4'-8"
	DW - CONDENSATE DRYWELL
	● - REMOVABLE BOLLARDS

SITE LAYOUT (ENLARGED)
(N.T.S.)


FPID # 240200-2-52-01- SR 429 (WEKIVA PARKWAY, SECTION 7A) INCLUDES TOLL FACILITY AT FOLLOWING LOCATIONS:
 1. NON-ACCESSIBLE, SINGLE SPAN GANTRY AT RAMP E @ STA. 615+80.00
 2. NON-ACCESSIBLE, SINGLE SPAN GANTRY AT RAMP F @ STA. 712+00.00
 (FOR SITE LOCATION MAP REFER TO 'SYMBOLS, LEGEND AND NOTES', DRAWING # AG-100).

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Rajnikant J. Patel, P.E. No. 51149	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			DRAWING NO. GC-004
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	
					SR 429	SEMINOLE	240200-2-52-01	TOLL SITE LAYOUT - RAMP F (WEKIVA PARKWAY SECTION 7A)


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




REMOVABLE BOLLARD DETAIL
(ON EXISTING GROUND)
SCALE: N.T.S.




REMOVABLE BOLLARD DETAIL
(ON ASPHALT PAVEMENT)
SCALE: N.T.S.



(CONCRETE SIDEWALK ADJACENT TO CONCRETE BARRIER WALL)
SCALE: N.T.S.



CONC. SIDEWALK/ASPHALT PAVEMENT JOINT DETAIL (INDEX 305)
SCALE: N.T.S.





CONCRETE PAD FOR GENERATOR AND FUEL TANK - 12" THICK
SCALE: N.T.S.


PAD CONSTRUCTION MATERIAL: CONCRETE: CLASS II, FDOT 3400 PSI, 28 DAYS REIN. STEEL: ASTM A615, GRADE 60 UNCOATED

NOTE: CONCRETE PAD FOR TRANSFORMER - CONTRACTOR TO COORDINATE WITH THE LOCAL ELECTRIC UTILITY COMPANY TO DETERMINE THE CORRECT TRANSFORMER PAD SIZE, SHAPE AND CUTOUTS THAT ARE REQUIRED BY THE UTILITY.


NOTE: BARRIER MOUNTED SIGN - REFER TO STANDARD INDEX 11870 FOR MATERIAL PROPERTIES




END PLATE




SIGN TPK - 8 (RIGHT) GROUND MOUNTED (INDEX 11860)
SCALE: N.T.S.




TYPICAL SECTION THRU BARRIER WALL AT SIGN SUPPORT BRACKET (LOOKING IN DIRECTION OF TRAFFIC)
SCALE: N.T.S.




PLAN SIGN SUPPORT BRACKET



BASE PLATE



SIGN SUPPORT WELDMENT DETAIL



U-BOLT PLATE WASHER


REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
C.A. No. 8115
Rajnikant J. Patel, P.E. No. 51149

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

TOLL SITE DETAILS	
(WEKIVA PARKWAY SECTION 7A)	DRAWING NO. GC-005 SHEET NO. 5

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



- - - EJ - - - EXPANSION JOINT - REFER TO NOTE #7 ON DWG. NO. 'GC-003'.
 - - - CJ - - - CONTRACTION JOINT - REFER TO NOTE #7 ON DWG. NO. 'GC-003'.

LEGEND

- BLDG. - TOLL EQUIPMENT BUILDING 21'-0" X 12'-6"
- DW - CONDENSATE DRYWELL
- FT - FUEL TANK - 11'-0" X 4'-6"
- GEN - GENERATOR - 9'-2" X 3'-10"
- T - PAD MOUNTED TRANSFORMER - 4'-8" X 4'-8"
- - REMOVABLE BOLLARDS

6" THICK CONCRETE SIDEWALK			
POINT	STATION	OFFSET	ELEVATION
A	616+30.00	27.00' RT	69.40'
B	616+30.00	33.16' RT	69.50'
C	615+84.95	32.75' RT	70.70'
D	615+84.94	37.75' RT	70.80'
E	615+75.06	37.75' RT	71.08'
F	615+75.08	49.50' RT	71.15'
G	615+44.59	49.71' RT	71.15'
H	615+44.39	32.43' RT	71.20'
I	615+29.00	32.66' RT	71.40'
J	615+28.96	27.00' RT	71.30'
K	615+44.39	27.00' RT	71.15'
L	615+75.06	27.00' RT	70.90'
M	615+84.95	27.00' RT	70.60'
R1	615+70.11	27.00' RT	71.00'
L1	615+75.06	32.00' RT	71.00'

BUILDING EXTERIOR CORNERS			
POINT	STATION	OFFSET	ELEVATION
R	615+70.11	32.02' RT	71.10'
S	615+49.33	32.16' RT	71.20'
T	615+49.45	44.66' RT	71.25'
U	615+70.15	44.52' RT	71.25'

12" THICK CONCRETE PAD			
POINT	STATION	OFFSET	ELEVATION
W	615+44.59	49.71' RT	71.60'
X	615+44.39	32.43' RT	71.60'
Y	615+29.05	32.66' RT	71.60'
Z	615+29.34	49.93' RT	71.60'

TOP OF PULL BOX ELEVATIONS	
POINT	ELEVATION
PB-1	69.62'
PB-2	70.07'
PB-3	70.30'
PB-4	70.60'
PB-5	70.94'
PB-6	71.09'
PB-7	71.18'
PB-ITS	71.18'
TELCO	71.20'
DW	71.20'

100 YEAR FLOOD ELEVATION:
 Lake Sylvan (South side of Mainline): 42.2' (NAVD 88)
 Yankee Lake (North side of Mainline): 37.2' (NAVD 88)
 (REFER TO ' DRAINAGE DESIGN DOCUMENTATION '
 - FPID # 240200-2-52-01, WEKIVA PARKWAY, SECTION 7A)



BUILDING FLOOR ELEVATION - 71.30'
 FUEL TANK / GENERATOR PAD ELEVATION - 71.65'
 TRANSFORMER PAD ELEVATION - 71.55'

PULL BOX ELEVATIONS DEPICTED HERE ARE AT THE CENTER OF THE PULL BOX. THE PULL BOX TOP SHALL MATCH THE CROSS SLOPE OF ADJACENT CONCRETE WORK.

STATION OFFSET DEPICTED ON THIS PLAN SHEET ARE RADIAL TO THE RAMP E BASELINE.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Rajnikant J. Patel, P.E. No. 51149	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			TOLL SITE GRADING - RAMP E S.R. 429 (WEKIVA PARKWAY SECTION 7A)	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		GC-006
					SR 429	SEMINOLE	240200-2-52-01	SHEET NO.	
								6	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



- - - EJ - - - EXPANSION JOINT - REFER TO NOTE #7 ON DWG. NO. 'GC-004'.
 - - - CJ - - - CONTRACTION JOINT - REFER TO NOTE #7 ON DWG. NO. 'GC-004'.

LEGEND

- BLDG. - TOLL EQUIPMENT BUILDING 21'-0" X 12'-6"
- DW - CONDENSATE DRYWELL
- FT - FUEL TANK - 11'-0" X 4'-6"
- GEN - GENERATOR
- T - PAD MOUNTED TRANSFORMER - 4'-8" X 4'-8"
- - REMOVABLE BOLLARDS

6" THICK CONCRETE SIDEWALK			
POINT	STATION	OFFSET	ELEVATION
A	711+50.00	27.00' LT	61.10'
B	711+50.00	32.00' LT	61.20'
C	711+95.00	32.00' LT	60.50'
D	711+95.00	38.50' LT	60.50'
E	712+05.00	38.50' LT	60.20'
F	712+05.00	52.25' LT	60.20'
G	712+36.00	52.25' LT	60.20'
H	712+36.00	32.30' LT	60.10'
I	712+51.50	32.30' LT	60.00'
J	712+51.50	27.00' LT	59.90'
K	712+36.00	27.00' LT	60.00'
L	712+05.00	27.00' LT	60.20'
M	711+95.00	27.00' LT	60.40'
R1	712+10.00	27.00' LT	60.18'
L1	712+05.00	32.75' LT	60.30'
S1	712+31.00	27.00' LT	60.15'

BUILDING EXTERIOR CORNERS			
POINT	STATION	OFFSET	ELEVATION
R	712+10.00	32.75' LT	60.30'
S	712+31.00	32.75' LT	60.20'
T	712+31.00	45.25' LT	60.30'
U	712+10.00	45.25' LT	60.30'

12" THICK CONCRETE PAD			
POINT	STATION	OFFSET	ELEVATION
W	712+36.00	52.25' LT	60.40'
X	712+36.00	32.30' LT	60.40'
Y	712+51.50	32.30' LT	60.40'
Z	712+51.50	52.25' LT	60.40'

TOP OF PULL BOX ELEVATIONS	
POINT	ELEVATION
PB-1	61.09'
PB-2	60.88'
PB-3	60.68'
PB-4	60.50'
PB-5	60.26'
PB-6	60.21'
PB-7	60.15'
PB-ITS	60.24'
TELCO	60.24'
DW	60.26'
IPB-1	60.24'

100 YEAR FLOOD ELEVATION:
 Lake Sylvan (South side of Mainline): 42.2' (NAVD 88)
 Yankee Lake (North side of Mainline): 37.2' (NAVD 88)
 (REFER TO ' DRAINAGE DESIGN DOCUMENTATION ' - FPID # 240200-2-52-01, WEKIVA PARKWAY, SECTION 7A)

BUILDING FLOOR ELEVATION - 60.35'
 FUEL TANK / GENERATOR PAD ELEVATION - 60.45'
 TRANSFORMER PAD ELEVATION - 60.20'

PULL BOX ELEVATIONS DEPICTED HERE ARE AT THE CENTER OF THE PULL BOX. THE PULL BOX TOP SHALL MATCH THE CROSS SLOPE OF ADJACENT CONCRETE WORK.


REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Rajnikant J. Patel, P.E. No. 51149	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			TOLL SITE GRADING - RAMP F S.R. 429 (WEKIVA PARKWAY SECTION 7A)	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		GC-007
					SR 429	SEMINOLE	240200-2-52-01	SHEET NO.	
								7	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

ELECTRICAL SYMBOL LEGEND:

SYMBOL	DESCRIPTION
	CONDUIT UP.
	CONDUIT DOWN.
	HOMERUN TO PANEL - LETTER INDICATES PANEL, NUMBERS INDICATE CIRCUITS. ALL RACEWAYS WITHOUT FURTHER DESIGNATION INDICATE A TWO-WIRE CIRCUIT. FOUR WIRES ARE INDICATED. LONG MARKS INDICATE NEUTRAL CONDUCTOR, SHORT MARKS INDICATE PHASE CONDUCTORS. PROVIDE GREEN GROUND CONDUCTOR IN ALL CONDUITS. (TIE) INDICATES CIRCUIT IS SHARED WITH ADDITIONAL RECEPTACLES.
	DEVICE OR EQUIPMENT AS NOTED
	REFERENCE NOTES
	OUTLET OR JUNCTION BOX, SIZE PER NEC.
	PANELBOARD. (DIRTY POWER)
	SQUARE D POWERLINK PANELBOARD (CRITICAL POWER) PANELBOARD FED VIA UPS
	CONTROL PANEL.
	AUTOMATIC TRANSFER SWITCH.
	SURGE PROTECTION DEVICE.
	PULL BOX.
	EMERGENCY POWER SHUTOFF SWITCH.
	LIGHTNING PROTECTION CONDUCTOR.
	UNDERGROUND GROUND CONDUCTOR.
	CONDUIT RACEWAY EXPOSED.
	CONDUIT RACEWAY CONCEALED IN CEILING SPACE OR WALLS.
	CONDUIT RACEWAY IN CONCRETE SLAB OR UNDERGROUND.
	WIREWAY
	WIREWAY FITTING
	GROUND INSPECTION WELL
	GROUND BUSBAR
	GROUND ROD

GENERAL SYMBOL LEGEND:



ABBREVIATIONS:

A	AMPS
AASHTO	AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS
AC	AIR CONDITIONING [UNIT]
AFF	ABOVE FINISH FLOOR
AFG	ABOVE FINISH GRADE
AL, ALUM.	ALUMINUM
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS
ATS	AUTOMATIC TRANSFER SWITCH
AVI	AUTOMATIC VEHICLE IDENTIFICATION
AWG	AMERICAN WIRE GAUGE
BCU	BATTERY CHARGER UNIT
BLDG.	BUILDING
BPS	BYPASS SWITCH
C	CONDUIT
CCTV	CLOSED CIRCUIT TELEVISION
CKT.	CIRCUIT
COMP	COMPUTER
CU	COPPER
COMM.	COMMUNICATION
DEP	DEPARTMENT OF ENVIRONMENTAL PROTECTION
DIA.	DIAMETER
DN	DOWN
DWG.	DRAWING
E6	ENCOMPASS 6 MULTIPROTOCOL READER
EB	EASTBOUND
ENG.	ENGINE
E.T.C.	ELECTRONIC TOLL COLLECTION
ETC.	ET CETERA
EQUIP.	EQUIPMENT
EPA	ENVIRONMENTAL PROTECTION AGENCY
EPO	EMERGENCY POWER OFF
EXT.	EXTERIOR
FBC	FLORIDA BUILDING CODE
FOC	FIBER OPTIC CABLE
FT	FOOT; FEET
FTE	FLORIDA'S TURNPIKE ENTERPRISE
FTL	FEED THROUGH LUGS
FTM	FUEL TANK MONITOR
FUT	FUTURE
GA	GAUGE
GAL.	GALLON
GEC	GROUNDING ELECTRODE CONDUCTOR
GEN	GENERATOR
GFI	GROUND FAULT INTERRUPTER
GND	GROUND
HID	HIGH INTENSITY DISCHARGE
HP	HORSEPOWER
HZ	HORIZONTAL, HERTZ
I.C.	INTERRUPTING CAPACITY
I.D.	IDENTIFICATION
IN.	INCHES
IPB	INTERMEDIATE PULLBOX
ITS	INTELLIGENT TRANSPORTATION SYSTEM
JB	JUNCTION BOX
KA	KILOAMPERES
KVA	KILOVOLT AMPERES
KW	KILOWATT
LED	LIGHT EMITTING DIODE
LFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT
LN CTR	LANE CONTROLLER
LOC.	LOCATION
LLC	LEAD LAG CONTROLLER
LP	LIGHTNING PROTECTION
LTG	LIGHTING
MAX.	MAXIMUM
MCB	MAIN CIRCUIT BREAKER
MTS	MANUAL TRANSFER SWITCH
MIN.	MINIMUM
ML	MAINLINE
M.L.O.	MAIN LUGS ONLY
MOT	MAINTENANCE OF TRAFFIC
MPB	MEDIAN PULLBOX
MTD	MOUNTED
N	NEUTRAL
NB	NORTHBOUND
N.C.	NORMALLY CLOSED
NEC	NATIONAL ELECTRICAL CODE

ABBREVIATIONS CONT:

NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
NIC	NOT IN CONTRACT
NO.	NUMBER
N.O.	NORMALLY OPEN
N.T.S.	NOT TO SCALE
N3R	NEMA 3R
OC	ON CENTER
ORT	OPEN ROAD TOLLING
Ø	PHASE
P	POLE
PB	PULLBOX
PCB	POLYCHLORINATED BIPHENYL
PNL	PANEL
PTZ	PAN-TILT-ZOOM
PVC	POLYVINYL CHLORIDE
RECEPT.	RECEPTACLE
RGS	RIGID GALVANIZED STEEL
RMS	ROOT MEAN SQUARED
SB	SOUTHBOUND
SCADA	SUPERVISORY CONTROL & DATA ACQUISITION
SCH.	SCHEDULE
SCP	SCADA CONTROL PANEL
SCTE	SOCIETY OF CABLE TELECOMMUNICATIONS ENGINEERS
SD	SQUARE D
SER	SERVICE ENTRANCE RATED
SPD	SURGE PROTECTIVE DEVICE
SPEC(S)	SPECIFICATION(S)
S.P.S.T.	SINGLE POLE SINGLE THROW
S.S.	STAINLESS STEEL
STP	SHIELDED TWISTED PAIR
SQ.	SQUARE
STFE	STATE TOLL FACILITY ENGINEER
SYMM.	SYMMETRICAL
T.E.C.	TOLL EQUIPMENT CONTRACTOR
T&H	TEMPERATURE AND HUMIDITY SENSOR
T.O.	TOLL OPERATIONS
TSP	TECHNICAL SPECIAL PROVISIONS
TYP.	TYPICAL
UL	UNDERWRITERS LABORATORIES
UON	UNLESS OTHERWISE NOTED
UPS	UNINTERRUPTIBLE POWER SUPPLY
V	VOLTS
VAC	VOLTS ALTERNATING CURRENT
VDAC	VEHICLE DETECTION AND CLASSIFICATION UNIT
VES	VIOLATION ENFORCEMENT SYSTEM
VSS	VIDEO SURVEILLANCE SYSTEM
W	WIRE; WATT
W/	WITH
WB	WESTBOUND
WP	WEATHERPROOF (NEMA 3R)
XFMR	TRANSFORMER


REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ELECTRICAL SYMBOL LEGEND AND ABBREVIATIONS		DRAWING NO. CE-101
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		SHEET NO.
						SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A	

ELECTRICAL GENERAL NOTES:

1. FEED ALL RECEPTACLES AND DEVICES WITH (2) #12, (1) #12 GND IN 3/4" C, UON.
2. PROVIDE AN EQUIPMENT GROUNDING CONDUCTOR IN ALL FEEDER AND BRANCH CIRCUIT RACEWAYS.
3. ALL 120V, 20A CIRCUIT HOMERUNS OVER 50FT. SHALL BE #10 CU MINIMUM, UON.
4. ALL 120V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #8 CU MINIMUM, UON.
5. ALL 240V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #10 CU. MINIMUM, UON.
6. ALL 240V, 20A CIRCUIT HOMERUNS OVER 300FT. SHALL BE #8 CU MINIMUM, UON.
7. VERIFY EXACT LOCATION OF ALL MECHANICAL EQUIPMENT WITH MECHANICAL INSTALLER PRIOR TO ROUGH-IN.
8. PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT AND RACEWAYS WITH LABELING AT EACH END. REFER TO DETAIL 3, DWG. CE-114.
9. THE USE OF ANY PROCESS INVOLVING ASBESTOS OR PCB, AND THE INSTALLATION OF ANY PRODUCT, INSULATION, COMPOUND OR MATERIAL CONTAINING OR INCORPORATING ASBESTOS OR PCB, IS PROHIBITED. PROVIDE A COMPLETE AND PROPERLY OPERATING ELECTRICAL SYSTEM WITHOUT THE USE OF ASBESTOS OR PCB.
10. CONTACT THE POWER COMPANY AND TELEPHONE COMPANY WITHIN 10 BUSINESS DAYS OF THE AWARD OF THE CONTRACT AND SCHEDULE NEW SERVICE INSTALLATION.
11. CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID. SUBMISSION OF A BID WILL BE CONSTRUED AS EVIDENCE THAT SUCH EXAMINATION HAS BEEN MADE AND LATER CLAIMS FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WILL NOT BE RECOGNIZED.
12. INCLUDE THE TRANSPORT AND DISPOSAL OR RECYCLING OF ALL WASTE MATERIALS GENERATED BY THIS PROJECT IN ACCORDANCE WITH ALL RULES, REGULATIONS AND GUIDELINES APPLICABLE.
 - A) COMPLY FULLY WITH FLORIDA STATUTE 403.7186 REGARDING MERCURY CONTAINING DEVICES AND LAMPS.
 - B) TRANSPORT AND DISPOSE OF LAMPS, BALLASTS AND OTHER MATERIALS IN ACCORDANCE WITH ALL DEP AND EPA GUIDELINES.
 - C) PROVIDE WRITTEN CERTIFICATION THAT ALL MATERIALS WERE RECYCLED OR DISPOSED OF PROPERLY PER THE GUIDELINES NOTED ABOVE.
13. LOCATE EXISTING UTILITIES AND PROTECT THEM FROM DAMAGE.
14. PHASE WORK AS REQUIRED BY MOT PLANS.
15. UNDERGROUND CONDUIT SHALL BE PVC SCH. 80, UON. UNDERGROUND CONDUIT SHALL TRANSITION TO RGS CONDUIT WITH PVC TO RGS CONDUIT FITTINGS. CONDUIT SHALL BE RGS ABOVE GRADE THROUGH AND INCLUDING THE FIRST 90 DEGREE FITTING UNDERGROUND UON. APPLY 2-COAT BITUMASTIC COATING TO DIRECT BURIED PORTION OF RGS CONDUIT, UP TO AND INCLUDING 6" ABOVE FINAL GRADE. REFER TO TSP FOR FURTHER INFORMATION.
16. TOLL EQUIPMENT AND ALL WIRING/CABLING FOR TOLL EQUIPMENT WILL BE FURNISHED AND INSTALLED BY T.E.C., UON.
17. UNDERGROUND CONDUITS SHALL BE INSTALLED A MINIMUM OF 36" BELOW GRADE.
18. EXPOSED EXTERIOR CONDUIT SHALL BE RGS THROUGH AND INCLUDING THE FIRST 90° BEND INSTALLED UNDERGROUND. TRANSITIONS BETWEEN RGS AND PVC CONDUIT SHALL BE MADE WITH A RGS TO PVC CONDUIT FITTING.
19. EQUIPMENT SPECIFIED WITH CATALOG NUMBERS OR PART NUMBERS SHALL NOT BE SUBSTITUTED UNLESS "OR EQUAL" IS INDICATED.
20. CONDUIT RESERVED FOR TOLLING LOOPS SHALL BE SCH. 80 PVC.
21. PLASTIC END CAPS SHALL BE INSTALLED ON ENDS OF UNISTRUT.
22. ALL LIQUID-TIGHT, FLEXIBLE CONDUIT SHALL BE METALLIC.
23. ADJUST THE LOCATIONS OF THE SPD'S SUCH THAT THE MAXIMUM SPD BRAIDED/TWISTED LEADS LENGTH DO NOT EXCEED 24 INCHES AND HAVE NO SHARP TURNS.
24. AC OR DC ELECTRICAL CIRCUITS OR WIRING THAT OPERATES AT 25 VOLTS OR GREATER SHALL NOT BE INSTALLED AND/OR LOCATED WITHIN 5 FEET OF ANY TRAFFIC DETECTION LOOP OR LOOP PULL BOX.
25. MAINLINE GANTRY DATA WIRE TROUGHS SHALL BE MODIFIED BY A UL OR ETL LISTED PANEL SHOP. THE WIREWAYS TERMINATED TO THE TOP OF THE WIRE TROUGH SHALL BE MODIFIED AND ASSEMBLED IN THE PANEL SHOP & NOT IN THE FIELD TO ENSURE PROPER WATERTIGHT SEAL. SHOP DRAWINGS INCLUDING DIMENSIONED SKETCHES & MATERIAL PRODUCT DATA SHALL BE SUBMITTED FOR REVIEW FOR FABRICATION OF DATA WIRE TROUGH. REFER TO MAINLINE GANTRY DETAILS FOR ADDITIONAL REQUIREMENTS.
26. CONDUIT BENDS SHALL NOT EXCEED 270° BETWEEN PULL POINTS.
27. OUTLET AND DEVICE JUNCTION BOXES INSTALLED OUTDOORS SHALL BE MANUFACTURED FROM GALVANIZED CAST IRON WITH THREADED HUBS, UON. REFER TO TSP SECTION 26 05 33 FOR DETAILS.
28. REFER TO CIVIL PLANS FOR TOLL FACILITY SITE LOCATIONS.
29. THESE PLANS SHALL BE READ IN CONJUNCTION WITH ALL COMPONENTS OF THE ROADWAYS PLANS, TOLL FACILITIES GANTRY PLANS, TOLL FACILITY BUILDING PLANS, SIGNING & PAVEMENT MARKING PLANS, ITS PLANS AND LIGHTING PLANS.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	ELECTRICAL GENERAL NOTES	CE-102
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 SITE ELECTRICAL PLAN - RAMP E
 CE-111 SCALE: 1" = 20'-0"


REFERENCE NOTES:

- 1 PROPOSED BURIED PRIMARY CIRCUITING BY POWER COMPANY. REFER TO UTILITY ADJUSTMENT SHEETS FOR CONTINUATION AND DETAILS. THE ELECTRICAL CONTRACTOR SHALL CONTACT THE UTILITY COMPANY (FP&L, GARRETT PETERSON, 407-328-1934) WITHIN TWO WEEKS OF NTP TO ENSURE ELECTRICAL SERVICE IS AVAILABLE WHEN CONSTRUCTION OF THE TOLL BUILDING IS COMPLETE. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR PAYING THE POWER COMPANY TO BRING POWER TO THE TRANSFORMER (PRIMARY).
- 2 UNDERGROUND SERVICE LATERAL, SEE DWG. AE-130. THE CONTRACTOR SHALL RUN SERVICE LATERAL AROUND, BUT NOT UNDER, LARGE PIECES OF EQUIPMENT AND/OR BUILDING FOOTERS. CONTRACTOR SHALL PAY FOR COSTS ASSOCIATED WITH THE INSTALLATION OF THE ELECTRICAL SERVICE FROM THE SECONDARY LUGS OF THE UTILITY XFMR TO AND INCLUDING THE SERVICE DISCONNECTING MEANS, GROUNDING, METER SOCKET AND OTHER WORK AS SPECIFIED.



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: SITE ELECTRICAL PLAN AT RAMP E		DRAWING NO. CE-111
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 10
						SR 429	SEMINOLE	240200-2-52-01		

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




1 ENLARGED SITE ELECTRICAL PLAN - RAMP E
 CE-112 SCALE: 1" = 5'-0"

REFERENCE NOTES:

- ① SERVICE LATERAL. REFER TO POWER RISER DIAGRAM ON DWG. AE-130 FOR DETAILS.
- ② POWER CIRCUITING FROM GENERATOR CIRCUIT BREAKER (GCB) TO ATS. REFER TO POWER RISER DIAGRAM, DWG. AE-130.
- ③ 1" CONDUIT FOR BATTERY CHARGING CIRCUIT, 2 #6 (COLOR RED FOR +12V, COLOR BLACK FOR -12V), TYPE MTW CONDUCTORS.
- ④ 1" CONDUIT FOR JACKET WATER HEATER CIRCUITING. REFER TO PANEL SCHEDULE, DWG. AE-131.
- ⑤ (1) 1-1/2" CONDUIT FROM GENERATOR CONTROL PANEL TO SCADA PANEL. REFER TO DWG. AE-133.
- ⑥ (1) 1-1/2" CONDUIT FOR SCADA CONNECTIONS. REFER TO DWG. AE-133.
- ⑦ 2 #14 (GENSET RUN), 4 #14 (SPARE), 1 #14 GND. 1" C.
- ⑧ 4" X 4" WEATHERPROOF CAST IRON BOX WITH A GASKETED COVER, APPLETON CATALOG # FSD-2-75 OR APPROVED EQUAL.
- ⑨ 1" CONDUIT. REFER TO PANEL SCHEDULE, DWG. AE-131.
- ⑩ (1) COMMUNICATION CABLE IN 1" C. FROM GENERATOR CONTROL PANEL TO EPO STATION ON EXTERIOR WALL OF ENTRANCE DOOR. REFER TO DETAIL 3, DWG. AE-120.

- ⑪ MOUNT TOP OF EQUIPMENT 5'-0" AFG ON UNISTRUT SUPPORT STRUCTURE. SEE DETAIL 3 ON DRAWING GE-113.
- ⑫ PROVIDE (2) 2" C WITH PULL STRING FOR FOC NETWORK CONNECTIONS. EXTEND CONDUITS 5'-0" BEYOND CONCRETE EDGE AND CAP. CONDUIT CONTINUATION & FOC WILL BE INSTALLED BY ITS CONTRACTOR.
- ⑬ (4) 3" CONDUIT (LOOPS).
- ⑭ (4) 2" CONDUIT (POWER).
- ⑮ (3) 4" CONDUIT (DATA).
- ⑯ (2) 4" CONDUIT (E6).
- ⑰ (2) 2" CONDUIT (CCTV).
- ⑱ (1) 1" C. (POWER FOR PTZ CAMERA).
- ⑲ (1) 3" CONDUIT (LOOPS).
- ⑳ GROUNDING ELECTRODE SYSTEM. REFER TO DWG. AE-121 AND AE-130.
- ㉑ PROVIDE 24"x36"x24" POLYMER CONCRETE PULLBOX WITH COVER STAMPED "ITS INTERFACE". PULLBOX AND COVER SHALL BE MINIMUM UL LISTED, ANSI/STCE 77 LOAD COMPLIANT, AND ANSI TIER 15 RATED.

- ㉒ (2) 2" C. WITH PULL STRING FOR COMMUNICATION SERVICE CONNECTIONS.
- ㉓ PROVIDE 24"x36"x24" POLYMER CONCRETE PULLBOX WITH COVER STAMPED "TELCO COMMUNICATIONS" FOR COMMUNICATION SERVICE. PULLBOX AND COVER SHALL BE MINIMUM UL LISTED, ANSI TIER 15 RATED.
- ㉔ PROVIDE (2) 2" C. FOR TELCO COMMUNICATION SERVICE. EXTEND CONDUIT 5'-0" BEYOND CONCRETE EDGE FOR FUTURE CONNECTION BY OTHERS.
- ㉕ 90 DEGREE WIREWAY FITTING. FITTING SHALL BE UL LISTED FOR HORIZONTAL TO VERTICAL TRANSITION. REFER TO TSP 26 05 34.
- ㉖ 6" X 6" FEED THROUGH WIREWAY. REFER TO TSP 26 05 34 FOR WIREWAY RATING AND DETAILS.
- ㉗ PROVIDE FLEXIBLE FITTING TO COMPENSATE FOR MISALIGNMENT, STRETCH LENGTH RANGE FROM 3-1/2" TO 12", HYPALON BELLOW WITH STAINLESS STEEL FLANGES.
- ㉘ 12" X 12" X 24" NEMA 3R POWER WIRE TROUGH. MOUNT 5'-0" AFG. PROVIDE (20) TERMINAL GROUND BAR AND ROUTE #8 BARE, STRANDED CU. CONDUCTOR FROM GROUND BAR TO PANEL 'EDP'. REFER TO DETAIL 3 ON GE-113, AND DETAIL 2 ON GE-116.




REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: ENLARGED SITE ELECTRICAL PLAN AT RAMP E	DRAWING NO. CE-112
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 11

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



GENERAL NOTES:


1. THIS SHEET DEPICTS THE LIGHTNING PROTECTION SYSTEM FOR THE GANTRY. ALL WORK SHALL MEET NFPA 780.
2. SEE TSP SECTION 26 41 13.

REFERENCE NOTES:

- 1 STRANDED COPPER LIGHTNING PROTECTION CONDUCTOR, BONDED TO GANTRY COLUMN AND TO GROUND RING ELECTRODE. REFER TO DRAWING GE-116.
- 2 20' LONG X 5/8" DIAMETER COPPER-CLAD STEEL GROUND ROD.
- 3 BARE, STRANDED-COPPER CONDUCTOR, 36" BELOW FINISHED GRADE. DO NOT ROUTE CONDUCTOR UNDER TOLLING LOOP PAVEMENT.
- 4 LIGHTNING PROTECTION CONDUCTOR (DIRECT BURIED) TO TOLL EQUIPMENT BUILDING GROUND RING ELECTRODE.
- 5 BOND ALL METAL WIRE TROUGHS TO THE UNDERGROUND LIGHTNING PROTECTION GROUND RING ELECTRODE.



NORTH



1 LIGHTNING PROTECTION PLAN - RAMP E
 CE-113 SCALE: 1" = 10'-0"


REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103


STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: LIGHTNING PROTECTION PLAN AT RAMP E	DRAWING NO. CE-113
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 12


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 TOLLING LOOP PULL BOX - TYPICAL PLAN
 CE-114 SCALE: N.T.S.




2 TYPICAL TOLLING LOOP PULL BOX SECTION A-A
 CE-114 SCALE: N.T.S.



CONDUIT I.D. NOTES:

1. CAPPED CONDUIT SHOWN. USE SIMILAR INSTALLATION WITH COUPLING AND URETHANE FOAM PLUG. REFER TO DETAIL 1, THIS SHEET, FOR LANE LOOP STUB-OUT CONDUITS.
2. I.D. TAG TO INCLUDE FOLLOWING INFORMATION:
 NAME OF CONDUIT SYSTEM, INTENDED EQUIPMENT OR DEVICE LOCATED AT OTHER END OF CONDUIT.

3 EMPTY CONDUIT PULL ROPE AND IDENTIFICATION DETAIL
 CE-114 SCALE: N.T.S.



4 LOOP CONDUIT STUB-OUT DETAIL
 CE-114 SCALE: N.T.S.

GENERAL NOTES:

1. SEAL BOTH ENDS OF CONDUIT WITH NON-CONDUCTING SEALING COMPOUND MANUFACTURED FOR THAT PURPOSE.
2. A SINGLE CONTINUOUS SLAB SHALL BE POURED TO ENCOMPASS ALL LOOP PULL BOXES. UON, SLAB SHALL EXTEND A MIN. OF 12" ON ALL SIDES OF PULL BOXES.
3. COORDINATE INSTALLATION OF ALL LOOP CONDUITS AND PULLBOXES WITH ROADWAY AND BARRIER WALL CONSTRUCTION.



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: TOLLING LOOP CONDUIT & PULL BOX DETAILS		DRAWING NO. CE-114
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 13
						SR 429	SEMINOLE	240200-2-52-01		

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

ELECTRICAL SYMBOL LEGEND:

SYMBOL	DESCRIPTION
	CONDUIT UP.
	CONDUIT DOWN.
	HOMERUN TO PANEL - LETTER INDICATES PANEL, NUMBERS INDICATE CIRCUITS. ALL RACEWAYS WITHOUT FURTHER DESIGNATION INDICATE A TWO-WIRE CIRCUIT. FOUR WIRES ARE INDICATED. LONG MARKS INDICATE NEUTRAL CONDUCTOR, SHORT MARKS INDICATE PHASE CONDUCTORS. PROVIDE GREEN GROUND CONDUCTOR IN ALL CONDUITS. (TIE) INDICATES CIRCUIT IS SHARED WITH ADDITIONAL RECEPTACLES.
	DEVICE OR EQUIPMENT AS NOTED
	REFERENCE NOTES
	OUTLET OR JUNCTION BOX, SIZE PER NEC.
	PANELBOARD. (DIRTY POWER)
	SQUARE D POWERLINK PANELBOARD (CRITICAL POWER) PANELBOARD FED VIA UPS
	CONTROL PANEL.
	AUTOMATIC TRANSFER SWITCH.
	SURGE PROTECTION DEVICE.
	PULL BOX.
	EMERGENCY POWER SHUTOFF SWITCH.
	LIGHTNING PROTECTION CONDUCTOR.
	UNDERGROUND GROUND CONDUCTOR.
	CONDUIT RACEWAY EXPOSED.
	CONDUIT RACEWAY CONCEALED IN CEILING SPACE OR WALLS.
	CONDUIT RACEWAY IN CONCRETE SLAB OR UNDERGROUND.
	WIREWAY
	WIREWAY FITTING
	GROUND INSPECTION WELL
	GROUND BUSBAR
	GROUND ROD

GENERAL SYMBOL LEGEND:



ABBREVIATIONS:

A	AMPS
AASHTO	AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS
AC	AIR CONDITIONING [UNIT]
AFF	ABOVE FINISH FLOOR
AFG	ABOVE FINISH GRADE
AL, ALUM.	ALUMINUM
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS
ATS	AUTOMATIC TRANSFER SWITCH
AVI	AUTOMATIC VEHICLE IDENTIFICATION
AWG	AMERICAN WIRE GAUGE
BCU	BATTERY CHARGER UNIT
BLDG.	BUILDING
BPS	BYPASS SWITCH
C	CONDUIT
CCTV	CLOSED CIRCUIT TELEVISION
CKT.	CIRCUIT
COMP	COMPUTER
CU	COPPER
COMM.	COMMUNICATION
DEP	DEPARTMENT OF ENVIRONMENTAL PROTECTION
DIA.	DIAMETER
DN	DOWN
DWG.	DRAWING
E6	ENCOMPASS 6 MULTIPROTOCOL READER
EB	EASTBOUND
ENG.	ENGINE
E.T.C.	ELECTRONIC TOLL COLLECTION
ETC.	ET CETERA
EQUIP.	EQUIPMENT
EPA	ENVIRONMENTAL PROTECTION AGENCY
EPO	EMERGENCY POWER OFF
EXT.	EXTERIOR
FBC	FLORIDA BUILDING CODE
FOC	FIBER OPTIC CABLE
FT	FOOT; FEET
FTE	FLORIDA'S TURNPIKE ENTERPRISE
FTL	FEED THROUGH LUGS
FTM	FUEL TANK MONITOR
FUT	FUTURE
GA	GAUGE
GAL.	GALLON
GEC	GROUNDING ELECTRODE CONDUCTOR
GEN	GENERATOR
GFI	GROUND FAULT INTERRUPTER
GND	GROUND
HID	HIGH INTENSITY DISCHARGE
HP	HORSEPOWER
HZ	HORIZONTAL, HERTZ
I.C.	INTERRUPTING CAPACITY
I.D.	IDENTIFICATION
IN.	INCHES
IPB	INTERMEDIATE PULLBOX
ITS	INTELLIGENT TRANSPORTATION SYSTEM
JB	JUNCTION BOX
KA	KILOAMPERES
KVA	KILOVOLT AMPERES
KW	KILOWATT
LED	LIGHT EMITTING DIODE
LFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT
LN CTR	LANE CONTROLLER
LOC.	LOCATION
LLC	LEAD LAG CONTROLLER
LP	LIGHTNING PROTECTION
LTG	LIGHTING
MAX.	MAXIMUM
MCB	MAIN CIRCUIT BREAKER
MTS	MANUAL TRANSFER SWITCH
MIN.	MINIMUM
ML	MAINLINE
M.L.O.	MAIN LUGS ONLY
MOT	MAINTENANCE OF TRAFFIC
MPB	MEDIAN PULLBOX
MTD	MOUNTED
N	NEUTRAL
NB	NORTHBOUND
N.C.	NORMALLY CLOSED
NEC	NATIONAL ELECTRICAL CODE

ABBREVIATIONS CONT:

NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
NIC	NOT IN CONTRACT
NO.	NUMBER
N.O.	NORMALLY OPEN
N.T.S.	NOT TO SCALE
N3R	NEMA 3R
OC	ON CENTER
ORT	OPEN ROAD TOLLING
Ø	PHASE
P	POLE
PB	PULLBOX
PCB	POLYCHLORINATED BIPHENYL
PNL	PANEL
PTZ	PAN-TILT-ZOOM
PVC	POLYVINYL CHLORIDE
RECEPT.	RECEPTACLE
RGS	RIGID GALVANIZED STEEL
RMS	ROOT MEAN SQUARED
SB	SOUTHBOUND
SCADA	SUPERVISORY CONTROL & DATA ACQUISITION
SCH.	SCHEDULE
SCP	SCADA CONTROL PANEL
SCTE	SOCIETY OF CABLE TELECOMMUNICATIONS ENGINEERS
SD	SQUARE D
SER	SERVICE ENTRANCE RATED
SPD	SURGE PROTECTIVE DEVICE
SPEC(S)	SPECIFICATION(S)
S.P.S.T.	SINGLE POLE SINGLE THROW
S.S.	STAINLESS STEEL
STP	SHIELDED TWISTED PAIR
SQ.	SQUARE
STFE	STATE TOLL FACILITY ENGINEER
SYMM.	SYMMETRICAL
T.E.C.	TOLL EQUIPMENT CONTRACTOR
T&H	TEMPERATURE AND HUMIDITY SENSOR
T.O.	TOLL OPERATIONS
TSP	TECHNICAL SPECIAL PROVISIONS
TYP.	TYPICAL
UL	UNDERWRITERS LABORATORIES
UON	UNLESS OTHERWISE NOTED
UPS	UNINTERRUPTIBLE POWER SUPPLY
V	VOLTS
VAC	VOLTS ALTERNATING CURRENT
VDAC	VEHICLE DETECTION AND CLASSIFICATION UNIT
VES	VIOLATION ENFORCEMENT SYSTEM
VSS	VIDEO SURVEILLANCE SYSTEM
W	WIRE; WATT
W/	WITH
WB	WESTBOUND
WP	WEATHERPROOF (NEMA 3R)
XFMR	TRANSFORMER


REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ELECTRICAL SYMBOL LEGEND AND ABBREVIATIONS		DRAWING NO. CE-201
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 14
						SR 429	SEMINOLE	240200-2-52-01		

ELECTRICAL GENERAL NOTES:

1. FEED ALL RECEPTACLES AND DEVICES WITH (2) #12, (1) #12 GND IN 3/4" C, UON.
2. PROVIDE AN EQUIPMENT GROUNDING CONDUCTOR IN ALL FEEDER AND BRANCH CIRCUIT RACEWAYS.
3. ALL 120V, 20A CIRCUIT HOMERUNS OVER 50FT. SHALL BE #10 CU MINIMUM, UON.
4. ALL 120V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #8 CU MINIMUM, UON.
5. ALL 240V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #10 CU. MINIMUM, UON.
6. ALL 240V, 20A CIRCUIT HOMERUNS OVER 300FT. SHALL BE #8 CU MINIMUM, UON.
7. VERIFY EXACT LOCATION OF ALL MECHANICAL EQUIPMENT WITH MECHANICAL INSTALLER PRIOR TO ROUGH-IN.
8. PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT AND RACEWAYS WITH LABELING AT EACH END. REFER TO DETAIL 3, DWG. CE-214.
9. THE USE OF ANY PROCESS INVOLVING ASBESTOS OR PCB, AND THE INSTALLATION OF ANY PRODUCT, INSULATION, COMPOUND OR MATERIAL CONTAINING OR INCORPORATING ASBESTOS OR PCB, IS PROHIBITED. PROVIDE A COMPLETE AND PROPERLY OPERATING ELECTRICAL SYSTEM WITHOUT THE USE OF ASBESTOS OR PCB.
10. CONTACT THE POWER COMPANY AND TELEPHONE COMPANY WITHIN 10 BUSINESS DAYS OF THE AWARD OF THE CONTRACT AND SCHEDULE NEW SERVICE INSTALLATION.
11. CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID. SUBMISSION OF A BID WILL BE CONSTRUED AS EVIDENCE THAT SUCH EXAMINATION HAS BEEN MADE AND LATER CLAIMS FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WILL NOT BE RECOGNIZED.
12. INCLUDE THE TRANSPORT AND DISPOSAL OR RECYCLING OF ALL WASTE MATERIALS GENERATED BY THIS PROJECT IN ACCORDANCE WITH ALL RULES, REGULATIONS AND GUIDELINES APPLICABLE.
 - A) COMPLY FULLY WITH FLORIDA STATUTE 403.7186 REGARDING MERCURY CONTAINING DEVICES AND LAMPS.
 - B) TRANSPORT AND DISPOSE OF LAMPS, BALLASTS AND OTHER MATERIALS IN ACCORDANCE WITH ALL DEP AND EPA GUIDELINES.
 - C) PROVIDE WRITTEN CERTIFICATION THAT ALL MATERIALS WERE RECYCLED OR DISPOSED OF PROPERLY PER THE GUIDELINES NOTED ABOVE.
13. LOCATE EXISTING UTILITIES AND PROTECT THEM FROM DAMAGE.
14. PHASE WORK AS REQUIRED BY MOT PLANS.
15. UNDERGROUND CONDUIT SHALL BE PVC SCH. 80, UON. UNDERGROUND CONDUIT SHALL TRANSITION TO RGS CONDUIT WITH PVC TO RGS CONDUIT FITTINGS. CONDUIT SHALL BE RGS ABOVE GRADE THROUGH AND INCLUDING THE FIRST 90 DEGREE FITTING UNDERGROUND UON. APPLY 2-COAT BITUMASTIC COATING TO DIRECT BURIED PORTION OF RGS CONDUIT, UP TO AND INCLUDING 6" ABOVE FINAL GRADE. REFER TO TSP FOR FURTHER INFORMATION.
16. TOLL EQUIPMENT AND ALL WIRING/CABLING FOR TOLL EQUIPMENT WILL BE FURNISHED AND INSTALLED BY T.E.C., UON.
17. UNDERGROUND CONDUITS SHALL BE INSTALLED A MINIMUM OF 36" BELOW GRADE.
18. EXPOSED EXTERIOR CONDUIT SHALL BE RGS THROUGH AND INCLUDING THE FIRST 90° BEND INSTALLED UNDERGROUND. TRANSITIONS BETWEEN RGS AND PVC CONDUIT SHALL BE MADE WITH A RGS TO PVC CONDUIT FITTING.
19. EQUIPMENT SPECIFIED WITH CATALOG NUMBERS OR PART NUMBERS SHALL NOT BE SUBSTITUTED UNLESS "OR EQUAL" IS INDICATED.
20. CONDUIT RESERVED FOR TOLLING LOOPS SHALL BE SCH. 80 PVC.
21. PLASTIC END CAPS SHALL BE INSTALLED ON ENDS OF UNISTRUT.
22. ALL LIQUID-TIGHT, FLEXIBLE CONDUIT SHALL BE METALLIC.
23. ADJUST THE LOCATIONS OF THE SPD'S SUCH THAT THE MAXIMUM SPD BRAIDED/TWISTED LEADS LENGTH DO NOT EXCEED 24 INCHES AND HAVE NO SHARP TURNS.
24. AC OR DC ELECTRICAL CIRCUITS OR WIRING THAT OPERATES AT 25 VOLTS OR GREATER SHALL NOT BE INSTALLED AND/OR LOCATED WITHIN 5 FEET OF ANY TRAFFIC DETECTION LOOP OR LOOP PULL BOX.
25. MAINLINE GANTRY DATA WIRE TROUGHS SHALL BE MODIFIED BY A UL OR ETL LISTED PANEL SHOP. THE WIREWAYS TERMINATED TO THE TOP OF THE WIRE TROUGH SHALL BE MODIFIED AND ASSEMBLED IN THE PANEL SHOP & NOT IN THE FIELD TO ENSURE PROPER WATERTIGHT SEAL. SHOP DRAWINGS INCLUDING DIMENSIONED SKETCHES & MATERIAL PRODUCT DATA SHALL BE SUBMITTED FOR REVIEW FOR FABRICATION OF DATA WIRE TROUGH. REFER TO MAINLINE GANTRY DETAILS FOR ADDITIONAL REQUIREMENTS.
26. CONDUIT BENDS SHALL NOT EXCEED 270° BETWEEN PULL POINTS.
27. OUTLET AND DEVICE JUNCTION BOXES INSTALLED OUTDOORS SHALL BE MANUFACTURED FROM GALVANIZED CAST IRON WITH THREADED HUBS, UON. REFER TO TSP SECTION 26 05 33 FOR DETAILS.
28. REFER TO CIVIL PLANS FOR TOLL FACILITY SITE LOCATIONS.
29. THESE PLAN SHALL BE READ IN CONJUNCTION WITH ALL COMPONENTS OF THE ROADWAYS PLANS, TOLL FACILITIES GANTRY PLANS, TOLL FACILITY BUILDING PLANS, SIGNING & PAVEMENT MARKING PLANS, ITS PLANS AND LIGHTING PLANS.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	ELECTRICAL GENERAL NOTES	CE-202
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 SITE ELECTRICAL PLAN – RAMP F
 CE-211 SCALE: 1" = 20'-0"


REFERENCE NOTES:

- 1 PROPOSED BURIED PRIMARY CIRCUITING BY POWER COMPANY. REFER TO UTILITY ADJUSTMENT SHEETS FOR CONTINUATION AND DETAILS. THE ELECTRICAL CONTRACTOR SHALL CONTACT THE UTILITY COMPANY (FP&L, GARRETT PETERSON, 407-328-1934) WITHIN TWO WEEKS OF NTP TO ENSURE ELECTRICAL SERVICE IS AVAILABLE WHEN CONSTRUCTION OF THE TOLL BUILDING IS COMPLETE. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR PAYING THE POWER COMPANY TO BRING POWER TO THE TRANSFORMER (PRIMARY).
- 2 UNDERGROUND SERVICE LATERAL, SEE DWG. AE-130. THE CONTRACTOR SHALL RUN SERVICE LATERAL AROUND, BUT NOT UNDER, LARGE PIECES OF EQUIPMENT AND/OR BUILDING FOOTERS. CONTRACTOR SHALL PAY FOR COSTS ASSOCIATED WITH THE INSTALLATION OF THE ELECTRICAL SERVICE FROM THE SECONDARY LUGS OF THE UTILITY XFMR TO AND INCLUDING THE SERVICE DISCONNECTING MEANS, GROUNDING, METER SOCKET AND OTHER WORK AS SPECIFIED.



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	SITE ELECTRICAL PLAN AT RAMP F	CE-211
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 16

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




1 ENLARGED SITE ELECTRICAL PLAN - RAMP F
 CE-212 SCALE: 1" = 5'-0"

REFERENCE NOTES:

- ① SERVICE LATERAL. REFER TO POWER RISER DIAGRAM ON DWG. AE-130 FOR DETAILS.
- ② POWER CIRCUITING FROM GENERATOR CIRCUIT BREAKER (GCB) TO ATS. REFER TO POWER RISER DIAGRAM, DWG. AE-130.
- ③ 1" CONDUIT FOR BATTERY CHARGING CIRCUIT, 2 #6 (COLOR RED FOR +12V, COLOR BLACK FOR -12V), TYPE MTW CONDUCTORS.
- ④ 1" CONDUIT FOR JACKET WATER HEATER CIRCUITING. REFER TO PANEL SCHEDULE, DWG. AE-131.
- ⑤ (1) 1-1/2" CONDUIT FROM GENERATOR CONTROL PANEL TO SCADA PANEL. REFER TO DWG. AE-133.
- ⑥ (1) 1-1/2" CONDUIT FOR SCADA CONNECTIONS. REFER TO DWG. AE-133.
- ⑦ 2 #14 (GENSET RUN), 4 #14 (SPARE), 1 #14 GND. 1" C.
- ⑧ 4" X 4" WEATHERPROOF CAST IRON BOX WITH A GASKETED COVER, APPLETON CATALOG # FSD-2-75 OR APPROVED EQUAL.
- ⑨ 1" CONDUIT. REFER TO PANEL SCHEDULE, DWG. AE-131.
- ⑩ (1) COMMUNICATION CABLE IN 1" C. FROM GENERATOR CONTROL PANEL TO EPO STATION ON EXTERIOR WALL OF ENTRANCE DOOR. REFER TO DETAIL 3, DWG. AE-120.


- ⑪ MOUNT TOP OF EQUIPMENT 5'-0" AFG ON UNISTRUT SUPPORT STRUCTURE. SEE DETAIL 3 ON DRAWING GE-213.
- ⑫ PROVIDE (2) 2" C WITH PULL STRING FOR FOC NETWORK CONNECTIONS. EXTEND CONDUITS 5'-0" BEYOND CONCRETE EDGE AND CAP. CONDUIT CONTINUATION & FOC WILL BE INSTALLED BY ITS CONTRACTOR.
- ⑬ (4) 3" CONDUIT (LOOPS).
- ⑭ (4) 2" CONDUIT (POWER).
- ⑮ (3) 4" CONDUIT (DATA).
- ⑯ (2) 4" CONDUIT (E6).
- ⑰ (2) 2" CONDUIT (CCTV).
- ⑱ (1) 1" C. (POWER FOR PTZ CAMERA).
- ⑲ (1) 3" CONDUIT (LOOPS).
- ⑳ GROUNDING ELECTRODE SYSTEM. REFER TO DWG. AE-121 AND AE-130.
- ㉑ PROVIDE 24"x36"x24" POLYMER CONCRETE PULLBOX WITH COVER STAMPED "ITS INTERFACE". PULLBOX AND COVER SHALL BE MINIMUM UL LISTED, ANSI/STCE 77 LOAD COMPLIANT, AND ANSI TIER 15 RATED.

- ㉒ (2) 2" C. WITH PULL STRING FOR COMMUNICATION SERVICE CONNECTIONS.
- ㉓ PROVIDE 24"x36"x24" POLYMER CONCRETE PULLBOX WITH COVER STAMPED "TELCO COMMUNICATIONS" FOR COMMUNICATION SERVICE. PULLBOX AND COVER SHALL BE MINIMUM UL LISTED, ANSI TIER 15 RATED.
- ㉔ PROVIDE (2) 2" C. FOR TELCO COMMUNICATION SERVICE. EXTEND CONDUIT 5'-0" BEYOND CONCRETE EDGE FOR FUTURE CONNECTION BY OTHERS.
- ㉕ 90 DEGREE WIREWAY FITTING. FITTING SHALL BE UL LISTED FOR HORIZONTAL TO VERTICAL TRANSITION. REFER TO TSP 26 05 34.
- ㉖ 6" X 6" FEED THROUGH WIREWAY. REFER TO TSP 26 05 34 FOR WIREWAY RATING AND DETAILS.
- ㉗ PROVIDE FLEXIBLE FITTING TO COMPENSATE FOR MISALIGNMENT, STRETCH LENGTH RANGE FROM 3-1/2" TO 12", HYPALON BELLOW WITH STAINLESS STEEL FLANGES.
- ㉘ 12" X 12" X 24" NEMA 3R POWER WIRE TROUGH. MOUNT 5'-0" AFG. PROVIDE (20) TERMINAL GROUND BAR AND ROUTE #8 BARE, STRANDED CU. CONDUCTOR FROM GROUND BAR TO PANEL 'EDP'. REFER TO DETAIL 3 ON GE-213, AND DETAIL 2 ON GE-216.



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ENLARGED SITE ELECTRICAL PLAN AT RAMP F		DRAWING NO. CE-212
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 17
					SR 429	SEMINOLE	240200-2-52-01			

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




GENERAL NOTES:

1. THIS SHEET DEPICTS THE LIGHTNING PROTECTION SYSTEM FOR THE GANTRY. ALL WORK SHALL MEET NFPA 780.
2. SEE TSP SECTION 26 41 13.

REFERENCE NOTES:


- 1 STRANDED COPPER LIGHTNING PROTECTION CONDUCTOR, BONDED TO GANTRY COLUMN AND TO GROUND RING ELECTRODE. REFER TO DRAWING GE-216.
- 2 20' LONG X 5/8" DIAMETER COPPER-CLAD STEEL GROUND ROD.
- 3 BARE, STRANDED-COPPER CONDUCTOR, 36" BELOW FINISHED GRADE. DO NOT ROUTE CONDUCTOR UNDER TOLLING LOOP PAVEMENT.
- 4 LIGHTNING PROTECTION CONDUCTOR (DIRECT BURIED) TO TOLL EQUIPMENT BUILDING GROUND RING ELECTRODE.
- 5 BOND ALL METAL WIRE TROUGHS TO THE UNDERGROUND LIGHTNING PROTECTION GROUND RING ELECTRODE.

1 LIGHTNING PROTECTION PLAN - RAMP F
 CE-213 SCALE: 1" = 10'-0"




REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: LIGHTNING PROTECTION PLAN AT RAMP F		DRAWING NO. CE-213
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 18
					SR 429	SEMINOLE	240200-2-52-01			


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 TOLLING LOOP PULL BOX - TYPICAL PLAN
 CE-214 SCALE: N.T.S.




2 TYPICAL TOLLING LOOP PULL BOX SECTION A-A
 CE-214 SCALE: N.T.S.



3 EMPTY CONDUIT PULL ROPE AND IDENTIFICATION DETAIL
 CE-214 SCALE: N.T.S.

CONDUIT I.D. NOTES:

- CAPPED CONDUIT SHOWN. USE SIMILAR INSTALLATION WITH COUPLING AND URETHANE FOAM PLUG. REFER TO DETAIL 1, THIS SHEET, FOR LANE LOOP STUB-OUT CONDUITS.
- I.D. TAG TO INCLUDE FOLLOWING INFORMATION: NAME OF CONDUIT SYSTEM, INTENDED EQUIPMENT OR DEVICE LOCATED AT OTHER END OF CONDUIT.



4 LOOP CONDUIT STUB-OUT DETAIL
 CE-214 SCALE: N.T.S.

GENERAL NOTES:

- SEAL BOTH ENDS OF CONDUIT WITH NON-CONDUCTING SEALING COMPOUND MANUFACTURED FOR THAT PURPOSE.
- A SINGLE CONTINUOUS SLAB SHALL BE POURED TO ENCOMPASS ALL LOOP PULL BOXES. UON, SLAB SHALL EXTEND A MIN. OF 12" ON ALL SIDES OF PULL BOXES.
- COORDINATE INSTALLATION OF ALL LOOP CONDUITS AND PULLBOXES WITH ROADWAY AND BARRIER WALL CONSTRUCTION.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	TOLLING LOOP CONDUIT & PULL BOX DETAILS	CE-214
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME:	SHEET NO.
							SR 429 WEKIVA PARKWAY SECTION 7A	19	

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

STATE OF FLORIDA
DEPARTMENT OF TRANSPORTATION

CONTRACT PLANS

FINANCIAL PROJECT ID 240200-2-52-01
(FEDERAL FUNDS)
SEMINOLE COUNTY (77320)

INDEX OF TOLL FACILITIES - BUILDING PLANS

SHEET NO.	DRAWING NO.	BUILDING PERMIT SET	SHEET DESCRIPTION
-----------	-------------	---------------------	-------------------

STATE ROAD NO. 429 (WEKIVA PARKWAY SECTION 7A)

1	AG-001	A / B	Key Sheet
2	AG-002	----	Signature Sheet

ARCHITECTURAL PLANS

3	AG-100		Symbols Legend and Notes
4	AG-101	A	Gantry Equipment Building Code data and Life Safety Plan
5	AA-101	B	Floor Plan at Ramp E
6	AA-102	----	Reflected Ceiling Plan & Roof Plan at Ramp E
7	AA-103	----	Floor Plan at Ramp F
8	AA-104	A	Reflected Ceiling Plan & Roof Plan at Ramp F
9	AA-201	B	Building Elevations
10	AA-301		Building Wall Sections
11	AA-501		Building Door Details
12	AA-601		Door Schedule, Door and Door Frame Types

STRUCTURAL PLANS

13	AS-001		Structural General Notes
14	AS-100		Plans
15	AS-200		Exterior Elevations
16	AS-300		Sections and Details
17	AS-301		Sections and Details

MECHANICAL PLANS

18	AM-001		HVAC General Notes and Legend
19	AM-101		HVAC Floor Plan at Ramp E
20	AM-102		HVAC Floor Plan at Ramp F
21	AM-501		Mechanical Details
22	AM-502		Generator Plan Elevation Detail and Notes
23	AM-503		Fuel Tank Anchoring Details

ELECTRICAL PLANS

24	AE-010		Electrical Symbols, Legend and Abbreviations
25	AE-011		Electrical General Notes
26	AE-101		Building - Power Plan at Ramp E
27	AE-102		Building - Lighting Plan at Ramp E
28	AE-103		Building - Lightning Protection Plan at Ramp E
29	AE-104		Building - Scada and Security System Plan at Ramp E
30	AE-105		Building - Tolling System Plan at Ramp E
31	AE-106		Building - Power Plan at Ramp F
32	AE-107		Building - Lighting Plan at Ramp F
33	AE-108		Building - Lightning Protection Plan at Ramp F
34	AE-109		Building - Scada and Security System Plan at Ramp F
35	AE-110		Building - Tolling System Plan at Ramp F
36	AE-111		Building - Tolling Communication Cabinet Detail
37	AE-112		Building - Interior Elevations (1 of 3)
38	AE-113		Building - Interior Elevations (2 of 3)
39	AE-114		Building - Interior Elevations (3 of 3)
40	AE-120		Building - Electrical Details
41	AE-121		Building - Grounding Details (1 of 2)
42	AE-122		Building - Grounding Details (2 of 2)
43	AE-123		Building - Lightning Protection Details
44	AE-124		Building - Security and Access Control System Details
45	AE-125		Building - Raceway Installation Details
46	AE-126		Building - Conduit Stub-up Details
47	AE-130		Building - Power Riser Diagram
48	AE-131		Building - Panel Schedules and Load Summary
49	AE-132		SCADA System Block Diagram Notes
50	AE-133		SCADA System Block Diagram

TOLL FACILITIES - BUILDING PLANS

TOLL FACILITIES-BUILDING PLANS
ENGINEER OF RECORD:

SUSAN FUNK NUTE, AR
AR No.: 11913
AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
Phone (813) 286-1711
CONTRACT NO. C-9855
VENDOR NO. F952661922
CERTIFICATE OF AUTHORIZATION NO. 00008115

FDOT PROJECT MANAGER:

KEVIN MOSS, P.E.

DRAWING
NO.


AG-001

CONSTRUCTION CONTRACT NO.	FISCAL YEAR	SHEET NO.
---------------------------	-------------	-----------


T5626

18

1



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:




PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM TECHNICAL SERVICES, INC.
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 SUSAN FUNK NUTE, A.R. NO. 11913

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G1-16.005, F.A.C.

TOLL FACILITIES - BUILDING PLANS

SHEET NO.	DRAWING NO.	SHEET DESCRIPTION
1	AG-001	Key Sheet
2	AG-002	Signature Sheet
3	AG-100	Symbols Legend and Notes
4	AG-101	Gantry Equipment Building Code data and Life Safety Plan
5	AA-101	Floor Plan at Ramp E
6	AA-102	Reflected Ceiling Plan & Roof Plan at Ramp E
7	AA-103	Floor Plan at Ramp F
8	AA-104	Reflected Ceiling Plan & Roof Plan at Ramp F
9	AA-201	Building Elevations
10	AA-301	Building Wall Sections
11	AA-501	Building Door Details
12	AA-601	Door Schedule, Door and Door Frame Types



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:




PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM Technical Services, Inc.,
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 GEORGE R. PAPADOPOULOS, P.E. NO. 55843

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.

TOLL FACILITIES - BUILDING PLANS

SHEET NO.	DRAWING NO.	SHEET DESCRIPTION
2	AG-002	Signature Sheet
13	AS-001	Structural General Notes
14	AS-100	Plans
15	AS-200	Exterior Elevations
16	AS-300	Sections and Details
17	AS-301	Sections and Details



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:




PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM Technical Services, Inc.,
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 PETER J. PASTORE, P.E. NO. 77103

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.

TOLL FACILITIES - BUILDING PLANS

SHEET NO.	DRAWING NO.	SHEET DESCRIPTION
2	AG-002	Signature Sheet
24	AE-010	Electrical Symbols, Legend and Abbreviations
25	AE-011	Electrical General Notes
26	AE-101	Building - Power Plan at Ramp E
27	AE-102	Building - Lighting Plan at Ramp E
28	AE-103	Building - Lightning Protection Plan at Ramp E
29	AE-104	Building - Scada and Security System Plan at Ramp E
30	AE-105	Building - Tolling System Plan at Ramp E
31	AE-106	Building - Power Plan at Ramp F
32	AE-107	Building - Lighting Plan at Ramp F
33	AE-108	Building - Lightning Protection Plan at Ramp F
34	AE-109	Building - Scada and Security System Plan at Ramp F
35	AE-110	Building - Tolling System Plan at Ramp F
36	AE-111	Building - Tolling Communication Cabinet Detail
37	AE-112	Building - Interior Elevations (1 of 3)
38	AE-113	Building - Interior Elevations (2 of 3)
39	AE-114	Building - Interior Elevations (3 of 3)
40	AE-120	Building - Electrical Details
41	AE-121	Building - Grounding Details (1 of 2)
42	AE-122	Building - Grounding Details (2 of 2)
43	AE-123	Building - Lightning Protection Details
44	AE-124	Building - Security and Access Control System Details
45	AE-125	Building - Raceway Installation Details
46	AE-126	Building - Conduit Stub-up Details
47	AE-130	Building - Power Riser Diagram
48	AE-131	Building - Panel Schedules and Load Summary
49	AE-132	SCADA System Block Diagram Notes
50	AE-133	SCADA System Block Diagram



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:



PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM TECHNICAL SERVICES, INC.
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 MICHAEL J. OVER, P.E. NO. 65665

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.

TOLL FACILITIES - BUILDING PLANS

SHEET NO.	DRAWING NO.	SHEET DESCRIPTION
2	AG-002	Signature Sheet
18	AM-001	HVAC General Notes and Legend
19	AM-101	HVAC Floor Plan at Ramp E
20	AM-102	HVAC Floor Plan at Ramp F
21	AM-501	Mechanical Details
22	AM-502	Generator Plan Elevation Detail and Notes
23	AM-503	Fuel Tank Anchoring Details

REVISIONS

DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 C.A. No. 8115
 Susan Funk Nute, AR No. 11913

STATE OF FLORIDA
 DEPARTMENT OF TRANSPORTATION

ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SIGNATURE SHEET
(BUILDING PLANS)

DRAWING NO.
AG-002
 SHEET NO.
2

ARCHITECTURAL PROJECT NOTES

- GENERAL CONTRACTOR, PERMIT HOLDER AND/OR QUALIFYING AGENT MUST COMPLY WITH LATEST EDITION OF THE FTE TOLL EQUIPMENT BUILDING CODE COMPLIANCE PROCEDURES FOR OBTAINING CERTIFICATE OF OCCUPANCY OR COMPLETION DOCUMENTS FROM BCAS (BUILDING CODE ADMINISTRATOR SERVICES) AS REFERENCED IN THE GENERAL TOLLING REQUIREMENTS, FOR ALL PERMITTING AND INSPECTIONS RELATED TO TOLL EQUIPMENT BUILDING CONSTRUCTION AND/OR DEMOLITION.
- ALL TOLL EQUIPMENT BUILDING MANUFACTURERS SUPPLYING TOLL EQUIPMENT BUILDINGS FOR FDOT MUST BE DBPR CERTIFIED MANUFACTURERS. THE MANUFACTURER'S CURRENT DBPR CERTIFICATE MUST BE PROVIDED TO BCAS AT THE TIME OF SUBMISSION OF THE PLANS FOR BCAS REVIEW.
- THE 100% APPROVED FDOT CONSTRUCTION DOCUMENTS FOR MANUFACTURED TOLL EQUIPMENT BUILDINGS MUST BE SUBMITTED TO DBPR OR IT'S "THIRD PARTY AGENCY" FOR REVIEW AND APPROVAL.
- THE DBPR-APPROVED PLANS MUST BE AVAILABLE ON THE DBPR WEBSITE FOR CERTIFICATION VERIFICATION (CURRENTLY, [HTTP://FLORIDABUILDING.ORG/CD/DEFAULT.ASPX](http://FLORIDABUILDING.ORG/CD/DEFAULT.ASPX)).
- ANY CODE CHANGES MADE TO DBPR-APPROVED PLANS WILL MAKE THE PLANS OBSOLETE UNTIL THEY HAVE BEEN REVIEWED, APPROVED FOR CODE COMPLIANCE BY DBPR OR IT'S "THIRD PARTY AGENCY" AND RE-POSTED ON THE DBPR WEBSITE.
- ALL BUILDING CODE COMPLIANCE INSPECTIONS MUST BE CONDUCTED AT THE MANUFACTURER BY DBPR OR ITS "THIRD PARTY AGENCY" TO ENSURE THE STRUCTURES ARE BEING BUILT TO THE SPECIFIC, DBPR-APPROVED PLANS.
- ALL MANUFACTURED TOLL EQUIPMENT BUILDINGS MUST BEAR THE DBPR INSIGNIA, VERIFYING DBPR CERTIFICATION AND INSPECTION.
- NO ROOFING INSPECTION CONDUCTED BY BCAS, INC. WILL BE REQUIRED, PROVIDED THAT THE ROOF IS INSTALLED AT THE TEB MANUFACTURER BY A MANUFACTURER-APPROVED INSTALLER AND A PROGRESS INSPECTION IS CONDUCTED BY THE ROOFING MANUFACTURER TO CERTIFY AND WARRANTY THE ROOF.
- IF THE ROOFS WILL BE INSTALLED AT THE JOB SITE, BCAS, INC. WILL NEED TO CONDUCT ITS OWN "IN PROGRESS" AND FINAL ROOF INSPECTIONS TO CERTIFY COMPLIANCE.
- THE BUILDING MANUFACTURER MUST ALSO CERTIFY THAT THEY HAVE BUILT THESE TOLL EQUIPMENT BUILDINGS IN ACCORDANCE WITH THE 100%-APPROVED FDOT CONSTRUCTION DOCUMENTS FOR THESE SPECIFIC TOLL EQUIPMENT BUILDINGS. THEY MUST ALSO WARRANTY THESE BUILDINGS.
- IF ANY OF THESE ITEMS HAVE NOT BEEN ADHERED TO, THE BUILDING OFFICIAL, HAS JURISDICTION UNDER FLORIDA STATUTE 553.791 (13) TO "RED TAG" ANY JOB UNTIL SAID DEFICIENCIES HAVE BEEN SATISFACTORILY ADDRESSED OR RECTIFIED.
- ARCHITECTURAL PROJECT NOTES APPLY TO ALL ARCHITECTURAL DRAWINGS.
- GENERAL NOTES AND SPECIFIC KEYED NOTES APPLY ONLY TO THE SHEET ON WHICH THEY APPEAR.
- CONTRACTOR SHALL COMPLY WITH GOVERNING CODES AND LOCAL REGULATIONS.
- DO NOT SCALE DRAWINGS.
- CONTRACTOR SHALL FIELD VERIFY ALL CONDITIONS AND DIMENSIONS PRIOR TO COMMENCING ANY WORK AND SHALL BE RESPONSIBLE FOR COORDINATION OF ALL DIMENSIONS, WORK AND MATERIALS REQUIRED.
- CONTRACTOR SHALL REPORT ANY DISCREPANCIES PRIOR TO THE START OF CONSTRUCTION ON THE AFFECTED ITEM.

SECURITY NOTES

- ACCESS TO SITE: COORDINATE WITH THE DEPARTMENT FOR ACCESS REQUIREMENTS FOR ALL EMPLOYEES AND EQUIPMENT OF THE CONTRACTOR AND OR SUB-CONTRACTORS.

DIMENSION NOTES


- ALL DIMENSIONS ARE ACTUAL AND ARE TO FACE OF CONCRETE WALLS, FACE OF MASONRY WALLS, FACE OF FRAME (ON FRAME WALLS) OR CENTERLINE OF COLUMNS, UNLESS NOTED OTHERWISE.

ABBREVIATIONS

- ABBREVIATIONS APPLY TO DRAWING SHEETS. ADDITIONAL ABBREVIATIONS NOT NOTED BELOW MAY OCCUR ON OTHER DRAWING SHEETS.
- WORDS MAY OCCUR AS ABBREVIATIONS OR SPELLED OUT IN FULL.
- THE CONTRACTOR SHALL BE FAMILIAR WITH THE ABBREVIATIONS AS LISTED BELOW.
- ABBREVIATIONS FOLLOWED BY AN "S" INDICATE THE WORD HAS BEEN MADE PLURAL.

AIR CONDITIONING UNIT	ACU	FOOTING	FTG	PLATE	PL
AIR CONDITIONING	A/C	FRAME	F	POLYVINYL CHLORIDE	PVC
ABOVE FINISH FLOOR	AFF	FRONT AND BACK	F/B	POUNDS	LBS
ADDITIONAL	ADDNL	GALVANIZED	GALV	POUNDS PER SQUARE INCH	PSI
ALUMINUM	ALUM	GAS	G	POINT OF TANGENCY	P.T.
ANCHOR	ANC	GAS METER	GM	PRESSURE TREATED	PT
ANCHOR BOLT	AB			RADIUS	RAD
ASPHALT	ASPH	GLAZING	GLZ	REFERENCE	RE
AUXILIARY	AUX	GRADE	GR	REINFORCING	REINF
AVERAGE	AVG	GROUND	GND	REINFORCING BAR	REBAR
BETWEEN	B/W	GROUND FAULT INTERRUPTER	GFI	REQUIRED	REQD
BLOCK	BLK	GYP SUM BOARD	GYP BD	REVISED	REV
BOTTOM	BOT	HEATER VENT	HV	ROOF DRAIN	RD
BUILDING	BLDG	HEIGHT	HT	ROADWAY	RDWY
BUILDING LINE	BL	HIGH INTENSITY DISCHARGE	HID	ROOM	RM
CAST IRON	CI	HORIZONTAL	HORIZ	SCHEDULE	SCH
CENTERLINE	CL	HEIGHT	HT	SECOND	SEC
CENTER TO CENTER	C TO C	INSIDE DIAMETER	ID	SECTION	SECT
CEILING HEIGHT	CH	INCH	IN	SHEET	SHT
CIRCUIT	CKT	INFORMATION	INFO	SIDEWALK	S/W
CLEARANCE	CLR	INSIDE DIAMETER	ID	SIMILAR	SIM
COLUMN	COL	INVERT	INV	SOUTH	S
CONCRETE	CONC	IRON PIPE	IP	SOUTHEAST	SE
CONCRETE MASONRY UNIT	CMU	JOINT	JT	SOUTHWEST	SW
CONSTRUCTION	CONST	JUNCTION BOX	JB	SPECIFICATION	SPEC
CONSTRUCTION DOCUMENTS	CD	KIPS	K	SQUARE	SQ
CONTROL JOINT	CJ	KIPS PER SQUARE INCH	KSI	SQUARE FEET	SF
CONTINUOUS	CONT	KILOVOLT-AMPERES	KVA	STANDARD	STD
COPPER	CU	LAVATORY	LAV	STAINLESS STEEL	SS
CUBIC INCH	CI	LIGHT	LT	STEEL	STL
DETAIL	DET	LIGHTWEIGHT	LT WT	STIRRUP	STR
DIAMETER	DIA OR Ø	LENGTH	L	STREET	ST
DIAGONAL	DIAG	LIGHTING	LTG	SWITCH	SWT
DIMENSION	DIM	LINEAR	LIN	SYMMETRICAL	SYM
DISTANCE	DIST	LINEAR FEET	LF	TANGENT	TAN
DOWN	DN	LONG	LG	TELEPHONE	TELE
DOWNSPOUT	DS	MATERIAL	MATL	TEMPORARY	TEMP
DRAWING	DWG	MANUFACTURER	MANUF	THICKNESS	THK
DRINKING FOUNTAIN	DF	MAXIMUM	MAX	TOP AND BOTTOM	T/B
DRIVE	DR	MEAN SEA LEVEL	MSL	TOP FACE	T/F
EACH	EA	MECHANICAL	MECH	TOP OF CONCRETE	T/C
EACH WAY	EW	MEDIUM	MED	TOP OF CURB	TC
EAST/EASTING	E	METAL	MTL	TOP OF SLAB	T/S
ELEVATION	EL OR ELEV	MINIMUM	MIN	TOP OF STEEL	T/STL
ELECTRICAL	ELEC	MISCELLANEOUS	MISC	TYPICAL	TYP
EQUIPMENT	EQUIP	NORTH/NORTHING	N	UNLESS NOTED OTHERWISE	UNO
EQUAL	EQ	NORTHEAST	NE	UNDERWRITERS LABORATORIES INC.	UL
EXHAUST FAN	EX	NORTHWEST	NW	URINAL	UR
EXISTING	EXIST	NOT APPLICABLE	N/A	VARIABLE	VAR
EXPANSION JOINT	EJ	NOT IN CONTRACT	NIC	VENT THRU ROOF	VTR
EXPOSED STRUCTURE	EXP STR	NOT TO SCALE	NTS	VERIFY IN FIELD	VIF
EXTERIOR	EXT	NUMBER	#	VERTICAL	VERT
FEEDER	FDR	ON CENTER	O/C	WATER LINE	WL
FEET	FT	OPPOSITE	OPP	WATER CLOSET	WC
FINISH FLOOR ELEVATION	FFE	OUTSIDE DIAMETER	OD	WIDTH	W
FIRE EXTINGUISHER	FE	OVERHEAD	OH	WITH	W/
FLOOR	FL	PANEL	PNL	WITHOUT	W/O
FLOOR DRAIN	FD	PAVEMENT	PVMT	WOOD	WD
FOOT	FT	PERCENT	%		

END CONSTRUCTION SEC 7A
 £ CONST EB FRONTAGE ROAD STA 2164+51.29
 £ CONST WB FRONTAGE ROAD STA 3178+40.66



**LOCATION MAP
NTS**

SYMBOLS LEGEND

	KEYED NOTES		INDICATES DIRECTION OF CUTTING PLANE
	DOOR / FRAME NUMBER		SECTION/DETAIL-LETTER/#
	ROOM NUMBER		SHEET # WHERE SHOWN
	SURFACE MOUNTED FIRE EXTINGUISHER LOCATION		EXTERIOR ELEVATION MARKER
	AREA OF DETAIL		SECTION/DETAIL-LETTER/NUMBER
	SECTION/DETAIL-LETTER/#		TITLE MARK
	SHEET # WHERE SHOWN		SECTION CUT MARKER
	DETAIL MARKER		INDICATES DIRECTION OF CUTTING PLANE
	PLAN NORTH		SECTION/DETAIL-LETTER/#
	TRUE NORTH		SHEET # WHERE SHOWN
	NORTH INDICATOR		SECTION CUT MARKER

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 AA 26000687 Susan Funk Nute, AR 11913	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	SYMBOLS LEGEND AND NOTES	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		AG-100
					SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A		3

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.

NOTICE OF ACCEPTANCE BASIS OF DESIGN

PRODUCT	SUB CATEGORY	MANUFACTURER	NOTICE OF ACCEPTANCE (NOA) OR STATE OF FLORIDA APPROVAL NUMBER
EXTERIOR DOORS	SWINGING	CECO DOOR PRODUCTS	FLORIDA APPROVED PRODUCT NO. 4553-R10
ROOFING	SBS MODIFIED BITUMEN ROOFING SYSTEM	SOPREMA	NOA NO. 15-0709.14
ROOFING	ROOFING ACCESSORIES THAT ARE AN INTEGRAL PART OF THE ROOFING SYSTEM	SOPREMA	NOA NO. 12-0315.02

* CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL DOCUMENTATION REQUIRED TO SUBSTANTIATE NOA COMPLIANCE FROM MANUFACTURER.

NOTICE OF ACCEPTANCE GENERAL NOTES

- ALL EXTERIOR BUILDING ENVELOPE COMPONENTS AND SYSTEM PRODUCTS SHALL BE CERTIFIED AND LABELED IN ACCORDANCE WITH FLORIDA STATUTES 553.842 PRODUCT EVALUATION AND APPROVAL AND MEET THE FLORIDA BUILDING CODE 2014, HIGH VELOCITY HURRICANE ZONE STRUCTURAL AND BUILDING CONSTRUCTION REQUIREMENTS.
- CONTRACTOR TO PROVIDE A VALID FLORIDA PRODUCT APPROVAL CERTIFICATION OR A NOTICE OF ACCEPTANCE (NOA) FOR ALL BUILDING ENVELOPE COMPONENTS AND SYSTEMS.
- REFER TO THE PROJECT SPECIFICATIONS FOR ADDITIONAL PROJECT SYSTEMS AND EXTERIOR BUILDING ENVELOPE COMPONENTS THAT REQUIRE TESTING, EVALUATION, AND OR CERTIFICATION.
- FIRE SUPPRESSION SYSTEMS, EARLY WARNING AND MANUAL OVERRIDES WILL BE FURNISHED AND INSTALLED BY THE DEPARTMENT. SEPARATE CONTRACT DOCUMENTS WILL BE PREPARED BY THE DEPARTMENT AND ASSOCIATED TO THIS FACILITY TO ENSURE COMPLIANCE WITH THE REQUIREMENTS OF THE APPLICABLE FIRE CODE. THE SYSTEMS WILL BE UNDER SEPARATE CONTRACT AND SUBMITTAL REVIEW. ALL SYSTEMS WILL BE IN OPERATION PRIOR TO THE FINAL CERTIFICATE OF OCCUPANCY OF THIS FACILITY.

LIFE SAFETY INFORMATION

APPLICABLE CODES AND STANDARDS:

FLORIDA BUILDING CODE 2014
 FLORIDA FIRE PREVENTION CODE, 2014
 NFPA 101, 2012
 FLORIDA BUILDING CODE ENERGY CONSERVATION 2014
 FLORIDA MECHANICAL CODE, 2014
 FLORIDA PLUMBING CODE, 2014
 NFPA 70, 2011 (NATIONAL ELECTRIC CODE)
 FLORIDA TURNPIKE ENTERPRISE GENERAL TOLLING REQUIREMENTS (GTR) JUNE 6, 2014

OCCUPANCY CLASSIFICATION:

GROUP S-2 - LOW HAZARD INDUSTRIAL STORAGE (CHAPTER 3, SECTION 311.3) UNMANNED BUILDING

OCCUPANCY SEPARATION:

NO SEPARATION REQUIRED

FIRE RESISTANCE:

NON-COMBUSTIBLE

TYPE IIB - PROTECTED CONSTRUCTION, INERT GAS SYSTEM (CONSTRUCTION REQUIREMENTS PER TABLE 601 (FBC, 2014))

INTERIOR BEARING WALLS

NON-COMBUSTIBLE

INTERIOR NON BEARING WALL

NON-COMBUSTIBLE

COLUMNS

NON-COMBUSTIBLE

BEAMS, GIRDERS, TRUSSES AND ARCHES

NON-COMBUSTIBLE

FLOORS AND FLOOR/CEILING ASSEMBLIES

NON-COMBUSTIBLE

ROOFS AND ROOF/CEILING

NON-COMBUSTIBLE

EXTERIOR BEARING WALLS

10'-20'; NON-COMBUSTIBLE

EXIT ACCESS CORRIDOR WALLS

NON-RATED

(LESS THAN 30 OCCUPANTS)

(FBC TABLE 1018.1)

HEIGHT AND AREA LIMITATIONS FOR TYPE IIB, PROTECTED CONSTRUCTION

UNSPRINKLERED (PER FBC TABLE 503)

MAX HEIGHT ALLOWED: 55' ACTUAL HEIGHT: 11'-3" MAX AREA ALLOWED: 26,000 S.F.

FLOOR AREA EQUIPMENT BUILDING:

TOTAL GROSS BUILDING AREA = 263 S.F. TOTAL

NET BUILDING AREA = 228 S.F.

OCCUPANCY LOAD CALCULATIONS

USE OF AREA AREA (SQ FT) OCC. PER SF OCC. LOAD (ROUNDED UP) MECH/ELEC./STOR.
 228 (GROSS) / 300 = 1 (1 MAINTENANCE STAFF MAY BE PRESENT)

TOTAL OCCUPANCY LOAD = 0 (ROUNDED UP)

EXIT CALCULATIONS

TOTAL BUILDING OCCUPANT LOAD = 0 UNMANNED BUILDING

TOTAL EGRESS WIDTH OF DOOR REQUIRED: 32" MIN. PER FBC 1008.1.1

FIRST FLOOR (0 X 0.2) = 0.0 INCH

PROVIDED TOTAL EXIT DOOR WIDTH = 34 INCHES

MINIMUM CLEAR WIDTH OF EXIT DOOR PROVIDED: 34 INCHES > 32 INCHES; ACCEPTABLE

LIFE SAFETY NOTES AND SYMBOLS

CLASSIFICATION OF OCCUPANCY (NFPA 101 - 2012 EDITION)

OCCUPANCY BY CODE DEFINITION: LOW HAZARD INDUSTRIAL STORAGE


➔ MEANS OF EGRESS GREATEST PATH OF TRAVEL W/OCCUPANT LOAD AT EXIT.

MAXIMUM ALLOWABLE TRAVEL DISTANCE (TABLE 1016.2) AND (CHAPTER 9, SECTION 904.2)


LOW HAZARD INDUSTRIAL STORAGE: 300 FEET

MAX. ACTUAL TRAVEL DISTANCE: 24 FEET

: INDICATES LIFE SAFETY PLAN EGRESS DOOR EXIT.



1 LIFE SAFETY PLAN
 AG-101 SCALE: 1/4" = 1'-0"



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 AA 26000687 Susan Funk Nute, AR 11913	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: GANTRY EQUIPMENT BUILDING CODE DATA AND LIFE SAFETY PLAN	DRAWING NO. AG-101
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.


INTERIOR COLOR SCHEDULE	
COLOR 3	BROWN - FED STD 595 NO. 20062
COLOR 4	WHITE - FED STD 595 NO. 17925

FLOOR ELEVATION

TOLL EQUIPMENT BUILDING FINISH FLOOR SLAB ELEVATION ON BUILDING PLANS INDICATED AS 0'-0" EQUALS 1'-6" ABOVE THE ESTABLISHED 100 YEAR FLOOD PLAIN. REFER TO CIVIL DRAWINGS FOR ACTUAL SLAB ELEVATION.

GENERAL NOTES

- A. REFER TO CIVIL PLANS FOR SITE INFORMATION, INCLUDING SIDEWALK LOCATIONS.
- B. SEE STRUCTURAL PLANS FOR LOCATION OF OPENINGS AND REVEALS IN PRECAST CONCRETE PANELS.
- C. PROVIDE, INSTALL AND TEST GROUND RODS PRIOR TO SLAB INSTALLATION, SEE ELECTRICAL PLANS.
- D. INTERIOR EXPOSED CONCRETE SLAB TO RECEIVE CLEAR COAT CONCRETE SEALER.
- E. PAINT INTERIOR WALLS AND CEILING COLOR 4
- F. RESILIENT BASE SHALL BE COLOR 3
- G. DOOR AND DOOR FRAME SHALL BE COLOR 1 INSIDE AND OUTSIDE (SEE EXTERIOR COLOR SCHEDULE ON AA-201).



A TYPICAL CORNER JOINT
AA-101 SCALE: 1 1/2" = 1'-0"

1 FLOOR PLAN
AA-101 SCALE: 1/4" = 1'-0"



GRAPHIC SCALES

SCALE: 1 1/2" = 1'-0"
0 3" 6"

SCALE: 1/4" = 1'-0"
0 2' 4'

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
AA 26000687
Susan Funk Nute, AR 11913


**STATE OF FLORIDA
DEPARTMENT OF TRANSPORTATION**

ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


SHEET TITLE:	FLOOR PLAN AT RAMP E	DRAWING NO.	AA-101
PROJECT NAME:	SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO.	5

GENERAL NOTES



A. ALL ROOF COMPONENTS SHALL MEET FLORIDA BUILDING CODE WIND LOAD POSITIVE AND NEGATIVE PRESSURES AND HAVE A VALID FLORIDA PRODUCT APPROVAL CERTIFICATE AND/OR A MIAMI-DADE N.O.A. FOR THESE LOADS. SEE STRUCTURAL PLANS FOR DESIGN LOADS.



1 ROOF PLAN
AA-102 SCALE: 1/4" = 1'-0"



2 REFLECTED CEILING PLAN
AA-102 SCALE: 1/4" = 1'-0"



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
AA 26000687
Susan Funk Nute, AR 11913

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: REFLECTED CEILING PLAN & ROOF PLAN AT RAMP E	DRAWING NO. AA-102
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 6

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.



INTERIOR COLOR SCHEDULE	
COLOR 3	BROWN - FED STD 595 NO. 20062
COLOR 4	WHITE - FED STD 595 NO. 17925

FLOOR ELEVATION

TOLL EQUIPMENT BUILDING FINISH FLOOR SLAB ELEVATION ON BUILDING PLANS INDICATED AS 0'-0" EQUALS 1'-6" ABOVE THE ESTABLISHED 100 YEAR FLOOD PLAIN. REFER TO CIVIL DRAWINGS FOR ACTUAL SLAB ELEVATION.


GENERAL NOTES

- A. REFER TO CIVIL PLANS FOR SITE INFORMATION, INCLUDING SIDEWALK LOCATIONS.
- B. SEE STRUCTURAL PLANS FOR LOCATION OF OPENINGS AND REVEALS IN PRECAST CONCRETE PANELS.
- C. PROVIDE, INSTALL AND TEST GROUND RODS PRIOR TO SLAB INSTALLATION, SEE ELECTRICAL PLANS.
- D. INTERIOR EXPOSED CONCRETE SLAB TO RECEIVE CLEAR COAT CONCRETE SEALER.
- E. PAINT INTERIOR WALLS AND CEILING COLOR 4
- F. RESILIENT BASE SHALL BE COLOR 3
- G. DOOR AND DOOR FRAME SHALL BE COLOR 1 INSIDE AND OUTSIDE (SEE EXTERIOR COLOR SCHEDULE ON AA-201).



A TYPICAL CORNER JOINT
AA-103 SCALE: 1 1/2" = 1'-0"

1 FLOOR PLAN
AA-103 SCALE: 1/4" = 1'-0"



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
AA 26000687
Susan Funk Nute, AR 11913


STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: FLOOR PLAN AT RAMP F	DRAWING NO. AA-103
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 7


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.

GENERAL NOTES


A. ALL ROOF COMPONENTS SHALL MEET FLORIDA BUILDING CODE WIND LOAD POSITIVE AND NEGATIVE PRESSURES AND HAVE A VALID FLORIDA PRODUCT APPROVAL CERTIFICATE AND/OR A MIAMI-DADE N.O.A. FOR THESE LOADS. SEE STRUCTURAL PLANS FOR DESIGN LOADS.



1 ROOF PLAN
AA-104 SCALE: 1/4" = 1'-0"



2 REFLECTED CEILING PLAN
AA-104 SCALE: 1/4" = 1'-0"



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
AA 26000687
Susan Funk Nute, AR 11913

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: REFLECTED CEILING PLAN & ROOF PLAN AT RAMP F	DRAWING NO. AA-104
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 8


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.

EXTERIOR COLOR SCHEDULE	
COLOR 1	PEARL GRAY - 872D4
COLOR 2	DARK BRONZE

GENERAL NOTES


A. NOTES INDICATED AS "TYPICAL" ON ELEVATION 1/AA-201 AND 3/AA-201 APPLY TO ALL ELEVATIONS.

B. ALL REVEALS AND PENETRATIONS IN PRECAST WALL PANELS ARE DIMENSIONED IN THE STRUCTURAL DRAWINGS.




1 ELEVATION
AA-201 SCALE: 1/4" = 1'-0"


WALL MOUNT A/C UNIT, VERIFY SIZE AND MODEL PRIOR TO PRECAST CONCRETE FABRICATION: REFER TO MECHANICAL PLANS FOR ANCHORING DETAILS, CONDENSATE LINES AND DRYWELL LOCATIONS, TYPICAL




2 ELEVATION
AA-201 SCALE: 1/4" = 1'-0"



3 ELEVATION
AA-201 SCALE: 1/4" = 1'-0"



4 ELEVATION
AA-201 SCALE: 1/4" = 1'-0"



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION


AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
AA 26000687
Susan Funk Nute, AR 11913

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


SHEET TITLE:	
BUILDING ELEVATIONS	
PROJECT NAME:	
SR 429 WEKIVA PARKWAY SECTION 7A	

DRAWING NO.
AA-201
SHEET NO.
9


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.



1 WALL SECTION
AA-301 SCALE: 1 1/2" = 1'-0"



2 WALL SECTION
AA-301 SCALE: 1 1/2" = 1'-0"



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
AA 26000687
Susan Funk Nute, AR 11913

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


SHEET TITLE:	
BUILDING WALL SECTIONS	
PROJECT NAME:	
SR 429 WEKIVA PARKWAY SECTION 7A	

DRAWING NO.
AA-301
SHEET NO.
10


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.

KEY NOTES


- 1 PROVIDE THREE STAINLESS STEEL JAMB GUARD PLATES ON THE INTERIOR SIDE AT LOCATIONS INDICATED, COORDINATE SIZE OF JAMB GUARD WITH DOOR FRAME PROVIDED BY TOLL EQUIPMENT BUILDING MANUFACTURER.




2 DOOR JAMBS SECTION
AA-501 SCALE: 3" = 1'-0"



1 DOOR EXTERIOR ELEVATION
AA-501 SCALE: 3/4" = 1'-0"



3 INTERIOR ELEVATION - JAMB GUARD
AA-501 SCALE: 3" = 1'-0"



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
AA 26000687
Susan Funk Nute, AR 11913

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	BUILDING DOOR DETAILS
PROJECT NAME:	SR 429 WEKIVA PARKWAY SECTION 7A


DRAWING NO.	AA-501
SHEET NO.	11

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G1-16.005, F.A.C.


DOOR / FRAME SCHEDULE													
DOOR NUMBER	BUILDING NAME	DOOR							FRAME			HARDWARE SET	REMARKS
		SIZE	THICKNESS	TYPE	LOUVER	LABEL	MATERIAL	UNDER CUT	TYPE	MAT.	THRESHOLD		
G1	RAMP GANTRY	3'-0" X 7'-0"	1 3/4"	D1	-	-	H.M.	-	F1	H.M.	NOTE 2	NOTE 2	SEE ELECTRICAL FOR ACCESS CONTROL REQUIREMENTS

DOOR SCHEDULE NOTES:

- DOOR AND HARDWARE SHALL MEET FBC FOR POSITIVE AND NEGATIVE PRESSURES AND HAVE A FLORIDA PRODUCT APPROVAL FOR THESE LOADS. SEE STRUCTURAL FOR DESIGN LOADS.
- REFER TO SPECIFICATIONS SECTION 08 71 00 FOR HARDWARE REQUIREMENTS.



GRAPHIC SCALE



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 AA 26000687 Susan Funk Nute, AR 11913	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: DOOR SCHEDULE DOOR AND DOOR FRAME TYPES		DRAWING NO. AA-601
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		SHEET NO.
					SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A		12

STRUCTURAL GENERAL NOTES:

A. BUILDING CODES:

1. FLORIDA BUILDING CODE, 2014 EDITION.
2. ACI 318-11 BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE.
3. AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC) SPECIFICATION FOR THE DESIGN, FABRICATION, AND ERECTION OF STRUCTURAL STEEL FOR BUILDINGS, THIRTEENTH EDITION.
4. AWS STRUCTURAL WELDING CODE (CURRENT EDITION).

B. DESIGN CRITERIA:

1. LIVE LOADS:
BUILDING ROOF 65 PSF
SLAB-ON-GRADE 125 PSF
2. DEAD LOADS:
ROOF 4 PSF
MISC 3 PSF
3. BUILDING WIND LOADS AS PER ASCE 7-10 FOR A ULTIMATE DESIGN WIND SPEED (3-SECOND GUST) OF 186 MPH AND NOMINAL DESIGN WIND SPEED OF 144 MPH.
RISK CATEGORY: IV
EXPOSURE "C"
INTERNAL PRESSURE COEFFICIENT (TABLE 26.11-1: ±0.18)
ENCLOSURE CLASSIFICATION: ENCLOSED
COMPONENT AND CLADDING PRESSURES: BASED ON ULTIMATE DESIGN WIND SPEED (3-SECOND GUST) OF 186 MPH: DOOR/HVAC UNIT HUNG ON WALL (+67 PSF; -)89 PSF)
SCREEN WALL WIND LOADS AS PER ASCE 7-10 FOR A ULTIMATE DESIGN WIND SPEED (3-SECOND GUST) OF 186 MPH AND A NOMINAL DESIGN WIND SPEED OF 144 MPH.
4. ALLOWABLE SOIL PRESSURE - 2500 PSF (NET)

C. CONSTRUCTION MATERIALS:

1. CAST-IN-PLACE CONCRETE COMPRESSIVE STRENGTH:
4000 PSI AT 28 DAYS (SLAB, FOUNDATION, EQUIPMENT PADS)
2500 PSI AT 28 DAYS (GROUT IN 8" CMU WALL)
2. REINFORCING STEEL - ASTM A 615, GRADE 60 UNCOATED.
3. WELDING ELECTRODES - AWS E-70XX.
4. WELDED STEEL WIRE FABRIC - ASTM A 185
5. PRECAST CONCRETE COMPRESSIVE STRENGTH:
5000 PSI AT 28 DAYS (BUILDING)
6. ALL MISCELLANEOUS STEEL ASTM - A 36.
7. ANCHOR BOLTS - A307 OR A36, GALVANIZED
8. MINIMUM COMPRESSIVE STRENGTH OF MASONRY F'm = 1500 PSI
NOTE:
NET AREA COMPRESSIVE STRENGTH OF CONCRETE MASONRY UNITS WITH TYPE M OR S MORTAR = 1900 PSI

D. FOUNDATIONS:

1. ALL EARTHWORK AND COMPACTION FOR STRUCTURES SHALL BE AS PER TECHNICAL SPECIAL PROVISION SECTION 31 00 00, EARTHWORK.

E. PRECAST CONCRETE BUILDING:

1. PRECAST CONCRETE BUILDING DESIGN TO MEET APPLICABLE DESIGN CRITERIA LISTED IN THE STRUCTURAL GENERAL NOTES AT A MINIMUM.
2. PRECAST CONCRETE BUILDING DESIGN SHALL ALSO CONSIDER LOADS FROM CONDUIT, CABLE TRAYS, AND ALL OTHER SUSPENDED ITEMS.
3. PRECAST CONCRETE BUILDING DESIGN AND WALL CONSTRUCTION SHALL PROVIDE THE CODE REQUIRED CLEAR COVER AT THE WALL REVEALS.

F. MASONRY:

1. MASONRY CONSTRUCTION AND MATERIALS SHALL CONFORM TO ALL REQUIREMENTS OF SPECIFICATIONS FOR MASONRY STRUCTURES (ACI 530.1/ASCE 6/TMS 602) PUBLISHED BY ACI EXCEPT AS MODIFIED BY REQUIREMENTS OF THE TECHNICAL SPECIFICATIONS.
2. ALL BLOCK SHALL BE 8" HOLLOW LOAD-BEARING (NORMAL WEIGHT) CONCRETE BLOCK CONFORMING TO ASTM C90, GRADE N, TYPE II. ALL MORTAR SHALL CONFORM TO ASTM C270 TYPE S, EXCEPT USE TYPE M BELOW GRADE.

G. GENERAL NOTES:

1. ALL CONCRETE EMBEDDED STEEL ANGLES, WELD PLATES, ANCHORAGE DEVICES, ETC., SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A 123 AND / OR F 2329.
2. ALL REINFORCEMENT TO BE DETAILED AND FABRICATED IN ACCORDANCE WITH THE ACI DETAILING MANUAL - 2004 [SP-66(04)]. ALL CONSTRUCTION JOINTS, WITH REINFORCING PASSING THROUGH THE JOINT, SHALL BE ROUGHENED TO A FULL AMPLITUDE OF APPROXIMATELY ¼" INCH, UNLESS NOTED OTHERWISE.
3. PROVIDE THE FOLLOWING MINIMUM CONCRETE COVER, UNLESS NOTED OTHERWISE ON THE PLANS:
FOUNDATIONS - - - - - 3"
SLABS ON GRADE - - - - - CENTERED
4. VERIFY AND CORRELATE ALL DIMENSIONS BEFORE PROCEEDING WITH FABRICATION AND CONSTRUCTION.
5. CHAMFER ALL EXPOSED CONCRETE EDGES ¾"x¾", EXCEPT AS NOTED OTHERWISE.
6. ALL DIMENSIONS ARE MEASURED HORIZONTALLY OR VERTICALLY UNLESS NOTED OTHERWISE.
7. REINFORCING STEEL SHALL NOT BE CUT AT FLOOR BLOCK-OUTS.

H. COORDINATION:

1. COORDINATE ALL MECHANICAL AND CONDUIT PENETRATIONS THROUGH CONCRETE WITH THE CIVIL, MECHANICAL, AND ELECTRICAL SHOP DRAWINGS PRIOR TO PLACING CONCRETE.
2. THE STRUCTURAL SHEETS SHALL BE COORDINATED WITH THE CIVIL, ARCHITECTURAL, MECHANICAL, AND ELECTRICAL SHEETS TO PROPERLY LOCATE PIPE SLEEVES, BLOCK-OUTS, ETC. DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER BEFORE PROCEEDING WITH THE WORK.
3. THE STRUCTURAL SHEETS SHALL BE COORDINATED WITH THE STANDARD SPECIFICATIONS, SUPPLEMENTS, AND TECHNICAL SPECIAL PROVISIONS.

I. DEWATERING

1. EXPECT TO PERFORM DEWATERING FOR FOUNDATIONS. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS TO PREVENT THE FLOTATION OF STRUCTURES UNTIL ALL BACKFILL IS PROPERLY COMPACTED IN PLACE AND CONSTRUCTION IS COMPLETE.


J. SUBMITTAL

1. SUBMIT FOR ENGINEER REVIEW SHOP DRAWINGS FOR THE FOLLOWING ITEMS:


CONCRETE MIX DESIGN

PRECAST CONCRETE BUILDING (INCLUDING SIGNED AND SEALED CALCULATIONS/DRAWINGS BY A LICENSED FLORIDA PROFESSIONAL ENGINEER)

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 George R. Papadopoulos P.E. No. 55843	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	STRUCTURAL GENERAL NOTES	AS-001
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 13



1 FOUNDATION / SLAB PLAN
AS-101 SCALE: 1/4" = 1'-0"



2 ROOF PLAN
AS-101 SCALE: 1/4" = 1'-0"



- STRUCTURAL ITEM NOTES:**
- N-1 CONDUIT PENETRATION ZONE. REFER TO ELECTRICAL DRAWINGS FOR QUANTITY, SIZE, AND LOCATION OF CONDUITS.
 - N-2 THE 8" DIMENSION WAS CHOSEN TO ALLOW VERTICAL INSTALLATION (NO BENDS) OF CONDUIT AND CONDUCTORS. ALL BLOCK OUTS TO BE FILLED IN AND REINFORCED AS PER SECTION "5"/AS-300.
 - N-3 6"x18" BLOCK OUT FOR TELEPHONE COMMUNICATION BACKBOARD AND UPS GROUND.
 - N-4 8"x24" BLOCK OUT FOR E6 READERS.
 - N-5 4"x6" BLOCKOUT FOR EPO CONDUIT PENETRATION.

3	2	3
2	1	2
3	2	3

COMPONENTS & CLADDING ROOF ZONES

AREA (SQ.FT.)	ROOF ZONE		
	1	2	3
≤ 10	-76 PSF	-127 PSF	-191 PSF
20	-74 PSF	-113 PSF	-158 PSF
50	-71 PSF	-95 PSF	-115 PSF
≥ 100	-69 PSF	-82 PSF	-82 PSF

(BASED ON ULTIMATE DESIGN WIND SPEED (3-SECOND GUST) OF 186 MPH)




REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
George R. Papadopoulos P.E. No. 55843


STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	PLANS AT RAMP E	DRAWING NO.
PROJECT NAME:		AS-101
SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO.
		14

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 FOUNDATION / SLAB PLAN
AS-102 SCALE: 1/4" = 1'-0"



2 ROOF PLAN
AS-102 SCALE: 1/4" = 1'-0"

STRUCTURAL ITEM NOTES:

- N-1 CONDUIT PENETRATION ZONE. REFER TO ELECTRICAL DRAWINGS FOR QUANTITY, SIZE, AND LOCATION OF CONDUITS.
- N-2 THE 8" DIMENSION WAS CHOSEN TO ALLOW VERTICAL INSTALLATION (NO BENDS) OF CONDUIT AND CONDUCTORS. ALL BLOCK OUTS TO BE FILLED IN AND REINFORCED AS PER SECTION "5"/AS-300.
- N-3 6"x18" BLOCK OUT FOR TELEPHONE COMMUNICATION BACKBOARD AND UPS GROUND.
- N-4 8"x24" BLOCK OUT FOR E6 READERS.
- N-5 4"x6" BLOCKOUT FOR EPO CONDUIT PENETRATION.


3	2	3
2	1	2
3	2	3

COMPONENTS & CLADDING ROOF ZONES

AREA (SQ.FT.)	ROOF ZONE		
	1	2	3
≤ 10	-76 PSF	-127 PSF	-191 PSF
20	-74 PSF	-113 PSF	-158 PSF
50	-71 PSF	-95 PSF	-115 PSF
≥ 100	-69 PSF	-82 PSF	-82 PSF


(BASED ON ULTIMATE DESIGN WIND SPEED (3-SECOND GUST) OF 186 MPH)

GRAPHIC SCALE




REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 George R. Papadopoulos P.E. No. 55843	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: PLANS AT RAMP F		DRAWING NO. AS-102
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 15
					SR 429	SEMINOLE	240200-2-52-01			

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




1 ELEVATION
AS-201 SCALE: 1/4" = 1'-0"




2 ELEVATION
AS-201 SCALE: 1/4" = 1'-0"

* - COORDINATE THE ATTACHMENTS FOR THE WALL MOUNTED CONDENSING UNITS WITH THE MECHANICAL DRAWINGS.




3 ELEVATION
AS-201 SCALE: 1/4" = 1'-0"



4 ELEVATION
AS-201 SCALE: 1/4" = 1'-0"

- STRUCTURAL ITEM NOTES:**
- N-1 REFER TO DETAIL 6/AS-300 FOR DETAIL OF REVEALS
 - N-2 SEE ARCHITECTURAL DRAWINGS FOR TYPICAL CORNER JOINT DETAIL.
 - N-3 SEE DETAIL "2"/AE-125 FOR WALL PENETRATION INFORMATION.
 - N-4 SEE DETAIL "4"/AE-125 FOR WALL PENETRATION INFORMATION.
 - N-5 SEE DETAIL "1"/AE-125 FOR WALL PENETRATION INFORMATION.
 - N-6 SEE DETAIL "1"/AE-120 FOR WALL PENETRATION INFORMATION.
 - N-7 SEE DETAIL "1"/AE-124 FOR WALL PENETRATION INFORMATION.
 - N-8 SLOPED PIPE SLEEVE. COORDINATE WITH THE MECHANICAL DRAWINGS RELATED TO THE HVAC UNITS.
 - N-9 PENETRATION FOR A/C UNIT DISCONNECT. SEE ELECTRICAL AND ARCHITECTURAL PLANS.
 - N-10 SEE DETAILS ON SHEET GE-112 FOR WALL PENETRATION INFORMATION.



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION



AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
George R. Papadopoulos P.E. No. 55843

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01



SHEET TITLE:	
EXTERIOR ELEVATIONS	
PROJECT NAME:	
SR 429 WEKIVA PARKWAY SECTION 7A	

DRAWING NO.
AS-201
SHEET NO.
16

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.






NOTE:
TOP OF CONCRETE FOUNDATION MUST BE CONSTRUCTED WITHIN A +1/4" TOLERANCE TO ALLOW FOR AN EVEN BEARING SURFACE FOR THE PRECAST CONCRETE BUILDING. STAINLESS STEEL SHIMS WILL BE USED TO ENSURE THAT ALL LOAD BEARING SURFACES ARE AT THE SAME ELEVATION (WITHIN A TOLERANCE OF +1/16"). WHEN THE SHELTER IS SET WITH THE CORRECT SHIMS IN PLACE, COMPLETELY ENCASE THE SHIMS IN GROUT. THIS NON-SHRINK HIGH STRENGTH GROUT SHALL ALSO BE USED TO COMPLETELY SEAL THE PERIMETER OF THE BUILDING AGAINST WATER INTRUSION.



STRUCTURAL ITEM NOTES:

- N-1 GROUNDING ELECTRODE CONDUCTOR BONDED TO FOUNDATION REBAR AND EXTENDING ABOVE FLOOR SLAB. CONDUCTOR TO BE PROVIDED AND INSTALLED BY THE ELECTRICAL CONTRACTOR. REFER TO ELECTRICAL DRAWINGS AND COORDINATE PRIOR TO PLACEMENT OF THE CONCRETE FOUNDATION
- N-2 CONCRETE SIDEWALK, SEE CIVIL PLANS
- N-3 DOWN CONDUCTOR THROUGH BUILDING WALL. REFER TO ELECTRICAL DRAWINGS FOR COORDINATION.
- N-4 SUPPORT SLAB AT GENERATOR AND FUEL TANK. REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR COORDINATION.



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION


AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
George R. Papadopoulos P.E. No. 55843

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


SHEET TITLE:	
SECTIONS AND DETAILS	
PROJECT NAME:	
SR 429 WEKIVA PARKWAY SECTION 7A	

DRAWING NO.
AS-300
SHEET NO.
17


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



TYPICAL FOUNDATION CORNER REINFORCING
NTS



OPTIONAL CONTROL JOINT OR CONSTRUCTION JOINT




CONTROL JOINT (C.J.)


SAW CONTROL JOINT NOTES:

1. MAKE SAW CUT AS SOON AS SLAB IS ABLE TO SUPPORT WEIGHT OF WORKERS AND SAWING EQUIPMENT WITHOUT DAMAGE TO FINISH SURFACE OF SLAB. BEGIN SAW CUTTING OF SLAB WITHIN 8 HOURS OF SLAB BEING FINISHED.
2. CLEAN JOINT PRIOR TO FILLING, WITH JOINT SEALER

TYPICAL SLAB JOINTS
NTS



2 SCREEN WALL ELEVATION N-2
AS-301 SCALE: NTS



1 SCREEN WALL SECTION N-2
AS-301 SCALE: NTS

STRUCTURAL ITEM NOTES:

- N-1 REFER TO CIVIL PLANS FOR CONCRETE PAD AND CONCRETE SIDEWALK.
- N-2 FULLY GROUT ALL CELLS OF THIS MASONRY WALL.
- N-3 PROVIDE REVEALS SIMILAR TO ADJACENT TOLL EQUIPMENT BUILDING.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 George R. Papadopoulos P.E. No. 55843	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	SECTIONS AND DETAILS	AS-301
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A

GENERAL NOTES:

1. IN GENERAL, PLANS AND DIAGRAMS OF UTILITY RUNS ARE SCHEMATIC ONLY AND SHOULD NOT BE SCALED. TAKE RESPONSIBILITY TO COORDINATE AT SITE ALL PLUMBING, HVAC AND ELECTRICAL WORK SO AS NOT TO CONFLICT IN LOCATION WITH OTHER WORK UNDER THE CONTRACT.
2. TAKE RESPONSIBILITY TO READ AND COMPLY WITH DIVISIONS 23 AND 26 OF THE CONTRACT SPECIFICATIONS SPECIAL TECHNICAL PROVISIONS FOR ALL WORK SHOWN ON THESE DRAWINGS.
3. WHERE THE CONTRACTOR PROPOSES TO USE AN APPROVED SUBSTITUTION ITEM OTHER THAN THAT SPECIFIED OR DETAILED ON THE DRAWINGS WHICH REQUIRES ANY REDESIGN OF THE STRUCTURE, PARTITIONS, FOUNDATIONS, PIPING, WIRING OR ANY OTHER PART OF THE MECHANICAL, ELECTRICAL, OR ARCHITECTURAL LAYOUT, ALL SUCH REDESIGN AND CONSTRUCTION COSTS AND ALL NEW DRAWINGS AND DETAILING REQUIRED SHALL BE PREPARED AND INSTALLED BY THE CONTRACTOR AT HIS OWN EXPENSE. PRIOR APPROVAL FOR THIS WORK MUST BE SUBMITTED TO THE ENGINEER.
4. SPACE ALLOTTED FOR MECHANICAL AND ELECTRICAL WORK IS CRITICAL. MECHANICAL AND ELECTRICAL EQUIPMENT HAVE BEEN LOCATED TO ACHIEVE REQUIRED SERVICE CLEARANCES AND MAY NOT BE CHANGED WITHOUT THE CONSENT OF THE ENGINEER. TAKE RESPONSIBILITY TO THOROUGHLY FAMILIARIZE SELF WITH THE ARCHITECTURAL, STRUCTURAL, MECHANICAL AND ELECTRICAL DRAWINGS AND SPECIFICATIONS PRIOR TO FABRICATING AND INSTALLING ANY MATERIALS.
5. ALL POWER WIRING OF MECHANICAL EQUIPMENT SHALL BE BY DIVISION 26.
6. ALL CONTROL WIRING, CONDUIT, AND RELATED CONTROL DEVICES SHALL BE INSTALLED UNDER DIVISION 23 AND SHALL COMPLY WITH THE REQUIREMENTS OF DIVISION 26.
7. MECHANICAL CONTRACTOR SHALL TAKE RESPONSIBILITY FOR THE PROTECTION OF STORED MATERIALS AND EQUIPMENT FOR THE DURATION OF THE PROJECT. PROVIDE PROTECTIVE COVER OVER EQUIPMENT TO ENSURE AGAINST WATER AND DUST DAMAGE AND PROVIDE SUITABLE PALLETS BETWEEN EQUIPMENT AND MATERIALS STORED ON GROUND.
8. IN THE EVENT THAT IT BECOMES NECESSARY FOR THE AIR CONDITIONING EQUIPMENT TO BE TURNED ON FOR BUILDING DEHUMIDIFICATION DURING THE FINAL PHASES OF CONSTRUCTION, TAKE RESPONSIBILITY FOR AND IMPLEMENT ALL PRECAUTIONS TO PROTECT THE EVAPORATOR COILS FROM DUST. A COMPLETE CHANGE OF FILTERS WILL BE REQUIRED PRIOR TO TESTING AND BALANCING THE SYSTEM.
9. MECHANICAL CONTRACTOR SHALL TAKE RESPONSIBILITY FOR COORDINATING SUPPLY AND RETURN AIR OPENINGS IN PRECAST WALLS WITH TOLL EQUIPMENT BUILDING AND MECHANICAL EQUIPMENT MANUFACTURERS. SEE ARCHITECTURAL AND STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION.
10. REFER TO TSPs FOR SEQUENCE OF OPERATION.


HVAC LEGEND	
	DUCTWORK SIZE. FIRST NUMBER DENOTES WIDTH AND SECOND NUMBER DENOTES DEPTH. SIZE INDICATES CLEAR INSIDE DIMENSIONS.
	AIR FLOW
	EQUIPMENT IDENTIFICATION
	CONDENSATE DRAIN
AHU	AIR HANDLING UNIT
CU	CONDENSING UNIT
CFM	CUBIC FEET PER MINUTE
AFF	ABOVE FINISHED FLOOR
FTE	FLORIDA'S TURNPIKE ENTERPRISE
SS	STAINLESS STEEL
	KEYED NOTE
	SECTION LETTER
	SECTION SYMBOL
	SHEET WHERE SECTION IS SHOWN
	DETAIL NUMBER
	DETAIL SYMBOL
	SHEET WHERE DETAIL IS SHOWN
	ELEVATION LETTER
	ELEVATION SYMBOL
	SHEET WHERE SECTION IS SHOWN

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Michael J. Over PE 65665	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: HVAC GENERAL NOTES AND LEGEND		DRAWING NO. AM-001
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 18
						SR 429	SEMINOLE	240200-2-52-01		


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

NOTES:

- 1 5/8" AC UNIT CONDENSATE DRAIN LINE. INSULATE ENTIRE LENGTH WITH 1/2" THICK FLEXIBLE CLOSED CELL ELASTOMERIC PIPING INSULATION. UNIT PROVIDED WITH INTERNAL DRAIN TRAP, EXTERNAL TRAP NOT REQUIRED. INDIRECT WASTE TO 2" CONDENSATE RECEPTOR WITH AIR GAP. TYPICAL OF 2.
- 2 DUAL UNIT CONTROLLER WITH INTEGRAL THERMOSTAT AND TIMER. INSTALL CONTROLLER AT 92" AFF. COORDINATE ALL THERMOSTAT SEQUENCING AND ALARM SET-POINTS WITH FTE REPRESENTATIVE.
- 3 2"Ø SCHEDULE 40 PVC CONDENSATE DRAIN LINE BELOW GRADE, TYPICAL OF 2. MINIMUM SLOPE SHALL BE 1/8" PER FOOT.
- 4 CONTRACTOR SHALL TAKE RESPONSIBILITY OF FINAL FIELD COORDINATION WITH CIVIL SITE AND GRADING PLANS, UTILITY PLANS AND ALL OTHER TRADES FOR THE EXACT LOCATION OF CONDENSATE DRYWELL. SEE CIVIL SITE AND GRADING PLANS FOR DRYWELL LOCATION.
- 5 3-1/2" SLOPED PIPE SLEEVE THROUGH WALL FOR ELECTRICAL INTERCONNECT, REFRIGERANT AND CONDENSATE PIPING, TYPICAL OF TWO. PIPING PENETRATION SHALL BE COMPLETELY CONCEALED BEHIND THE AIR HANDLING UNIT. THE PENETRATION SHALL BE INCLINED SO THAT THE OUTSIDE OPENING IS LOWER THAN THE INSIDE OPENING. LOCATE CENTER OF SLEEVE AT APPROXIMATELY 80" AFF. FOLLOWING PIPING INSTALLATION, INSULATE AND SEAL PENETRATION WITH EXPANDING FOAM SEALANT. COORDINATE EXACT LOCATION AND PENETRATION REQUIREMENTS WITH THE APPROVED AC UNIT MANUFACTURER'S INSTALLATION REQUIREMENTS PRIOR TO CASTING THE WALL.
- 6 26 GAUGE GALVANIZED STEEL LINE-SET COVER TREATED WITH PAINT GRIP, TYPICAL OF TWO. PAINT COVER TO MATCH BUILDING WALL COLOR. INSTALL VERTICALLY FROM SOFFIT ABOVE DOWN TO 24" ABOVE FINISHED GRADE. ENSURE ALL BUILDING REVEAL CROSSINGS AND FITTING ENDS ARE PROPERLY SEALED TO PREVENT WATER INTRUSION OR RODENT ENTRY.
- 7 REFRIGERANT PIPING SIZED PER MANUFACTURERS RECOMMENDATIONS. INSULATE ENTIRE LENGTH OF LIQUID AND GAS PIPES SEPARATELY WITH 1/2" THICK FLEXIBLE CLOSED CELL ELASTOMERIC PIPING INSULATION, TYPICAL OF 2.



DUCTLESS SPLIT SYSTEM AC UNIT SCHEDULE	
RATED/TOTAL CAPACITY (MBH)	36.0
SENSIBLE CAPACITY (MBH)	25.2
VARIABLE CAPACITY RANGE (MBH)	16.0 - 36.0
MINIMUM SYSTEM SEER/EER	18.8 / 10.8
REFRIGERANT	R410A
SYSTEM ELECTRICAL REQUIREMENTS (VOLTS/PHASE/HERTZ)	240/1/60
MCA INDOOR/OUTDOOR (AMPS)	1 / 25
INDOOR WALL MOUNTED AIR HANDLING UNIT (AHU)	
EQUIPMENT TAG	AHU-1 & 2
TOTAL SUPPLY/OUTSIDE AIR FLOW (CFM)	830/0
SUPPLY AIR FLOW RATES (LOW-MED-HIGH) WET COIL	635/730/830
AIR TEMP. (°F) DB/WB	ENTERING 75/62.5 LEAVING 55/54
ECM BLOWER MOTOR FLA (AMPS)	0.57
ECM BLOWER MOTOR OUTPUT (WATTS)	56
SHF / MOISTURE REMOVAL (PINTS/HOUR)	0.70 / 9.7
FILTER	WASHABLE
UNIT WEIGHT (LBS)	46
OUTDOOR CONDENSING UNIT (CU)	
EQUIPMENT TAG	CU-1 & 2
COMPRESSOR DRIVE	DC INVERTER
COMPRESSOR TYPE	TWIN ROTARY
COMPRESSOR RLA (AMPS)	8
ECM FAN MOTOR FLA (QTY. / AMPS)	2 / 0.5
MOCP (AMPS)	31
RATED OUTDOOR AMBIENT TEMP. (°F)	95
UNIT WEIGHT (LBS)	211
NOTES	1-9




SCHEDULE NOTES:

- 1. PROVIDE WITH SINGLE POINT POWER CONNECTION AT THE OUTDOOR UNIT. INDOOR UNIT POWER SUPPLIED VIA ELECTRICAL INTERCONNECT FROM OUTDOOR UNIT.
- 2. PROVIDE ELECTRICAL INTERCONNECT; 3-#14 AWG CONDUCTORS AND 1-#14 AWG GROUND. COORDINATE WITH APPROVED EQUIPMENT MANUFACTURERS INSTALLATION REQUIREMENTS AND NEC.
- 3. PROVIDE OUTDOOR CONDENSING UNITS WITH MANUFACTURER'S SEACOAST PROTECTION PACKAGE.
- 4. PROVIDE MANUFACTURERS DUAL UNIT AC CONTROLLER FOR LEAD/LAG SEQUENCING. CONTROLLER SHALL HAVE A SOLID STATE TIMER WITH AUTO SEQUENCING.
- 5. THE TOLL BUILDING SCADA SYSTEM SHALL MONITOR AND PROVIDE ALARM OUTPUTS TO INDICATE EACH OF THE FOLLOWING ALARM CONDITIONS:
 - LOSS OF CURRENT ON THE BRANCH CIRCUITS TO EACH OUTDOOR UNIT. MONITORED AT THE CIRCUIT BREAKER.
 - LOSS OF VOLTAGE ON THE BRANCH CIRCUIT TO EACH OUTDOOR UNIT. MONITORED AT THE DISCONNECT SWITCH.
- 6. PROVIDE RIGID CONDUIT (EMT) FOR ALL CONTROL WIRING.
- 7. PROVIDE ENGRAVED PLASTIC EQUIPMENT NAMEPLATES.
- 8. REFER TO SPECIFICATIONS FOR UNIT AND CONTROLLER REQUIREMENTS.
- 9. REFER TO TSP SECTION 23 09 00 FOR SEQUENCE OF OPERATION.

DESIGN CONDITIONS SCHEDULE			
ORLANDO SANFORD, FL	SUMMER		WINTER
	DB(°F)	WB(°F)	DB(°F)
INDOOR	75	62.5	50
OUTDOOR*	93.0	75.2	40.9

*PER ASHRAE 2013 FUNDAMENTALS HANDBOOK




REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Causeway Tampa, FL 33607-1462 No. 8115 Michael J. Over PE 65665	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: HVAC FLOOR PLAN		DRAWING NO. AM-101
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 19
					SR 429	SEMINOLE	240200-2-52-01			


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

NOTES:

- 1 5/8" AC UNIT CONDENSATE DRAIN LINE. INSULATE ENTIRE LENGTH WITH 1/2" THICK FLEXIBLE CLOSED CELL ELASTOMERIC PIPING INSULATION. UNIT PROVIDED WITH INTERNAL DRAIN TRAP, EXTERNAL TRAP NOT REQUIRED. INDIRECT WASTE TO 2" CONDENSATE RECEPTOR WITH AIR GAP. TYPICAL OF 2.
- 2 DUAL UNIT CONTROLLER WITH INTEGRAL THERMOSTAT AND TIMER. INSTALL CONTROLLER AT 92" AFF. COORDINATE ALL THERMOSTAT SEQUENCING AND ALARM SET-POINTS WITH FTE REPRESENTATIVE.
- 3 2"Ø SCHEDULE 40 PVC CONDENSATE DRAIN LINE BELOW GRADE, TYPICAL OF 2. MINIMUM SLOPE SHALL BE 1/8" PER FOOT.
- 4 CONTRACTOR SHALL TAKE RESPONSIBILITY OF FINAL FIELD COORDINATION WITH CIVIL SITE AND GRADING PLANS, UTILITY PLANS AND ALL OTHER TRADES FOR THE EXACT LOCATION OF CONDENSATE DRYWELL. SEE CIVIL SITE AND GRADING PLANS FOR DRYWELL LOCATION.
- 5 3-1/2" SLOPED PIPE SLEEVE THROUGH WALL FOR ELECTRICAL INTERCONNECT, REFRIGERANT AND CONDENSATE PIPING, TYPICAL OF TWO. PIPING PENETRATION SHALL BE COMPLETELY CONCEALED BEHIND THE AIR HANDLING UNIT. THE PENETRATION SHALL BE INCLINED SO THAT THE OUTSIDE OPENING IS LOWER THAN THE INSIDE OPENING. LOCATE CENTER OF SLEEVE AT APPROXIMATELY 80" AFF. FOLLOWING PIPING INSTALLATION, INSULATE AND SEAL PENETRATION WITH EXPANDING FOAM SEALANT. COORDINATE EXACT LOCATION AND PENETRATION REQUIREMENTS WITH THE APPROVED AC UNIT MANUFACTURER'S INSTALLATION REQUIREMENTS PRIOR TO CASTING THE WALL.
- 6 26 GAUGE GALVANIZED STEEL LINE-SET COVER TREATED WITH PAINT GRIP, TYPICAL OF TWO. PAINT COVER TO MATCH BUILDING WALL COLOR. INSTALL VERTICALLY FROM SOFFIT ABOVE DOWN TO 24" ABOVE FINISHED GRADE. ENSURE ALL BUILDING REVEAL CROSSINGS AND FITTING ENDS ARE PROPERLY SEALED TO PREVENT WATER INTRUSION OR RODENT ENTRY.
- 7 REFRIGERANT PIPING SIZED PER MANUFACTURERS RECOMMENDATIONS. INSULATE ENTIRE LENGTH OF LIQUID AND GAS PIPES SEPARATELY WITH 1/2" THICK FLEXIBLE CLOSED CELL ELASTOMERIC PIPING INSULATION, TYPICAL OF 2.



DUCTLESS SPLIT SYSTEM AC UNIT SCHEDULE	
RATED/TOTAL CAPACITY (MBH)	36.0
SENSIBLE CAPACITY (MBH)	25.2
VARIABLE CAPACITY RANGE (MBH)	16.0 - 36.0
MINIMUM SYSTEM SEER/EER	18.8 / 10.8
REFRIGERANT	R410A
SYSTEM ELECTRICAL REQUIREMENTS (VOLTS/PHASE/HERTZ)	240/1/60
MCA INDOOR/OUTDOOR (AMPS)	1 / 25
INDOOR WALL MOUNTED AIR HANDLING UNIT (AHU)	
EQUIPMENT TAG	AHU-1 & 2
TOTAL SUPPLY/OUTSIDE AIR FLOW (CFM)	830/0
SUPPLY AIR FLOW RATES (LOW-MED-HIGH) WET COIL	635/730/830
AIR TEMP. (°F) DB/WB	ENTERING 75/62.5 LEAVING 55/54
ECM BLOWER MOTOR FLA (AMPS)	0.57
ECM BLOWER MOTOR OUTPUT (WATTS)	56
SHF / MOISTURE REMOVAL (PINTS/HOUR)	0.70 / 9.7
FILTER	WASHABLE
UNIT WEIGHT (LBS)	46
OUTDOOR CONDENSING UNIT (CU)	
EQUIPMENT TAG	CU-1 & 2
COMPRESSOR DRIVE	DC INVERTER
COMPRESSOR TYPE	TWIN ROTARY
COMPRESSOR RLA (AMPS)	8
ECM FAN MOTOR FLA (QTY. / AMPS)	2 / 0.5
MOCP (AMPS)	31
RATED OUTDOOR AMBIENT TEMP. (°F)	95
UNIT WEIGHT (LBS)	211
NOTES	1-9




SCHEDULE NOTES:

- PROVIDE WITH SINGLE POINT POWER CONNECTION AT THE OUTDOOR UNIT. INDOOR UNIT POWER SUPPLIED VIA ELECTRICAL INTERCONNECT FROM OUTDOOR UNIT.
- PROVIDE ELECTRICAL INTERCONNECT; 3-#14 AWG CONDUCTORS AND 1-#14 AWG GROUND. COORDINATE WITH APPROVED EQUIPMENT MANUFACTURERS INSTALLATION REQUIREMENTS AND NEC.
- PROVIDE OUTDOOR CONDENSING UNITS WITH MANUFACTURER'S SEACOAST PROTECTION PACKAGE.
- PROVIDE MANUFACTURERS DUAL UNIT AC CONTROLLER FOR LEAD/LAG SEQUENCING. CONTROLLER SHALL HAVE A SOLID STATE TIMER WITH AUTO SEQUENCING.
- THE TOLL BUILDING SCADA SYSTEM SHALL MONITOR AND PROVIDE ALARM OUTPUTS TO INDICATE EACH OF THE FOLLOWING ALARM CONDITIONS:
 - LOSS OF CURRENT ON THE BRANCH CIRCUITS TO EACH OUTDOOR UNIT. MONITORED AT THE CIRCUIT BREAKER.
 - LOSS OF VOLTAGE ON THE BRANCH CIRCUIT TO EACH OUTDOOR UNIT. MONITORED AT THE DISCONNECT SWITCH.
- PROVIDE RIGID CONDUIT (EMT) FOR ALL CONTROL WIRING.
- PROVIDE ENGRAVED PLASTIC EQUIPMENT NAMEPLATES.
- REFER TO SPECIFICATIONS FOR UNIT AND CONTROLLER REQUIREMENTS.
- REFER TO TSP SECTION 23 09 00 FOR SEQUENCE OF OPERATION.


DESIGN CONDITIONS SCHEDULE			
ORLANDO SANFORD, FL	SUMMER		WINTER
	DB(°F)	WB(°F)	DB(°F)
INDOOR	75	62.5	50
OUTDOOR*	93.0	75.2	40.9

*PER ASHRAE 2013 FUNDAMENTALS HANDBOOK




REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Michael J. Over PE 65665	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: HVAC FLOOR PLAN		DRAWING NO. AM-102
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 20
					SR 429	SEMINOLE	240200-2-52-01			


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




2 CONDENSATE DRYWELL
AM-501 SCALE: NOT TO SCALE




3 LINE SET COVER DETAIL
AM-501 SCALE: NOT TO SCALE




4 CONDENSATE DRAIN DETAIL
AM-501 SCALE: NOT TO SCALE




5 ATTACHMENT DETAIL
AM-501 SCALE: NOT TO SCALE



1A WALL-MOUNTED CONDENSING UNIT - FRONT VIEW
AM-501 SCALE: NOT TO SCALE



1B WALL-MOUNTED CONDENSING UNIT - SIDE VIEW
AM-501 SCALE: NOT TO SCALE



A SECTION VIEW
AM-501 SCALE: NOT TO SCALE

PROVIDE STAINLESS STEEL ANGLE EQUIPMENT SUPPORT FRAME SHOP WELDED. COORDINATE EXACT SIZE AND CLEARANCE REQUIREMENTS WITH THE APPROVED CONDENSING UNIT EQUIPMENT MANUFACTURERS DIMENSIONS AND INSTALLATION INSTRUCTIONS.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Causeway
Tampa, FL 33607-1462
No. 8115
Michael J. Over PE 65665

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:		DRAWING NO.
MECHANICAL DETAILS		AM-501
PROJECT NAME:		SHEET NO.
SR 429 WEKIVA PARKWAY SECTION 7A		21


GENERATOR FUEL TANK & ACCESSORIES

ITEM No. DESCRIPTION

- ① RECTANGULAR 500 GALLON ABOVE GROUND FIRE RATED MONOLITHIC CONCRETE VAULTED DIESEL FUEL TANK. TANK SHALL BE UL-142 AND UL-2085 LISTED. FDEP APPROVED EQUIPMENT LIST NO. EQ-750.
- ② 7 GALLON CAPACITY, (UL) LISTED OVERSPILL CONTAINMENT.
- ③ 2" TANK INLET SPOUT ADAPTOR WITH DUST CAP.
- ④ 2" TANK INLET FOR FUEL LEVEL SENSOR. REFER TO ELECTRICAL DRAWINGS FOR DETAILS AND SPECIFICATION.
- ⑤ FUEL TANK MONITOR: SEE ELECTRICAL ENLARGED SITE PLANS FOR INSTALLATION LOCATION AND DETAILS. SEE SCADA SYSTEM BLOCK DIAGRAM AND NOTES FOR SPECIFIED FUEL TANK MONITOR AND CONNECTED ACCESSORIES.
- ⑥ 3/4" SCH. 40, BLACK IRON FUEL SUPPLY AND RETURN LINES.
- ⑦ SEE ELECTRICAL DRAWINGS FOR CONDUIT, WIRING JUNCTION BOXES AND EQUIPMENT GROUNDING.
- ⑧ LEAK DETECTION SWITCH AND STEM WITH SENSOR CABLE FOR TANK INTERSTITIAL SPACE MONITORING. PROVIDE WITH ALARM CONSOLE.
- ⑨ 3/4" UNION.
- ⑩ 2" PRIMARY VENT AND CAP.
- ⑪ 2" TANK FITTING FOR COMBINATION FUEL SUPPLY AND RETURN LINE.
- ⑫ 2" TANK FITTING AND OPEN VENT FITTING FOR TANK INTERSTITIAL SPACE.
- ⑬ 4" EMERGENCY VENT.
- ⑭ 2" OPENING FOR HIGH/LOW LEVEL ALARM SWITCH. SET HIGH LEVEL AT 90% TANK FILL LEVEL AND LOW LEVEL AT 30% TANK FILL.
- ⑮ LIQUID LEVEL CLOCK GAUGE WITH STAINLESS STEEL BALL AND CHAIN.
- ⑯ PIPE SUPPORT AND COVER PLATE. (SEE DETAIL)
- ⑰ AST OVERFILL PREVENTION VALVE ASSEMBLY, SET TO SHUT-OFF FUEL SUPPLY AT 95% TANK FILL.
- ⑱ 3/4" UL LISTED ANTI-SIPHON VALVE DESIGNED FOR DIESEL FUEL APPLICATIONS. THE ANTI-SIPHON VALVE SHALL BE INSTALLED IN THE FUEL SUPPLY LINE FROM THE TANK WITH MANUAL BALL VALVES FOR BYPASSING AND ISOLATING THE ANTI-SIPHON VALVE. THE ANTI-SIPHON VALVE SHALL BE SELECTED FOR ACTUAL EQUIPMENT AND PIPING LAYOUT HEAD REQUIREMENTS AND VERIFIED WITH HEAD LOSS CALCULATIONS.
- ⑲ 1" BRASS STRAINER WITH #20 MESH SCREEN FILTER.
- ⑳ CARBON STEEL, FULL PORT, FIRE SAFE DESIGN BALL VALVE, TYPICAL.
- ㉑ TIE DOWN STRAP, TWO REQUIRED. REFER TO FUEL TANK ANCHORING DETAILS.

GENERAL NOTES:

- 1. FUEL LEVEL SENSOR, FUEL TANK MONITOR, AND ALL WIRED OR POWERED ACCESSORIES ARE PROVIDED AND INSTALLED BY THE ELECTRICAL CONTRACTOR UNLESS NOTED OTHERWISE. SEE MECHANICAL AND ELECTRICAL SPECIFICATIONS.
- 2. MECHANICAL CONTRACTOR SHALL COORDINATE ALL TANK OPENINGS (SIZE AND LOCATION) WITH ELECTRICAL CONTRACTOR PRIOR TO ORDERING FUEL TANK.



NOTE:


- 1. FUEL PIPE COVER PLATE SHALL BE PROVIDED FOR ALL EXPOSED PIPING ROUTED WITHIN SERVICE WALKWAYS OR PATHS. REFER TO CIVIL SITE AND GRADING PLANS FOR INDIVIDUAL SITE LOCATIONS AND EQUIPMENT LAYOUT.

FUEL PIPE COVER PLATE DETAIL

SCALE: N.T.S.


NOTE:

- 1. FOR LOCATION OF GENERATOR AND DIESEL FUEL TANK REFER TO CIVIL SITE AND GRADING PLANS. LAYOUT AND CONFIGURATION WILL VARY.



FLOOR PLAN

SCALE: N.T.S.




ELEVATION


SCALE: N.T.S.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Michael J. Over PE 65665	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: GENERATOR PLAN ELEVATION DETAIL AND NOTES	DRAWING NO. AM-502
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 22
						SR 429	SEMINOLE	240200-2-52-01	


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




PLAN VIEW
N.T.S.




SECTION A
N.T.S.




FUEL TANK HOLD DOWN CABLES, ENLARGED VIEW
N.T.S.



ELEVATION
N.T.S.



SECTION B
N.T.S.



PROVIDE TANK WITH OSHA AND ANSI COMPLIANT PERMANENT SAFETY SIGNS TO INDICATE THE FOLLOWING:

1. TYPE GRADE AND CLASS OF LIQUID IN TANK
2. HAZARD/DANGER
3. COMBUSTIBLE LIQUID
4. VOLUME OF TANK
5. NO SMOKING
6. NO OPEN FLAME

IDENTIFICATION SHALL BE POSITIONED SO THAT IT CAN BE EASILY SEEN FROM THE NORMAL ANGLE OF APPROACH.

FUEL TANK HOLD DOWN CABLES
N.T.S.

- NOTES:**
1. STRUCTURAL STEEL SHALL CONFORM TO ASTM A36.
 2. ALL WELDS SHALL BE IN ACCORDANCE WITH AWS CODE. ELECTRODE SHALL BE E70XX.
 3. THREADED ROD SHALL BE STANDARD ASTM A36.
 4. BOLTS SHALL CONFORM TO ASTM A325.
 5. PAINT ALL EXPOSED STEEL WITH GRAY COLD GALVANIZED PAINT.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
Michael J. Over PE 65665

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	FUEL TANK ANCHORING DETAILS	DRAWING NO.
PROJECT NAME:		AM-503
SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO.
		23


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

ELECTRICAL SYMBOL LEGEND:

SYMBOL	DESCRIPTION
A	FLUORESCENT LIGHTING FIXTURE WITH OUTLET BOX. LETTER INDICATES FIXTURE TYPE. SEE LIGHTING FIXTURE SCHEDULE.
B	LED LIGHTING FIXTURE, SURFACE MOUNTED. LETTER INDICATES FIXTURE TYPE. SEE LIGHTING FIXTURE SCHEDULE.
S	SINGLE POLE TOGGLE SWITCH. MOUNTED TOP 48" AFF.
ST	SINGLE POLE SWITCH WITH TIME DELAY DEVICE AS NOTED.
C	EMERGENCY LIGHT UNIT WALL MOUNTED 7'-0" AFF. CONNECT TO LINE SIDE (UNSWITCHED CONDUCTOR) OF CIRCUIT.
GFI	125V, 20A NEMA L-20R, DUPLEX RECEPTACLE. 'WP' INDICATES WEATHERPROOF WITH LOCKABLE METAL WHILE-IN-USE COVER. 'GFI' INDICATES GROUND FAULT INTERRUPTER. MOUNTED BOTTOM 16" AFF UNLESS OTHERWISE NOTED.
	QUAD (TWO DUPLEX) RECEPTACLE. MOUNTED BOTTOM 16" AFF. UNLESS OTHERWISE NOTED.
	QUAD RECEPTACLE - ORANGE NYLON FACE AND ORANGE THERMOPLASTIC WALL PLATE. MOUNTED BOTTOM 16" AFF UNLESS OTHERWISE NOTED.
	SPECIAL RECEPTACLE AS NOTED.
J	JUNCTION BOX 4" SQ. OR AS NOTED.
	PUSHBUTTON. MOUNTED AS NOTED.
SM	MANUAL MOTOR STARTER WITH OVERLOAD ELEMENT. MOUNTED AS NOTED.
	DISCONNECT SWITCH AS NOTED.
	METALLIC LIQUID TIGHT FLEXIBLE CONDUIT CONNECTION.
	OUTLET OR JUNCTION BOX, SIZE PER NEC.
	PANELBOARD. (DIRTY POWER)
	SQUARE D POWERLINK PANELBOARD (CRITICAL POWER) PANELBOARD FED VIA UPS
	CONTROL PANEL.
ATS	AUTOMATIC TRANSFER SWITCH.
SPD	SURGE PROTECTION DEVICE.
	ROOF-MOUNTED AIR TERMINAL.
	GROUND ROD UON.
PB	PULL BOX.
K	KNOX BOX. COORDINATE EXACT LOCATION AND REQUIREMENTS WITH LOCAL FIRE MARSHAL.
S	EMERGENCY POWER SHUTOFF SWITCH.
— LP —	LIGHTNING PROTECTION CONDUCTOR.
— G —	UNDERGROUND GROUND CONDUCTOR.
— N —	NEUTRAL CONDUCTOR.
-----	CONDUIT RACEWAY EXPOSED.
-----	CONDUIT RACEWAY CONCEALED IN CEILING SPACE OR WALLS.
-----	CONDUIT RACEWAY IN CONCRETE SLAB OR UNDERGROUND.

	CONDUIT UP.
	CONDUIT DOWN.
	HOMERUN TO PANEL - LETTER INDICATES PANEL, NUMBERS INDICATE BRANCH CIRCUITS. ALL RACEWAYS WITHOUT FURTHER DESIGNATION INDICATE A TWO-WIRE CIRCUIT. FOUR WIRES ARE INDICATED.
	LONG MARKS INDICATE NEUTRAL CONDUCTOR, SHORT MARKS INDICATE PHASE CONDUCTORS. PROVIDE GREEN GROUND CONDUCTOR IN ALL CONDUITS. (TIE) INDICATES CIRCUIT IS SHARED WITH ADDITIONAL RECEPTACLES.
	DEVICE OR EQUIPMENT AS NOTED
	REFERENCE NOTES
	TELEPHONE OUTLET BOX, INCLUDING TELEPHONE SET
	PAN TILT ZOOM CAMERA
	BACK BOX FOR CCTV CAMERA

GENERAL SYMBOL LEGEND:



ABBREVIATIONS:

A	AMPS
AASHTO	AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS
AC	AIR CONDITIONING [UNIT]
AFF	ABOVE FINISH FLOOR
AFG	ABOVE FINISH GRADE
AL, ALUM.	ALUMINUM
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS
ATS	AUTOMATIC TRANSFER SWITCH
AVI	AUTOMATIC VEHICLE IDENTIFICATION
AWG	AMERICAN WIRE GAUGE
BCU	BATTERY CHARGER UNIT
BLDG.	BUILDING
BPS	BYPASS SWITCH
C	CONDUIT
CCTV	CLOSED CIRCUIT TELEVISION
CKT.	CIRCUIT
COMP	COMPUTER
CU	COPPER
COMM.	COMMUNICATION
DEP	DEPARTMENT OF ENVIRONMENTAL PROTECTION
DIA.	DIAMETER
DN	DOWN
DWG.	DRAWING
E6	ENCOMPASS 6 MULTIPROTOCOL READER
ENG.	ENGINE
E.T.C.	ELECTRONIC TOLL COLLECTION
ETC	ET CETERA
EQUIP.	EQUIPMENT
EPA	ENVIRONMENTAL PROTECTION AGENCY
EPO	EMERGENCY POWER OFF
EXT.	EXTERIOR
FOC	FIBER OPTIC CABLE
FT	FOOT; FEET
FTE	FLORIDA'S TURNPIKE ENTERPRISE
FTL	FEED THROUGH LUGS
FTM	FUEL TANK MONITOR
FUT	FUTURE
GA	GAUGE
GAL.	GALLON
GCB	GENERATOR CIRCUIT BREAKER
GEC	GROUNDING ELECTRODE CONDUCTOR
GFI	GROUND FAULT INTERRUPTER
GND	GROUND
HID	HIGH INTENSITY DISCHARGE
HP	HORSEPOWER
HZ	HORIZONTAL, HERTZ
I.C.	INTERRUPTING CAPACITY
I.D.	IDENTIFICATION
IN.	INCHES
JB	JUNCTION BOX
KA	KILOAMPERES
KVA	KILOVOLT AMPERES
KW	KILOWATT
LED	LIGHT EMITTING DIODE
LFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT
LN CTR	LANE CONTROLLER
LOC.	LOCATION
LLC	LEAD LAG CONTROLLER
LP	LIGHTNING PROTECTION
LTG	LIGHTING
MAX.	MAXIMUM
MCB	MAIN CIRCUIT BREAKER
MTS	MANUAL TRANSFER SWITCH
MIN.	MINIMUM
ML	MAINLINE
M.L.O.	MAIN LUGS ONLY
MOT	MAINTENANCE OF TRAFFIC
MTD	MOUNTED
N	NEUTRAL
NB	NORTHBOUND
N.C.	NORMALLY CLOSED
NEC	NATIONAL ELECTRICAL CODE
NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
NIC	NOT IN CONTRACT
NO.	NUMBER
N.O.	NORMALLY OPEN
N.T.S.	NOT TO SCALE

ABBREVIATIONS CONT:

N3R	NEMA 3R
OC	ON CENTER
ORT	OPEN ROAD TOLLING
Ø	PHASE
P	POLE
PCB	POLYCHLORINATED BIPHENYL
PNL	PANEL
PVC	POLYVINYL CHLORIDE
RECEPT.	RECEPTACLE
RGS	RIGID GALVANIZED STEEL
RMS	ROOT MEAN SQUARE
SB	SOUTHBOUND
SCADA	SUPERVISORY CONTROL & DATA ACQUISITION
SCH.	SCHEDULE
SCP	SCADA CONTROL PANEL
SCTE	SOCIETY OF CABLE TELECOMMUNICATIONS ENGINEERS
SD	SQUARE D
SER	SERVICE ENTRANCE RATED
SPD	SURGE PROTECTIVE DEVICE
SPEC(S)	SPECIFICATION(S)
S.P.S.T.	SINGLE POLE SINGLE THROW
S.S.	STAINLESS STEEL
STP	SHIELDED TWISTED PAIR
SQ.	SQUARE
STFE	STATE TOLL FACILITY ENGINEER
SYMM.	SYMMETRICAL
T.E.C.	TOLL EQUIPMENT CONTRACTOR
T&H	TEMPERATURE AND HUMIDITY SENSOR
T.O.	TOLL OPERATIONS
TSP	TECHNICAL SPECIAL PROVISIONS
TYP.	TYPICAL
UL	UNDERWRITERS LABORATORIES
UON	UNLESS OTHERWISE NOTED
UPS	UNINTERRUPTIBLE POWER SUPPLY
V	VOLTS
VAC	VOLTS ALTERNATING CURRENT
VDAC	VEHICLE DETECTION AND CLASSIFICATION UNIT
VES	VIOLATION ENFORCEMENT SYSTEM
VSS	VIDEO SURVEILLANCE SYSTEM
W	WIRE; WATT
W/	WITH
WP	WEATHERPROOF (NEMA 3R)
XFMR	TRANSFORMER

SECURITY CARD ACCESS SYSTEM SYMBOL LEGEND:

	PROXIMITY CARD READER PROVIDED BY SECURITY CONTRACTOR.
	DOOR CONTACT CONCEALED TYPE.
	ELECTRIFIED LEVER TRIM.
	REQUEST TO EXIT CONTACTS (INTEGRAL TO PUSH BAR).
	POWER TRANSFER DEVICE.
	REQUEST TO EXIT MOTION SENSOR.


REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ELECTRICAL SYMBOLS, LEGEND AND ABBREVIATIONS	DRAWING NO. AE-010
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 24
					SR 429	SEMINOLE	240200-2-52-01		

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

ELECTRICAL GENERAL NOTES:

1. FEED ALL RECEPTACLES AND DEVICES WITH (2) #12, (1) #12 GND IN 3/4" C, UON.
2. PROVIDE (2) #12, (1) #12 GND AND #12 SWITCHLEGS AS REQUIRED IN 3/4" C FOR ALL NEW BUILDING LIGHTING, UON.
3. PROVIDE AN EQUIPMENT GROUNDING CONDUCTOR IN ALL FEEDER AND BRANCH CIRCUIT RACEWAYS.
4. ALL 120V, 20A CIRCUIT HOMERUNS OVER 50FT. SHALL BE #10 CU MINIMUM, UON.
5. ALL 120V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #8 CU MINIMUM, UON.
6. ALL 240V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #10 CU. MINIMUM, UON.
7. ALL 240V, 20A CIRCUIT HOMERUNS OVER 300FT. SHALL BE #8 CU MINIMUM, UON.
8. VERIFY EXACT LOCATION OF ALL MECHANICAL EQUIPMENT WITH MECHANICAL INSTALLER PRIOR TO ROUGH-IN.
9. PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT AND RACEWAYS WITH LABELING AT EACH END.
10. THE USE OF ANY PROCESS INVOLVING ASBESTOS OR PCB, AND THE INSTALLATION OF ANY PRODUCT, INSULATION, COMPOUND OF MATERIAL CONTAINING OR INCORPORATING ASBESTOS OR PCB, IS PROHIBITED. PROVIDE A COMPLETE AND PROPERLY OPERATING ELECTRICAL SYSTEM WITHOUT THE USE OF ASBESTOS OR PCB.
11. CONTACT THE POWER COMPANY WITHIN 10 DAYS OF THE AWARD OF THE CONTRACT AND SCHEDULE NEW SERVICE INSTALLATION.
12. CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID. SUBMISSION OF A BID WILL BE CONSTRUED AS EVIDENCE THAT SUCH EXAMINATION HAS BEEN MADE AND LATER CLAIMS FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WILL NOT BE RECOGNIZED.
13. INCLUDE THE TRANSPORT AND DISPOSAL OR RECYCLING OF ALL WASTE MATERIALS GENERATED BY THIS PROJECT IN ACCORDANCE WITH ALL RULES, REGULATIONS AND GUIDELINES APPLICABLE.
 - A) COMPLY FULLY WITH FLORIDA STATUTE 403.7186 REGARDING MERCURY CONTAINING DEVICES AND LAMPS.
 - B) TRANSPORT AND DISPOSE OF LAMPS, BALLASTS AND OTHER MATERIALS IN ACCORDANCE WITH ALL DEP AND EPA GUIDELINES.
 - C) PROVIDE WRITTEN CERTIFICATION THAT ALL MATERIALS WERE RECYCLED OR DISPOSED OF PROPERLY PER THE GUIDELINES NOTED ABOVE.
14. LOCATE EXISTING UTILITIES AND PROTECT THEM FROM DAMAGE.
15. PHASE WORK AS REQUIRED BY MOT PLANS.
16. UNDERGROUND CONDUIT SHALL BE PVC SCH. 80, UON. UNDERGROUND CONDUIT SHALL TRANSITION TO RGS CONDUIT WITH RGS TO PVC CONDUIT FITTINGS. CONDUIT SHALL BE RGS ABOVE GRADE THROUGH AND INCLUDING THE FIRST 90 DEGREE FITTING UNDERGROUND UON.
17. EQUIPMENT BLDG. INTERIOR: CONDUIT WITH A TRADE SIZE OF LESS THAN 2" SHALL BE EMT. CONDUIT WITH A TRADE SIZE OF 2" AND GREATER SHALL BE RGS.
18. TOLL EQUIPMENT AND ALL WIRING/CABLING FOR TOLL EQUIPMENT WILL BE FURNISHED AND INSTALLED BY T.E.C., UON.
19. UNDERGROUND CONDUITS SHALL BE INSTALLED A MINIMUM OF 36" BELOW GRADE.
20. EXPOSED EXTERIOR CONDUIT SHALL BE RGS THROUGH AND INCLUDING THE FIRST 90° BEND INSTALLED UNDERGROUND. TRANSITIONS BETWEEN RGS AND PVC CONDUIT SHALL BE MADE WITH A RGS TO PVC CONDUIT FITTING.
21. EQUIPMENT SPECIFIED WITH CATALOG NUMBERS OR PART NUMBERS SHALL NOT BE SUBSTITUTED UNLESS "OR EQUAL" IS INDICATED.
22. CONDUIT RESERVED FOR TOLLING LOOPS SHALL BE SCH. 80 PVC.
23. PLASTIC END CAPS SHALL BE INSTALLED ON ENDS OF UNISTRUT.
24. ELECTRICAL INSTALLATION REQUIREMENTS INCLUDING ALL DRAWINGS AND SPECIFICATIONS SHALL BE PROVIDED TO THE BLDG. MANUFACTURER PRIOR TO BLDG. FABRICATION. FLUSH MOUNTED BACK BOXES, CONDUIT ROUTING, LIGHT FIXTURE SUPPORTS ETC. SHALL BE COORDINATED TO ENSURE PROPER INSTALLATION AND PROPER LOCATIONS. RE-WORK DUE TO INSUFFICIENT COORDINATION SHALL BE DONE AT THE CONTRACTOR'S EXPENSE.
25. SCALED BLDG. ELEVATION DRAWINGS INDICATING EQUIPMENT LAYOUT SHALL BE SUBMITTED FOR REVIEW PRIOR TO PROCUREMENT OF EQUIPMENT. REFER TO TSP'S FOR ADDITIONAL REQUIREMENTS.
26. MAINLINE GANTRY DATA WIRE TROUGHS SHALL BE MODIFIED BY A UL OR ETL LISTED PANEL SHOP. THE WIREWAYS TERMINATED TO THE TOP OF THE WIRE TROUGH SHALL BE MODIFIED AND ASSEMBLED IN THE PANEL SHOP & NOT IN THE FIELD TO ENSURE PROPER WATERTIGHT SEAL. SHOP DRAWINGS INCLUDING DIMENSIONED SKETCHES & MATERIAL PRODUCT DATA SHALL BE SUBMITTED FOR REVIEW FOR FABRICATION OF DATA WIRE TROUGH. REFER TO MAINLINE GANTRY DETAILS FOR ADDITIONAL REQUIREMENTS.
27. ALL LIQUID TIGHT FLEXIBLE CONDUIT SHALL BE METALLIC.
28. OUTLET AND DEVICE JUNCTION BOXES INSTALLED OUTDOORS SHALL BE MANUFACTURED FROM GALVANIZED CAST IRON WITH THREADED HUBS, UON. REFER TO TSP SECTION 26 05 33 FOR DETAILS.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	ELECTRICAL GENERAL NOTES	AE-011
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A




1 RAMP E BUILDING - POWER PLAN
 AE-101 SCALE: 1/4" = 1'-0"

GENERAL NOTES:

- REFER TO DWG. AE-125 FOR BUILDING RACEWAY INSTALLATION DETAILS.
- REFER TO DWG. AE-121 AND AE-122 FOR GROUNDING REQUIREMENTS.
- WALL MOUNTED EQUIPMENT SHALL BE MOUNTED ON UNISTRUT AND NOT DIRECTLY TO WALL. REFER TO TSP'S FOR DETAILS.

REFERENCE NOTES:

- SCADA PANEL 'SCP' TO BE PROVIDED BY CONTRACTOR. REFER TO TSP SECTION 26 09 13.
- MAIN DISTRIBUTION PANELBOARD 'MDP': REFER TO POWER RISER DIAGRAM FOR DETAILS.
- ELECTRICAL DISTRIBUTION PANELBOARD 'EDP': REFER TO PANELBOARD SCHEDULE ON DWG. AE-131 FOR DETAILS.
- AUTOMATIC TRANSFER SWITCH 'ATS': REFER TO POWER RISER DIAGRAM FOR DETAILS.
- PANELBOARD (CRITICAL POWER): REFER TO PANELBOARD SCHEDULES ON DWG. AE-131 FOR DETAILS.
- REFER TO AE-130 AND SITE PLANS FOR GROUNDING ELECTRODE SYSTEM REQUIREMENTS.
- UPS BYPASS SWITCH: MOUNT BYPASS 4'-6" AFF WITH CONTROLS ON TOP OF THE ENCLOSURE, REFER TO POWER RISER DIAGRAM FOR DETAILS.
- UPS: PROVIDE A MIN. OF 36" CLEAR SPACE IN FRONT AND 12" BEHIND UPS. REFER TO POWER RISER DIAGRAM FOR CIRCUITING REQUIREMENTS AND DETAILS.
- PROVIDE A #4 AWG BARE CU GROUNDING CONDUCTOR FROM CRITICAL PANEL GROUND BUS TO THE CABLE TRAY. BOND CONDUCTOR TO CABLE TRAY WITH UL LISTED FITTING FOR AL TO CU BOND.
- 240V, 30A, 2-POLE, NEMA 3R DISCONNECT FUSED AT 30A PER HVAC MANUFACTURER'S RECOMMENDATIONS.
- WALL-MOUNTED STORAGE CABINET. MOUNT WITH TOP OF CABINET AT 6'-0" AFF. 30"H X 27"W X 14"D. REFER TO TSP SECTION 26 28 13.
- ROUTE TC-ER TYPE CABLE (2 #12 AWG, 1 #12 GND) ALONG CABLE TRAYS AND EXTEND TO CABLE TRAY MOUNTED RECEPTACLES. PROVIDE CABLE GLAND SEAL FOR EACH TC-ER CABLE THAT PASS THROUGH TOP OF PANEL. CABLE GLAND SHALL BE COOPER CROUSE-HINDS CGB SERIES OR APPROVED EQUAL. MATCH CABLE GLAND NPT SIZE TO CABLE SIZE.
- BOND #4, BARE STRANDED-COPPER CONDUCTOR TO MAIN GROUND BUSBAR & EXTEND IN 1" SCH. 80 PVC OVERHEAD TO CABLE TRAY AND TOLLING CABINETS. BOND CONDUCTOR TO CABLE TRAY & EXTEND CONDUCTOR THE FULL LENGTH OF THE CABLE TRAY. BOND CONDUCTOR WITH UL LISTED FITTING FOR AL TO CU BOND EACH SECTION.
- 24" WIDE X 6" DEEP CABLE TRAY WITH DIVIDER. REFER TO AE-111 AND TSP'S FOR REQUIREMENT.
- #4 CONTINUOUS, BARE STRANDED-COPPER GROUNDING ELECTRODE CONDUCTOR TO GROUND ROD AND CONCRETE-ENCASED ELECTRODE. REFER TO DWG. AE-121 AND AE-130 FOR DETAILS.
- BOND #2/0 BARE, STRANDED-COPPER GROUNDING CONDUCTOR TO MAIN GROUND BUS BAR & EXTEND TO CONCRETE-ENCASED ELECTRODE.
- ROUTE LIQUID TIGHT FLEXIBLE METAL CONDUIT FROM UPS TO BPS.
- WALL-MOUNTED 12"(WIDE) X 5" MAX RAIL HEIGHT (4" NEMA VE1 LOADING DEPTH) ALUMINUM LADDER TYPE POWER CABLE TRAY (FROM TOP OF PANEL TO THE HEIGHT OF HORIZONTAL CABLE TRAY). PROVIDE AND INSTALL REDI-RAIL MODEL NO. H15AR100K006-06 OR APPROVED EQUAL. PROVIDE A CONTINUOUS #4 GROUND WIRE IN CABLE TRAY. PROVIDE A UL LISTED BONDING JUMPER COOPER B-LINE MODEL NO. 99-30 OR APPROVED EQUAL.
- BATTERY CHARGER UNIT FOR THE GENERATOR BATTERY.
- SURGE PROTECTION DEVICE (SPD). FIELD ADJUST THE LOCATIONS OF THE SPD SUCH THAT THE MAXIMUM SPD BRAIDED/TWISTED LEADS DO NOT EXCEED 24 INCHES AND HAVE NO SHARP TURNS. MAINTAIN LEADS AS SHORT & STRAIGHT AS POSSIBLE FROM CB TO SPD.
- BOND THE RAISED METAL SUPPORT FRAME TO THE CONCRETE-ENCASED ELECTRODE (OR REBAR IN FOOTER) BY #4, BARE, STRANDED-COPPER CONDUCTOR AT EACH END OF THE SUPPORT STAND. BOND CONDUCTOR WITH UL LISTED FITTING FOR AL TO CU BOND (IF ALUMINUM FRAME).
- WALL MOUNTED GROUND BUSBAR. BOND TO THE CONCRETE-ENCASED ELECTRODE BY #4, BARE, STRANDED-COPPER CONDUCTOR. REFER TO INTERIOR ELEVATION 1 ON DRAWING AE-114 AND AE-121 FOR FURTHER INFORMATION.
- PROVIDE A QUAD RECEPTACLE (ORANGE NYLON FACE, 125V, 20A) IN SURFACE MOUNTED DOUBLE GANG BACK BOX 48" AFF DEDICATED FOR COMMUNICATION SERVICE EQUIPMENT.
- DEDICATED SPACE (7'-0" X 3'-6") FOR FUTURE FIRE SUPPRESSION SYSTEM BY OWNER.
- THE WIRING BETWEEN THE AHU AND CU WILL BE FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR.



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	BUILDING - POWER PLAN AT RAMP E	AE-101
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

GENERAL NOTES:

- 1. REFER TO DWG. AE-125 FOR BUILDING RACEWAY INSTALLATION DETAILS.
- 2. LIGHT FIXTURE INSTALLATIONS/MOUNTING MUST BE COORDINATED WITH BLDG. MANUFACTURER.


REFERENCE NOTES:

- 1 BUILDING MOUNTED LIGHT FIXTURE TYPE 'B' SHALL HAVE AN INTEGRAL PHOTOCELL.
- 2 CONNECT EMERGENCY LIGHTS TO LOCAL AREA LIGHTING CIRCUIT AHEAD OF ALL SWITCHING DEVICES.



1 RAMP E BUILDING - LIGHTING PLAN
 AE-102 SCALE: 1/4" = 1'-0"

LIGHTING FIXTURE SCHEDULE						
TYPE	DESCRIPTION	MANUFACTURER	VOLT	LAMPS	MOUNTING	REMARKS
A	1' X 4' FLUORESCENT WRAPAROUND	LITHONIA #LB232A-120-GEB10IS-GLR OR APPROVED EQUAL	120	2-F32-T8CW	PENDANT-BOTTOM 8'-0" AFF SWIVEL STEM	
B	DIECAST ALUMINUM WALL MTD LED FIXTURE, DARK BRONZE FINISH, PHOTOCELL	KENALL #MR13EL-PP-DB-10L35K-1-120-BPC-SA-FS OR APPROVED EQUAL	120	10W LED 3500K W/UNIT	WALL SURFACE MTD. @ 9'-0" AFF	FOR WET LOCATION SEE ARCHITECTURAL ELEVATIONS
C	BATTERY PACK EMERGENCY LIGHT	LITHONIA ELM6LED-LP03VS OR APPROVED EQUAL	120	LED W/UNIT	WALL SURFACE MOUNTED	



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING - LIGHTING PLAN AT RAMP E	DRAWING NO. AE-102
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 27


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

GENERAL NOTES:


1. CONDUCTORS SHALL BE SIZED IN ACCORDANCE WITH NFPA 780 CLASS 1 MATERIAL REQUIREMENTS.
2. REFER TO SITE PLANS FOR ADDITIONAL REQUIREMENTS.

REFERENCE NOTES:

- 1 REFER TO TSP SECTION 26 41 13 FOR CONDUCTOR SIZES.
- 2 GROUND RING ELECTRODE SHALL BE INSTALLED 36" (MIN.) BELOW GRADE.
- 3 24" FROM EXTERIOR OF WALL TO CENTERLINE OF THROUGH-ROOF CONDUCTOR.



1 RAMP E BUILDING - LIGHTNING PROTECTION PLAN
 AE-103 SCALE: 1/4" = 1'-0"



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: BUILDING - LIGHTNING PROTECTION PLAN AT RAMP E		DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		SHEET NO.
						SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A	


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

GENERAL NOTES:


1. REFER TO DWG. AE-125 FOR BUILDING RACEWAY INSTALLATION DETAILS.
2. REFER TO DWG. AE-133 FOR SCADA SYSTEM BLOCK DIAGRAM AND DETAILS.
3. REFER TO DWG. AE-121 AND AE-122 FOR GROUNDING REQUIREMENTS.
4. CONDUIT STUBBED OVER CABLE TRAY SHALL BE PROVIDED WITH AN INSULATED THROAT GROUNDING BUSHING AND BONDED TO THE CABLE TRAY WITH A #4 BARE COPPER CONDUCTOR.
5. WALL-MOUNTED EQUIPMENT SHALL BE SECURED TO WALL VIA UNISTRUT SUPPORTS. SEE TSP'S FOR DETAILS.
6. REFER TO SITE PLANS FOR ADDITIONAL SCADA & SECURITY CONDUIT ROUTING.

REFERENCE NOTES:

- ① CONDUIT FOR SCADA CONNECTIONS. REFER TO AE-133 AND BUILDING INTERIOR ELEVATION FOR CONDUIT & CONDUCTOR SIZES.
- ② SINGLE GANG BACK BOX & 1" C. ROUTED TO DATA SIDE OF CABLE TRAY FOR UPS NETWORK CONNECTIONS. LOCATE BACK BOX NOT MORE THAN 12" FROM UPS NETWORK TERMINATIONS.
- ③ SECURITY ACCESS EQUIPMENT. REFER TO AE-010 & AE-124 FOR SYMBOLS AND DETAILS. REFER TO TSP'S FOR ADDITIONAL REQUIREMENTS.
- ④ 1" C (DATA) FOR CCTV CAMERA. CONDUIT TO BE ROUTED FROM J-BOX TO CABLE TRAY. COORDINATE EXACT LOCATION WITH DEPARTMENT.
- ⑤ 12"x12"x36", NEMA 1 PAINTED STEEL WIRING TROUGH. PROVIDE (2) 3" NIPPLES BETWEEN TOP OF WIRING TROUGH AND BOTTOM OF SCADA CONTROL PNL (SCP).
- ⑥ MOISTURE DETECTOR. REFER TO DWG. AE-133 FOR DETAILS.
- ⑦ (2) #12, 1 #12G, 1" C. (AHU-1/AHU-2 INTERCONNECT)
- ⑧ (4) #12, 1 #12G, 1" C. (HVAC LLC WIRING AND AHU-1/AHU-2 INTERCONNECT)
- ⑨ SCADA CONDUIT TO CONDENSING UNIT DISCONNECT SWITCH.




1 RAMP E BUILDING - SCADA AND SECURITY SYSTEM PLAN
 AE-104 SCALE: 1/4" = 1'-0"



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: BUILDING - SCADA AND SECURITY SYSTEM PLAN AT RAMP E		DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		SHEET NO.
						SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A	

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




1 RAMP E BUILDING - TOLLING SYSTEM PLAN
 AE-105 SCALE: 1/4" = 1'-0"

GENERAL NOTES:

1. REFER TO SITE PLANS FOR CONDUIT ROUTING OUTSIDE THE BUILDING.
2. REFER TO DWG. AE-126 FOR CONDUIT STUB-UP DETAIL INDICATING CONDUIT SIZE, LOCATION AND QUANTITIES.
3. REFER TO TSP'S FOR COMMUNICATION SERVICE CONNECTION REQUIREMENTS.
4. TOLLING EQUIPMENT CABINETS WILL BE PROVIDED AND INSTALLED BY THE DEPARTMENT'S TOLL EQUIPMENT CONTRACTOR AFTER THE ENTIRE SITE IS COMPLETE.

REFERENCE NOTES:

- 1 TOLLING EQUIPMENT CABINETS SHALL BE FURNISHED AND INSTALLED BY THE DEPARTMENT'S TOLL EQUIPMENT CONTRACTOR.
- 2 INSTALL (2) 2" PVC CONDUITS STUBBED UP UNDER THE TOLLING COMMUNICATIONS CABINET AND EXTENDED TO THE ITS PULL BOX SHOWN ON THE ENLARGED SITE PLAN. THE 90 DEGREE ELBOWS SHALL HAVE A 24" MINIMUM BENDING RADIUS. COORDINATE REQUIREMENTS WITH ITS PLANS PRIOR TO ROUGH IN.
- 3 INSTALL (2) 2" PVC CONDUITS STUBBED UP UNDER THE TOLLING COMMUNICATIONS CABINET FOR GANTRY MOUNTED CCTV CAMERAS. REFER TO SITE PLAN FOR CONDUIT ROUTING.
- 4 REFER TO AE-126 AND SITE PLAN FOR CONDUIT ROUTINGS.
- 5 (2) 4" CONDUIT STUB-UP FOR E6 READER. REFER TO SITE PLAN FOR CONDUIT ROUTING.
- 6 FTE COMMUNICATIONS CABINET. REFER TO TSP SECTION 27 11 16 FOR REQUIREMENTS.
- 7 1" C, CAT6 CABLE WITH RJ45 CONNECTORS WITH 6'-0" OF SLACK CABLE ON EACH END. STUB CONDUIT 2" BELOW TOP OF COMMUNICATIONS BACKBOARD. ROUTE CABLE FROM TELCO EQUIPMENT TO NETWORK SWITCH IN THE COMMUNICATIONS CABINET.
- 8 PROVIDE A 7-POSITION COPPER GROUND BAR WITHOUT PLATING APPROVED BY TELEPHONE COMPANY. BOND TO THE CONCRETE-ENCASED ELECTRODE BY #4, BARE, STRANDED-COPPER CONDUCTOR.
- 9 PROVIDE (2) 2"C. ROUTED FROM COMMUNICATIONS BACKBOARD TO TELCO PULL BOX. SEE SITE PLAN FOR DETAILS. CONDUIT BEND RADIUS SHALL NOT BE LESS THAN 24". COORDINATE REQUIREMENTS WITH TELEPHONE COMPANY PRIOR TO ROUGH IN.
- 10 PAINT A 2'X4' AREA ON PLYWOOD WALLS WITH FIRE-RETARDANT PAINT. VERIFY REQUIREMENTS WITH TELECOMMUNICATION COMPANY.



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


SHEET TITLE: BUILDING - TOLLING SYSTEM PLAN AT RAMP E	DRAWING NO. AE-105
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 30

GENERAL NOTES:



1. REFER TO DWG. AE-125 FOR BUILDING RACEWAY INSTALLATION DETAILS.
2. REFER TO DWG. AE-121 AND AE-122 FOR GROUNDING REQUIREMENTS.
3. WALL MOUNTED EQUIPMENT SHALL BE MOUNTED ON UNISTRUT AND NOT DIRECTLY TO WALL. REFER TO TSP'S FOR DETAILS.

REFERENCE NOTES:

- 1 SCADA PANEL 'SCP' TO BE PROVIDED BY CONTRACTOR. REFER TO TSP SECTION 26 09 13.
- 2 MAIN DISTRIBUTION PANELBOARD 'MDP': REFER TO POWER RISER DIAGRAM FOR DETAILS.
- 3 ELECTRICAL DISTRIBUTION PANELBOARD 'EDP': REFER TO PANELBOARD SCHEDULE ON DWG. AE-131 FOR DETAILS.
- 4 AUTOMATIC TRANSFER SWITCH 'ATS': REFER TO POWER RISER DIAGRAM FOR DETAILS.
- 5 PANELBOARD (CRITICAL POWER): REFER TO PANELBOARD SCHEDULES ON DWG. AE-131 FOR DETAILS.
- 6 REFER TO AE-130 AND SITE PLANS FOR GROUNDING ELECTRODE SYSTEM REQUIREMENTS.
- 7 UPS BYPASS SWITCH: MOUNT BYPASS 4'-6" AFF WITH CONTROLS ON TOP OF THE ENCLOSURE, REFER TO POWER RISER DIAGRAM FOR DETAILS.
- 8 UPS: PROVIDE A MIN. OF 36" CLEAR SPACE IN FRONT AND 12" BEHIND UPS. REFER TO POWER RISER DIAGRAM FOR CIRCUITING REQUIREMENTS AND DETAILS.
- 9 PROVIDE A #4 AWG BARE CU GROUNDING CONDUCTOR FROM CRITICAL PANEL GROUND BUS TO THE CABLE TRAY. BOND CONDUCTOR TO CABLE TRAY WITH UL LISTED FITTING FOR AL TO CU BOND.
- 10 240V, 30A, 2-POLE, NEMA 3R DISCONNECT FUSED AT 30A PER HVAC MANUFACTURER'S RECOMMENDATIONS.
- 11 WALL-MOUNTED STORAGE CABINET. MOUNT WITH TOP OF CABINET AT 6'-0" AFF. 30"H X 27"W X 14"D. REFER TO TSP SECTION 26 28 13.
- 12 ROUTE TC-ER TYPE CABLE (2 #12 AWG, 1 #12 GND) ALONG CABLE TRAYS AND EXTEND TO CABLE TRAY MOUNTED RECEPTACLES. PROVIDE CABLE GLAND SEAL FOR EACH TC-ER CABLE THAT PASS THROUGH TOP OF PANEL. CABLE GLAND SHALL BE COOPER CROUSE-HINDS CGB SERIES OR APPROVED EQUAL. MATCH CABLE GLAND NPT SIZE TO CABLE SIZE.
- 13 BOND #4, BARE STRANDED-COPPER CONDUCTOR TO MAIN GROUND BUSBAR & EXTEND IN 1" SCH. 80 PVC OVERHEAD TO CABLE TRAY AND TOLLING CABINETS. BOND CONDUCTOR TO CABLE TRAY & EXTEND CONDUCTOR THE FULL LENGTH OF THE CABLE TRAY. BOND CONDUCTOR WITH UL LISTED FITTING FOR AL TO CU BOND EACH SECTION.
- 14 24" WIDE X 6" DEEP CABLE TRAY WITH DIVIDER. REFER TO AE-111 AND TSP'S FOR REQUIREMENT.
- 15 #4 CONTINUOUS, BARE STRANDED-COPPER GROUNDING ELECTRODE CONDUCTOR TO GROUND ROD AND CONCRETE-ENCASED ELECTRODE. REFER TO DWG. AE-121 AND AE-130 FOR DETAILS.
- 16 BOND #2/0 BARE, STRANDED-COPPER GROUNDING CONDUCTOR TO MAIN GROUND BUS BAR & EXTEND TO CONCRETE-ENCASED ELECTRODE.
- 17 ROUTE LIQUID TIGHT FLEXIBLE METAL CONDUIT FROM UPS TO BPS.
- 18 WALL-MOUNTED 12"(WIDE) X 5" MAX RAIL HEIGHT (4" NEMA VE1 LOADING DEPTH) ALUMINUM LADDER TYPE POWER CABLE TRAY (FROM TOP OF PANEL TO THE HEIGHT OF HORIZONTAL CABLE TRAY). PROVIDE AND INSTALL REDI-RAIL MODEL NO. H15AR100K006-06 OR APPROVED EQUAL. PROVIDE A CONTINUOUS #4 GROUND WIRE IN CABLE TRAY. PROVIDE A UL LISTED BONDING JUMPER COOPER B-LINE MODEL NO. 99-30 OR APPROVED EQUAL.
- 19 BATTERY CHARGER UNIT FOR THE GENERATOR BATTERY.
- 20 SURGE PROTECTION DEVICE (SPD). FIELD ADJUST THE LOCATIONS OF THE SPD SUCH THAT THE MAXIMUM SPD BRAIDED/TWISTED LEADS DO NOT EXCEED 24 INCHES AND HAVE NO SHARP TURNS. MAINTAIN LEADS AS SHORT & STRAIGHT AS POSSIBLE FROM CB TO SPD.
- 21 BOND THE RAISED METAL SUPPORT FRAME TO THE CONCRETE-ENCASED ELECTRODE (OR REBAR IN FOOTER) BY #4, BARE, STRANDED-COPPER CONDUCTOR AT EACH END OF THE SUPPORT STAND. BOND CONDUCTOR WITH UL LISTED FITTING FOR AL TO CU BOND (IF ALUMINUM FRAME).
- 22 WALL MOUNTED GROUND BUSBAR. BOND TO THE CONCRETE-ENCASED ELECTRODE BY #4, BARE, STRANDED-COPPER CONDUCTOR. REFER TO INTERIOR ELEVATION 1 ON DRAWING AE-114 AND AE-121 FOR FURTHER INFORMATION.
- 23 PROVIDE A QUAD RECEPTACLE (ORANGE NYLON FACE, 125V, 20A) IN SURFACE MOUNTED DOUBLE GANG BACK BOX 48" AFF DEDICATED FOR COMMUNICATION SERVICE EQUIPMENT.
- 24 DEDICATED SPACE (7'-0" X 3'-6") FOR FUTURE FIRE SUPPRESSION SYSTEM BY OWNER.
- 25 THE WIRING BETWEEN THE AHU AND CU WILL BE FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR.



1 RAMP F BUILDING -- POWER PLAN
 AE-106 SCALE: 1/4" = 1'-0"



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: BUILDING - POWER PLAN AT RAMP F	DRAWING NO. AE-106
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
					SR 429	SEMINOLE	240200-2-52-01		


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

GENERAL NOTES:

- 1. REFER TO DWG. AE-125 FOR BUILDING RACEWAY INSTALLATION DETAILS.
- 2. LIGHT FIXTURE INSTALLATIONS/MOUNTING MUST BE COORDINATED WITH BLDG. MANUFACTURER.

REFERENCE NOTES:

- ① BUILDING MOUNTED LIGHT FIXTURE TYPE 'B' SHALL HAVE AN INTEGRAL PHOTOCELL.
- ② CONNECT EMERGENCY LIGHTS TO LOCAL AREA LIGHTING CIRCUIT AHEAD OF ALL SWITCHING DEVICES.



1 RAMP F BUILDING - LIGHTING PLAN
 AE-107 SCALE: 1/4" = 1'-0"

LIGHTING FIXTURE SCHEDULE						
TYPE	DESCRIPTION	MANUFACTURER	VOLT	LAMPS	MOUNTING	REMARKS
A	1' X 4' FLUORESCENT WRAPAROUND	LITHONIA #LB232A-120-GEB10IS-GLR OR APPROVED EQUAL	120	2-F32-T8CW	PENDANT-BOTTOM 8'-0" AFF SWIVEL STEM	
B	DIECAST ALUMINUM WALL MTD LED FIXTURE, DARK BRONZE FINISH, PHOTOCELL	KENALL #MR13EL-PP-DB-10L35K-1-120-BPC-SA-FS OR APPROVED EQUAL	120	10W LED 3500K W/UNIT	WALL SURFACE MTD. @ 9'-0" AFF	FOR WET LOCATION SEE ARCHITECTURAL ELEVATIONS
C	BATTERY PACK EMERGENCY LIGHT	LITHONIA ELM6LED-LP03VS OR APPROVED EQUAL	120	LED W/UNIT	WALL SURFACE MOUNTED	



GRAPHIC SCALE
 SCALE: 1/4" = 1'-0"
 0 2' 4'

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING - LIGHTING PLAN AT RAMP F	DRAWING NO. AE-107
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 32


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

GENERAL NOTES:


1. CONDUCTORS SHALL BE SIZED IN ACCORDANCE WITH NFPA 780 CLASS 1 MATERIAL REQUIREMENTS.
2. REFER TO SITE PLANS FOR ADDITIONAL REQUIREMENTS.

REFERENCE NOTES:

- 1 REFER TO TSP SECTION 26 41 13 FOR CONDUCTOR SIZES.
- 2 GROUND RING ELECTRODE SHALL BE INSTALLED 36" (MIN.) BELOW GRADE.
- 3 24" FROM EXTERIOR OF WALL TO CENTERLINE OF THROUGH-ROOF CONDUCTOR.



1 RAMP F BUILDING - LIGHTNING PROTECTION PLAN
 AE-108 SCALE: 1/4" = 1'-0"



GRAPHIC SCALE
 SCALE: 1/4" = 1'-0"
 0 2' 4'

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING - LIGHTNING PROTECTION PLAN AT RAMP F	DRAWING NO. AE-108
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 33


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

GENERAL NOTES:



1. REFER TO DWG. AE-125 FOR BUILDING RACEWAY INSTALLATION DETAILS.
2. REFER TO DWG. AE-133 FOR SCADA SYSTEM BLOCK DIAGRAM AND DETAILS.
3. REFER TO DWG. AE-121 AND AE-122 FOR GROUNDING REQUIREMENTS.
4. CONDUIT STUBBED OVER CABLE TRAY SHALL BE PROVIDED WITH AN INSULATED THROAT GROUNDING BUSHING AND BONDED TO THE CABLE TRAY WITH A #4 BARE COPPER CONDUCTOR.
5. WALL-MOUNTED EQUIPMENT SHALL BE SECURED TO WALL VIA UNISTRUT SUPPORTS. SEE TSP'S FOR DETAILS.
6. REFER TO SITE PLANS FOR ADDITIONAL SCADA & SECURITY CONDUIT ROUTING.

REFERENCE NOTES:

- 1 CONDUIT FOR SCADA CONNECTIONS. REFER TO AE-133 AND BUILDING INTERIOR ELEVATION FOR CONDUIT & CONDUCTOR SIZES.
- 2 SINGLE GANG BACK BOX & 1" C. ROUTED TO DATA SIDE OF CABLE TRAY FOR UPS NETWORK CONNECTIONS. LOCATE BACK BOX NOT MORE THAN 12" FROM UPS NETWORK TERMINATIONS.
- 3 SECURITY ACCESS EQUIPMENT. REFER TO AE-010 & AE-124 FOR SYMBOLS AND DETAILS. REFER TO TSP'S FOR ADDITIONAL REQUIREMENTS.
- 4 1" C (DATA) FOR CCTV CAMERA. CONDUIT TO BE ROUTED FROM J-BOX TO CABLE TRAY. COORDINATE EXACT LOCATION WITH DEPARTMENT.
- 5 12"X12"X36", NEMA 1 PAINTED STEEL WIRING TROUGH. PROVIDE (2) 3" NIPPLES BETWEEN TOP OF WIRING TROUGH AND BOTTOM OF SCADA CONTROL PNL (SCP).
- 6 MOISTURE DETECTOR. REFER TO DWG. AE-133 FOR DETAILS.
- 7 (2) #12, 1 #12G, 1" C. (AHU-1/AHU-2 INTERCONNECT)
- 8 (4) #12, 1 #12G, 1" C. (HVAC LLC WIRING AND AHU-1/AHU-2 INTERCONNECT)
- 9 SCADA CONDUIT TO CONDENSING UNIT DISCONNECT SWITCH.




1 RAMP F BUILDING - SCADA AND SECURITY SYSTEM PLAN
 AE-109 SCALE: 1/4" = 1'-0"



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	BUILDING - SCADA AND SECURITY SYSTEM PLAN AT RAMP F	AE-109
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 34

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.





1 RAMP F BUILDING - TOLLING SYSTEM PLAN
 AE-110 SCALE: 1/4" = 1'-0"

GENERAL NOTES:

1. REFER TO SITE PLANS FOR CONDUIT ROUTING OUTSIDE THE BUILDING.
2. REFER TO DWG. AE-126 FOR CONDUIT STUB-UP DETAIL INDICATING CONDUIT SIZE, LOCATION AND QUANTITIES.
3. REFER TO TSP'S FOR COMMUNICATION SERVICE CONNECTION REQUIREMENTS.
4. TOLLING EQUIPMENT CABINETS WILL BE PROVIDED AND INSTALLED BY THE DEPARTMENT'S TOLL EQUIPMENT CONTRACTOR AFTER THE ENTIRE SITE IS COMPLETE.


REFERENCE NOTES:

- 1 TOLLING EQUIPMENT CABINETS SHALL BE FURNISHED AND INSTALLED BY THE DEPARTMENT'S TOLL EQUIPMENT CONTRACTOR.
- 2 INSTALL (2) 2" PVC CONDUITS STUBBED UP UNDER THE TOLLING COMMUNICATIONS CABINET AND EXTENDED TO THE ITS PULL BOX SHOWN ON THE ENLARGED SITE PLAN. THE 90 DEGREE ELBOWS SHALL HAVE A 24" MINIMUM BENDING RADIUS. COORDINATE REQUIREMENTS WITH ITS PLANS PRIOR TO ROUGH IN.
- 3 INSTALL (2) 2" PVC CONDUITS STUBBED UP UNDER THE TOLLING COMMUNICATIONS CABINET FOR GANTRY MOUNTED CCTV CAMERAS. REFER TO SITE PLAN FOR CONDUIT ROUTING.
- 4 REFER TO AE-126 AND SITE PLAN FOR CONDUIT ROUTINGS.
- 5 (2) 4" CONDUIT STUB-UP FOR E6 READER. REFER TO SITE PLAN FOR CONDUIT ROUTING.
- 6 FTE COMMUNICATIONS CABINET. REFER TO TSP SECTION 27 11 16 FOR REQUIREMENTS.
- 7 1" C, CAT6 CABLE WITH RJ45 CONNECTORS WITH 6'-0" OF SLACK CABLE ON EACH END. STUB CONDUIT 2" BELOW TOP OF COMMUNICATIONS BACKBOARD. ROUTE CABLE FROM TELCO EQUIPMENT TO NETWORK SWITCH IN THE COMMUNICATIONS CABINET.
- 8 PROVIDE A 7-POSITION COPPER GROUND BAR WITHOUT PLATING APPROVED BY TELEPHONE COMPANY. BOND TO THE CONCRETE-ENCASED ELECTRODE BY #4, BARE, STRANDED-COPPER CONDUCTOR.
- 9 PROVIDE (2) 2"C. ROUTED FROM COMMUNICATIONS BACKBOARD TO TELCO PULL BOX. SEE SITE PLAN FOR DETAILS. CONDUIT BEND RADIUS SHALL NOT BE LESS THAN 24". COORDINATE REQUIREMENTS WITH TELEPHONE COMPANY PRIOR TO ROUGH IN.
- 10 PAINT A 2'X4' AREA ON PLYWOOD WALLS WITH FIRE-RETARDANT PAINT. VERIFY REQUIREMENTS WITH TELECOMMUNICATION COMPANY.



REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:		DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	BUILDING - TOLLING SYSTEM PLAN AT RAMP F		AE-110
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 35

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



REFERENCE NOTES:


- 1 (3) 120VAC 20A DEDICATED CIRCUITS FROM PANEL C1. SIMPLEX RECEPTACLES, COLOR TO BE ORANGE, TWIST LOCK (NEMA L5-20R)
- 2 (4) 120VAC 20A DEDICATED CIRCUITS FROM PANEL C1. SIMPLEX RECEPTACLES, COLOR TO BE ORANGE, TWIST LOCK (NEMA L5-20R)
- 3 MOUNT RECEPTACLES TO TOP OF CABLE TRAY IN SINGLE GANG BACK BOX. SECURE BACK BOX TO CABLE TRAY WITH MOUNTING BRACKET MANUFACTURED BY CABLE TRAY MANUFACTURER. PROVIDE STRAIN RELIEF CORD GRIPS FOR CABLES ENTERING BACK BOX KELLEMS OR EQUAL.
- 4 PROVIDE DROP-OUT FITTINGS WITH 4" RADIUS ABOVE EACH CABINET WHERE CABLES LEAVE CABLE TRAY.
- 5 TOLLING CABINET ORIENTATION IN BLDG. MAY DIFFER FROM ORIENTATION SHOWN ON THIS DWG. COORDINATE ORIENTATION WITH BLDG AND SITE PLANS.
- 6 FURNISH AND INSTALL FTE TOLLING COMMUNICATIONS CABINET. REFER TO TSP SECTION 27 11 16 FOR REQUIREMENTS.

1 TOLLING COMMUNICATION CABINET DETAIL
 AE-111 SCALE: N.T.S.


1
 AE-126

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: BUILDING TOLLING COMMUNICATION CABINET DETAIL		DRAWING NO. AE-111
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 36
						SR 429	SEMINOLE	240200-2-52-01		

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




1 INTERIOR ELEVATION
 AE-112 3/8" = 1'-0"



2 BUILDING SLAB CONDUIT PENETRATION DETAIL
 AE-112 SCALE: N.T.S

NOTE:
 THIS DETAIL APPLIES TO WALL MOUNTED EQUIPMENT ONLY. CONDUIT STUBBED-UP UNDER TOLLING CABINETS SHALL BE INSTALLED IN ACCORDANCE WITH REQUIREMENTS SPECIFIED ON DWG. AE-A506. THE FINAL POSITIONING OF ALL CONDUIT STUB-UPS IN THE BUILDING FLOOR SLAB AND WALL PENETRATION POINTS, SHALL BE FIELD VERIFIED AND APPROVED BY THE DEPARTMENT PRIOR TO THE BUILDING FLOOR SLAB BEING POURED.




REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION


AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING INTERIOR ELEVATION (1 OF 3)	DRAWING NO. AE-112
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 37



1 INTERIOR ELEVATION
 AE-113 SCALE: 3/8" = 1'-0"




REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103


STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING INTERIOR ELEVATION (2 OF 3)	DRAWING NO. AE-113
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 38


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 INTERIOR ELEVATION
 AE-114 SCALE: 3/8" = 1'-0"



2 INTERIOR ELEVATION
 AE-114 SCALE: 3/8" = 1'-0"



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION


AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:
BUILDING INTERIOR ELEVATION (3 OF 3)
PROJECT NAME:
SR 429 WEKIVA PARKWAY SECTION 7A

DRAWING NO.	AE-114
SHEET NO.	39


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




SIGN SPEC:

- PROVIDE ALUMINUM SHEET OF ALLOY AND TEMPER RECOMMENDED BY THE SIGN MANUFACTURER FOR THE TYPE OF USE AND FINISH INDICATED, AND WITH THE STRENGTH AND DURABILITY PROPERTIES NO LESS THAN SPECIFIED IN ASTM B-209 FOR 5005-H15.
- USE FASTENERS FABRICATED FROM METALS THAT ARE NOT CORROSIVE TO THE SIGN MATERIAL AND MOUNTING SURFACE.
- PROVIDE SIGN COPY THAT COMPLIES WITH THE REQUIREMENTS INDICATED FOR SIZE, STYLE, SPACING, CONTENT, POSITION, MATERIAL, FINISHES AND COLOR OF LETTERS, NUMBERS, AND OTHER GRAPHIC DEVICES.
- PROVIDE BAKED-ENAMEL FINISH:
 AA-M4XC12C42R1x (MECHANICAL FINISH: MANUFACTURER'S STANDARD, OTHER NONDIRECTIONAL TEXTURED; CHEMICAL FINISH: CHEMICAL CONVERSION COATING, ACID CHROMATE-FLUORIDE-PHOSPHATE PRETREATMENT; ORGANIC COATING: AS SPECIFIED BELOW). APPLY BAKED ENAMEL IN COMPLIANCE WITH PAINT MANUFACTURER'S SPECIFICATIONS FOR CLEANING, CONVERSION COATING, AND PAINTING.

1 EMERGENCY POWER SHUTOFF SWITCH DETAIL
 AE-120 SCALE: N.T.S.



2 EMERGENCY POWER SHUTOFF WIRING DIAGRAM
 AE-120 SCALE: N.T.S.



3 EMERGENCY POWER SHUTOFF RISER DIAGRAM
 AE-120 SCALE: N.T.S.

REFERENCE NOTES:


- 1 EPO STATION MOUNTED 6 FT ABOVE GRADE ON THE OUTSIDE WALL ADJACENT TO THE TOLL EQUIPMENT BUILDING DOOR, REFER TO FLOOR PLANS FOR PLAN LOCATION. 30mm NON-ILLUMINATED, TURN-TO-RELEASE, MUSHROOM PUSH BUTTON OPERATOR (COLOR RED), TRIGGER ACTION, WITH ONE NORMALLY OPEN CONTACT. CLASS 9001, CORROSION RESISTANT, UL TYPE 4 AND NEMA 4 RATED. INSTALLED WITH UL TYPE 4, NEMA 4 RATED, GUARDED ENCLOSURE (COLOR GRAY), TO PROTECT AGAINST INADVERTENT OPERATION OF MUSHROOM PUSH BUTTON. ENCLOSURE MATERIAL TO BE DIE CAST ZINC.
- MUSHROOM PUSH BUTTON (SQ-D CAT #SKR16H13), WITH ONE N.O. CONTACT (SQ-D CAT #KA1), GUARDED ENCLOSURE (SQ-D CAT #KYG1) OR APPROVED EQUAL.
- WHEN THE MUSHROOM PUSH BUTTON IS DEPRESSED, TO THE "OFF" POSITION, THE BACKUP GENERATOR WILL SHUT DOWN IF IT IS RUNNING. ENSURE THE BACKUP GENERATOR WILL NOT START UNTIL THE EPO SWITCH IS RETURNED TO THE "ON" POSITION, TURN-TO-RELEASE, AND THE SHUTDOWN ALARMS ARE CLEARED FROM THE OPERATOR CONTROL PANEL.
- 2 INSTALL A 10" X 10" ALUMINUM SIGN WITH RED FIELD AND 1/2" HIGH LETTERS DIRECTLY ABOVE THE EPO STATION.
- 3 (1) BELDEN #5140F1 CABLE WITH TINNED COPPER CONDUCTORS, OR APPROVED EQUAL.
- 4 EMERGENCY POWER OFF TERMINALS ON THE BACKUP GENERATOR.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION


AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


SHEET TITLE: BUILDING - ELECTRICAL DETAILS	DRAWING NO. AE-120
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 40



1 SERVICE ENTRANCE, UPS & GENERATOR GROUND REQUIREMENTS
 AE-121 SCALE: N.T.S.




2 GENERATOR GROUND DETAIL
 AE-121 SCALE: N.T.S.



3 GROUND INSPECTION WELL DETAIL
 AE-121 SCALE: N.T.S.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	BUILDING - GROUNDING DETAILS (1 OF 2)	AE-121
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 41

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




NOTES:


1. ALL HARDWARE BOLTS, NUTS, WASHERS, ETC. SHALL BE SOLID COPPER OR BRONZE.
2. COPPERPLATING IS NOT ACCEPTABLE. GROUND BUSBAR SHALL BE 1/4" THICK x 2" WIDE FLAT COPPER.
3. INCREASE LENGTH AS REQUIRED FOR NUMBER OF CONNECTIONS. PROVIDE 2" SPACING BETWEEN LUGS.

1 GROUND BUSBAR DETAIL
 AE-122 SCALE: N.T.S.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	BUILDING - GROUNDING DETAILS (2 OF 2)	AE-122
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME:
								SR 429 WEKIVA PARKWAY SECTION 7A	42





1 DOWN CONDUCTOR CONDUIT ENLARGED WALL SECTION
 AE-123 SCALE: N.T.S.




2 DOWN CONDUCTOR THRU ROOF ENLARGED WALL SECTION
 AE-123 SCALE: N.T.S.


GENERAL NOTES:
 1. REFER TO SPECIFICATIONS FOR MATERIALS AND ADDITIONAL REQUIREMENTS.
 2. OBTAIN MASTER LABEL FOR LIGHTNING PROTECTION SYSTEM.



5 DOWN CONDUCTOR BUILDING WALL SECTION
 AE-123 SCALE: N.T.S.



2 THRU ROOF CONNECTOR WITH FLASHING TUBE AND CABLE BASE
 AE-123 SCALE: N.T.S.



4 PARAPET AIR TERMINAL DETAIL
 AE-123 SCALE: N.T.S.


REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING - LIGHTNING PROTECTION DETAILS	DRAWING NO. AE-123
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 43

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 SECURITY/ACCESS CONTROL BUILDING DOOR DETAIL
 AE-124 SCALE: N.T.S.

GENERAL NOTES:


1. PROVIDE DOOR-MOUNTED SECURITY/ACCESS CONTROL DEVICE, OUTLET BOXES, WIRING, ELECTRIC LEVER TRIM, ENCLOSURES & ALL REQUIRED CABLING, REFER TO TSP 28 05 14 & 08 71 00.
2. SEE AE-104, AE-109 & AE-125 FOR DETAILS.
3. SEE AE-010 FOR SECURITY CARD ACCESS SYSTEM SYMBOL LEGEND.

REFERENCE NOTES:

- 1 ACCESS CONTROL PANEL ENCLOSURE 20"Wx24"H, HINGED DOOR AND BACK PANEL.
- 2 1" C.
- 3 4" SQUARE, SURFACE MOUNTED BOX WITH BLANK PLATE.
- 4 6" X 6" X 3" METAL JUNCTION BOX. MOUNT ON SECURE SIDE ABOVE DOOR.
- 5 BACK BOXES FOR CARD READERS SHALL BE MOUNTED 48" AFF.
- 6 BACK BOXES FOR CARD ACCESS DEVICES SHALL BE FLUSH MOUNTED.
- 7 SINGLE GANG BACK BOX FOR PROXIMITY CARD READER.
- 8 STUB CONDUIT OVER CABLE TRAY. PROVIDE INSULATED THROAT GROUNDING BUSHING ON END OF CONDUIT AND BOND CONDUIT TO CABLE TRAY WITH #6 AWG BARE COPPER GROUNDING CONDUCTOR.

SECURITY/ACCESS CONTROL WIRING NOTES:


- NOTE: CONDUCTORS SHALL BE SHIELDED, STRANDED UON.
- | | | |
|---|----------------------------------|---|
| A | CARD READER: | 18AWG-6 CONDUCTOR SHIELDED. |
| B | REQUEST TO EXIT: | 18AWG-2 CONDUCTOR. |
| C | ELECTRIFIED LEVER TRIM: | 18AWG-2 CONDUCTOR. |
| D | DOOR CONTACT: | 18AWG-4 CONDUCTOR. (PROVIDED WITH DOOR CONTACT) |
| E | DOOR CONTACT: | 18AWG-2 CONDUCTOR. |
| F | REQUEST TO EXIT INFRARED SENSOR: | 18AWG-2 CONDUCTOR. |




2 SECURITY CARD ACCESS SYSTEM RISER DIAGRAM
 AE-124 SCALE: N.T.S.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: BUILDING - SECURITY AND ACCESS CONTROL SYSTEM DETAILS		DRAWING NO. AE-124
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		SHEET NO.
						SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A	


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




1 FLUSH MOUNTED EXTERIOR DEVICE
 AE-125 SCALE: N.T.S.




2 SURFACE MOUNTED EXTERIOR CCTV OUTLET
 AE-125 SCALE: N.T.S.



3 INTERIOR CCTV OUTLET BOX
 AE-125 SCALE: N.T.S.



4 SURFACE MOUNTED LIGHT FIXTURE
 AE-125 SCALE: N.T.S.



5 SURFACE MOUNTED EXTERIOR DEVICE
 AE-125 SCALE: N.T.S.

GENERAL NOTES:

1. THE CONTRACTOR TO MAKE NECESSARY PROVISIONS FOR PROVIDING CONDUIT OPENINGS AND AVOID DISTURBANCE OF BUILDING REINFORCING MATERIAL.


REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING - RACEWAY INSTALLATION DETAILS	
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	
DRAWING NO. AE-125	SHEET NO. 45


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



1 TOLLING CABINETS-CONDUIT STUB-UP LAYOUT
 AE-126 SCALE: N.T.S.

GENERAL NOTES:

1. CONDUIT BELOW CABINETS SHALL BE STUBBED-UP 1" AFF.
2. PROVIDE INSULATED THROAT GROUNDING BUSHINGS ON METALLIC CONDUITS STUBBED UP UNDER TOLLING CABINET SUPPORT FRAME.
3. PROVIDE END BELL FITTINGS ON ALL PVC (LOOP) CONDUITS STUBBED UP UNDER THE TOLLING CABINET SUPPORT FRAME.
4. COORDINATE STUB-UP LOCATIONS AND CABINET ORIENTATION WITH ELECTRICAL PLANS AND ITS CONTRACTOR.
5. RAISED METAL FRAME TO SUPPORT THE TOLLING EQUIPMENT AND TOLLING COMMUNICATIONS CABINET WILL BE FURNISHED AND INSTALLED BY THE TOLLING FACILITY CONTRACTOR. CABINET SUPPORT FRAME DETAILS ARE SHOWN FOR CONDUIT STUB-UP COORDINATION ONLY.
6. COMMUNICATIONS CABINET WILL BE FURNISHED AND INSTALLED BY THE TOLLING FACILITY CONTRACTOR. SEE THE ITS PLANS FOR FURTHER INFORMATION.
7. TOLLING EQUIPMENT CABINETS WILL BE FURNISHED AND INSTALLED BY THE DEPARTMENT'S TOLL EQUIPMENT CONTRACTOR AFTER THE ENTIRE SITE IS COMPLETE.
8. TOLLING CABINET ORIENTATION IN BUILDING MAY DIFFER FROM ORIENTATION SHOWN ON THIS DWG. COORDINATE ORIENTATION WITH BUILDING AND SITE PLANS.
9. BUILDING WILL BE FABRICATED OFF SITE. CONDUIT STUB-UP LOCATIONS MUST BE COORDINATED WITH BUILDING FABRICATOR.




CONDUIT SCHEDULE

CABINET SUPPORT FRAME NOTES:


ALL CABINETS (TOLLING EQUIPMENT AND TOLLING COMMUNICATIONS) THAT ARE TO BE INSTALLED IN TOLL EQUIPMENT BUILDINGS SHALL BE INSTALLED ON AN ALUMINUM CABINET SUPPORT FRAME FURNISHED AND INSTALLED BY THE CONTRACTOR. THE CABINET FRAME SUPPORT SHALL BE AS FOLLOWS:

1. SIZE 148" L X 36" W X 8" H.
2. THE FRAME AREA WHERE THE CABINETS SIT SHALL BE 2.5" WIDE AT A MINIMUM OR AS REQUIRED TO ALLOW FOR ALL CABINETS TO BE PROPERLY PLACED OVER THE FRAME. GROUND BOTH ENDS OF FRAME TO CONCRETE ENCASED ELECTRODE. PROVIDE TWO HOLES IN VERTICAL RAIL AT EACH END FOR GROUNDING LUG ATTACHMENT.
3. IT SHALL HAVE TWO CROSS RIBS MADE OF THE SAME MATERIAL. THE CROSS RIBS SHALL BE 4" WIDE. ONE CROSS RIB SHALL BE LOCATED AT 62" FROM ONE END OF THE CABINET SUPPORT FRAME AND THE OTHER CROSS RIB SHALL BE LOCATED 54" FROM THE OPPOSITE END OF THE CABINET SUPPORT FRAME.
4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE STRUCTURAL DESIGN OF THE ALUMINUM CABINET SUPPORT FRAME, INCLUDING PLATE THICKNESS, ALUMINUM GRADE, ETC AS REQUIRED TO SUPPORT A LOAD OF UP TO 600 POUNDS PER CABINET. THE CONTRACTOR DESIGN SHALL ALSO ALLOW FOR THE PLACEMENT OF NEW TOLLING EQUIPMENT AND TOLLING COMMUNICATIONS CABINETS WITHIN THE FRAME PER THE CABINET MANUFACTURER'S RECOMMENDATIONS.
5. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THAT THE ALUMINUM CABINET SUPPORT FRAME CAN SUPPORT THE TOLLING EQUIPMENT AND TOLLING COMMUNICATIONS CABINET LOADS. PROVIDE 1/2" DIAMETER MOUNTING HOLES AT FOUR PLACES ON BOTTOM RAIL AND BOLT THE FRAME TO THE FLOOR WITH 1/4" X 2" CADMIUM PLATED CONCRETE SCREWS. BOLT THE CABINETS/RACKS TO THE FRAME WITH MANUFACTURER'S STANDARD CLIP ANCHORS.
6. AFTER THE TEC HAS FULLY COMPLETED THEIR ACTIVITIES AT EACH TOLLING POINT, THE CONTRACTOR SHALL FURNISH AND INSTALL ALUMINUM DIAMOND GRATING PLATES TO COVER THE EMPTY SPACES OF THE CABINET SUPPORT FRAMES NOT COVERED BY ALL CABINETS OR SUPPORT FRAMES (TOLLING EQUIPMENT AND COMMUNICATIONS) IN EACH TOLL EQUIPMENT BUILDING. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE STRUCTURAL DESIGN OF THE ALUMINUM DIAMOND GRATING PLATES, INCLUDING PLATE THICKNESS, ALUMINUM GRADE, ETC. AS REQUIRED TO SUPPORT A SINGLE POINT LOAD OF UP TO 350 POUNDS PER PLATE. THE DESIGN SHALL TAKE INTO ACCOUNT THAT NO PERMANENT DEFORMATIONS OCCUR TO THE PLATE AFTER THE 350-POUND SINGLE POINT LOAD IS APPLIED. THE PLATES SHALL BE SCREWED IN (COUNTER SUNK FASTENERS FLUSH WITH TOP OF PLATING) TO THE CABINET SUPPORT FRAMES AND PROPERLY DESIGNED TO SUPPORT ALL APPLICABLE LOADS. THE DIAMOND GRATING PLATES SHALL BE REMOVABLE TO ALLOW ACCESS TO TOLLING EQUIPMENT, COMMUNICATIONS, ETC. CABLING.



2 WORKING SPACE CONDUIT STUB-UP LAYOUT
 AE-126 SCALE: N.T.S.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	BUILDING - CONDUIT STUB-UP DETAILS	AE-126
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 46



1 BUILDING – POWER RISER DIAGRAM
AE-130 N.T.S.

REFERENCE NOTES:

- (1) PROVIDE 60KW STANDBY GENERATOR SET, 120/240V, 1Ø, 3W WITH WEATHERPROOF ENCLOSURE. PROVIDE MODBUS RTU MODULE. GENERATOR SHALL BE CLASSIFIED NFPA 110, LEVEL 2, TYPE 10.
- (2) PAD-MOUNTED UTILITY TRANSFORMER. 120/240V, 1Ø, 3W, 60HZ SECONDARY. COORDINATE REQUIREMENTS WITH LOCAL POWER COMPANY. REFER TO SITE PLAN FOR ADDITIONAL DETAILS.
- (3) SERVICE LATERAL: 3-500KCMIL IN 3"CONDUIT, 36" MINIMUM BELOW GRADE. RISER SHALL BE RGS CONDUIT. REFER TO AE-121 FOR BONDING REQUIREMENTS.
- (4) #2/0 BARE, STRANDED-COPPER GROUNDING CONDUCTOR.
- (5) 20' LONG X 5/8" DIAMETER COPPER-CLAD STEEL GROUND ROD.
- (6) 400A, FEED-THRU WALL-MOUNTED METER SOCKET, PAINTED ALUMINUM, WITH LEVER BYPASS AND GROUNDING PER POWER CO. REQUIREMENTS, FURNISHED & INSTALLED BY CONTRACTOR. CONTRACTOR SHALL COORDINATE AND PROVIDE A UTILITY COMPANY APPROVED METER SOCKET.
- (7) PANELBOARD "MDP" – 400A, 2P MCB, 3W, 240V, N.O. AUXILIARY CONTACT WITH GROUND BUS, INSULATED NEUTRAL BUS, NEMA 1 ENCLOSURE. PROVIDE NAMEPLATE "MAIN #1 OF 2. MAIN #2 IS LOCATED INSIDE GENERATOR ENCLOSURE". PANELBOARD MUST BE LISTED AS SUITABLE FOR USE AS SERVICE ENTRANCE EQUIPMENT.
- (8) PROVIDE TYPE 1 MODULAR PRIMARY SERVICE (ENTRANCE) SPD WITH INTEGRAL DISCONNECTING MEANS. PROVIDE #6 AWG LEADS IN 3/4"C. NIPPLE. REFER TO NOTE 30 AND TSP 26 43 13 FOR DETAILS.
- (9) SERVICE GROUNDING ELECTRODE CONDUCTOR, #2/0 BARE, STRANDED-COPPER. 36" MINIMUM BELOW GRADE.
- (10) ELECTRICAL DISTRIBUTION PANELBOARD "EDP", 120/240V, SINGLE PHASE, 3W. REFER TO PANELBOARD SCHEDULE ON DWG. AE-131.
- (11) NOT ALL GROUNDING CONDUCTORS ARE SHOWN ON THIS DWG. REFER TO DETAIL 1 ON AE-121 FOR ADDITIONAL BONDING REQUIREMENTS.
- (12) AUTOMATIC TRANSFER SWITCH, 400A, 120/240V, 3 POLE, 3W (2 POLE SINGLE-PHASE WITH SWITCHED NEUTRAL), NEMA TYPE 1 ENCLOSURE.
- (13) (2) 2"CONDUIT EACH WITH 3 #3/0 & 1 #2/0 GND.
- (14) PANELBOARD. REFER TO PANELBOARD SCHEDULES ON DWG. AE-131.
- (15) GENERATOR CIRCUIT BREAKER "GCB", 400A, 2P, 240V, AUXILIARY CONTACT SOLID NEUTRAL, GROUND BUS IN NEMA 3R ENCLOSURE. PROVIDE NAMEPLATE "MAIN #2 OF 2. MAIN #1 IS LOCATED INSIDE BUILDING".
- (16) #2/0 BARE STRANDED COPPER GROUNDING CONDUCTOR BETWEEN SUPPLEMENTAL GROUND BUSBAR AND LIGHTNING PROTECTION SYSTEM. INSTALL CONDUCTOR IN 1" SCH. 80 PVC CONDUIT WHERE EXPOSED.
- (17) REFER TO SITE PLAN FOR CIRCUITING REQUIREMENTS.
- (18) 15 KVA UPS, 120/240VAC, SINGLE PHASE, 3W WITH REMOTE SHUT OFF CONTACT MODBUS TCP/IP NETWORK MONITOR CARD WITH DB-9 CONNECTION, BATTERY MODULES AND GROUNDING LUG. REFER TO TSP 26 33 53 FOR DETAILS.
- (19) 3 #1 & 1 #6 GND IN 1 1/2" CONDUIT.
- (20) ENGINE JACKET HEATER.
- (21) GROUNDING CONDUCTOR FROM PANELBOARD "MDP" GROUND BUSBAR TO SUPPLEMENTAL GROUND BUSBAR, #2/0 BARE STRANDED COPPER.
- (22) PROVIDE TYPE 2 SECONDARY SERVICE SPD.
- (23) MAIN BONDING JUMPER #2/0 BARE STRANDED COPPER.
- (24) TYPE 1 PRIMARY SERVICE ENTRANCE SPD.
- (25) PROVIDE 240V, 125A, WALL MOUNTED BYPASS SWITCH. REFER TO TSP 26 33 53 FOR DETAILS.
- (26) PROVIDE CONCRETE ENCASED ELECTRODE IN ACCORDANCE WITH NEC ARTICLE 250.
- (27) SPLICE SPD CONDUCTORS TO INCOMING GENERATOR CONDUCTORS INSIDE ATS ENCLOSURE WITH A UL LISTED SPLICE.
- (28) PROVIDE LIQUID TIGHT FLEXIBLE METAL CONDUIT FROM 4" AFF TO UPS.
- (29) SPD SHALL BE LOCATED SUCH THAT THE MAXIMUM SPD BRAIDED/TWISTED LEADS DO NOT EXCEED 24 INCHES AND HAVE NO SHARP TURNS.
- (30) UNDERGROUND CONDUIT SHALL BE PVC SCH. 80, UON. UNDERGROUND CONDUIT SHALL TRANSITION TO RGS CONDUIT WITH RGS TO PVC FITTINGS. CONDUIT SHALL BE RGS ABOVE GRADE THROUGH AND INCLUDING THE FIRST 90° FITTING UNDERGROUND, UON. APPLY 2-COAT BITUMASTIC COATING TO DIRECT BURIED PORTION OF RGS CONDUIT, UP TO AND INCLUDING 6" ABOVE FINAL GRADE. REFER TO TSP FOR FURTHER INFORMATION.
- (31) BOND EACH END OF THE RAISED ALUMINUM TOLLING CABINET FRAME TO THE CONCRETE ENCASED ELECTRODE IN THE BUILDING FOUNDATION. REFER TO BUILDING POWER PLAN AND GROUND REQUIREMENTS ON DWG AE-121.

AVAILABLE FAULT CURRENT AT EQUIPMENT (KA)	
	BUILDING
PANEL "MDP"	10.7
ATS (NORM)	10.7
ATS (EMERGENCY)	10.7
PANEL "EDP"	10.2
PANEL C1	7.3
UPS-1	9.5
BYPASS SWITCH	9.5
BPS-1	

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	BUILDING - POWER RISER DIAGRAM	AE-130
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 47

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

120/240V.,1Ø,3W 22 KAIC MIN. FTL, SER												400A, MAIN CKT. BKR SURFACE MOUNTED NEMA TYPE 1		
CKT. NO.	KVA	BKR	WIRE SIZE	CON DUIT	LOAD	CKT. NO.	KVA	BKR	WIRE SIZE	CON DUIT	LOAD			
1	-	-	-	-	-	2	-	60/2	6	3/4	SPD (5)			
3	-	-	-	-	-	4	-	-	-	-	-			
5	0.2	20/1	12	3/4	RECEPTACLE	6	-	-	-	-	-			
7	0.2	20/1	12	3/4	RECEPTACLE	8	-	-	-	-	-			
9	-	-	-	-	-	10	-	-	-	-	-			
11	-	-	-	-	-	12	-	-	-	-	-			
13	-	-	-	-	-	14	-	-	-	-	-			
15	-	-	-	-	-	16	-	-	-	-	-			
17	-	-	-	-	-	18	-	-	-	-	-			
19	-	-	-	-	-	20	-	-	-	-	-			
TOTAL CONNECTED LOAD: 27.10 KVA														
TOTAL DEMAND LOAD: 27.48 KVA														

(1)(2)(7)(8)

120/240V.,1Ø,3W 22 KAIC MIN.												400A, M.L.O. SURFACE MOUNTED NEMA TYPE 1		
CKT. NO.	KVA	BKR	WIRE SIZE	CON DUIT	LOAD	CKT. NO.	KVA	BKR	WIRE SIZE	CON DUIT	LOAD			
1	0.4	20/1	12	3/4	LIGHTING (INTERIOR)	2	0.4	20/1	12	3/4	RECEPT.			
3	0.1	20/1	12	3/4	LIGHTING (BLDG. EXT.)	4	-	20/1	-	-	SPARE			
5	-	20/1	-	-	SPARE	6	-	20/1	-	-	SPARE			
7	-	20/1	-	-	SPARE	8	0.2	20/1	10	1	PTZ CAMERA			
9	3.30	30/2	10	3/4	AC-1	10	0.5	20/1	10	1	BATTERY CHARGER			
11	-	-	-	-	-	12	1.5	20/1	10	1	ENG. JACK HEATER			
13	3.30	30/2	10	3/4	AC-2	14	0.5	20/1	10	1	FUEL TANK MONITOR			
15	-	-	-	-	-	16	0.5	20/1	12	3/4	SECURITY SYSTEM			
17	-	-	-	-	-	18	-	20/1	-	-	SPARE			
19	16.0	100/2	1	1 1/2	PNL 'C1' VIA UPS-1	20	-	20/1	-	-	SPARE			
21	-	100/2	1	1 1/2	UPS-1 BYPASS	22	-	20/1	-	-	SPARE			
23	-	20/1	-	-	SPARE	24	-	20/1	-	-	SPARE			
25	-	20/1	-	-	SPARE	26	-	20/1	-	-	SPARE			
27	-	20/1	-	-	SPARE	28	-	20/1	-	-	SPARE			
29	-	20/1	-	-	SPARE	30	-	20/1	-	-	SPARE			
31	-	20/1	-	-	SPARE	32	-	20/1	-	-	SPARE			
33	-	20/1	-	-	SPARE	34	-	20/1	-	-	SPARE			
35	-	20/1	-	-	SPARE	36	-	20/1	-	-	SPARE			
37	-	20/1	-	-	SPARE	38	-	20/1	-	-	SPARE			
39	-	30/2	10	3/4	SPD (5)	40	-	20/1	-	-	SPARE			
41	-	-	-	-	-	42	-	20/1	-	-	SPARE			
TOTAL CONNECTED LOAD: 26.70 KVA														
TOTAL DEMAND LOAD: 27.08 KVA					SEE NOTES (1)(2)(8)									

REFERENCE NOTES:

- (1) PANELS SHALL BE PROVIDED WITH GROUND BAR & INSULATED NEUTRAL BAR.
- (2) MINIMUM 22,000 AIC FOR ALL CIRCUIT BREAKERS IN THE PANEL.
- (3) ALL CIRCUIT BREAKERS FOR PANEL C1 SHALL BE AS PER TSP 26 24 17.
- (4) PROVIDE CONTROLLER IN PANEL "C1".
- (5) SCH. 80 PVC CONDUIT.
- (6) PROVIDE BRANCH CIRCUIT MONITOR FACTORY INSTALLED.
- (7) PROVIDE FEED-THRU LUGS.
- (8) FOR ALL BRANCH CIRCUITS, SIZE THE EQUIPMENT GROUND PER NEC TABLE 250.122. UPSIZE FOR VOLTAGE DROP IF REQUIRED.

120/240V.,1Ø,3W 22 KAIC MIN.												100A, MAIN CKT. BKR SURFACE MOUNTED NEMA TYPE 1		
TYPICAL PANEL "C1" SCHEDULE (CRITICAL POWER)														
CKT. NO.	KVA	BKR	WIRE SIZE	CON DUIT	LOAD	CKT. NO.	KVA	BKR	WIRE SIZE	CON DUIT	LOAD			
1	0.5	20/1	12	-	TOLL EQUIP.	2	0.5	20/1	12	-	TOLL EQUIP.			
3	0.5	20/1	12	-	TOLL EQUIP.	4	0.5	20/1	12	-	TOLL EQUIP.			
5	0.5	20/1	12	-	TOLL EQUIP.	6	0.5	20/1	12	-	TOLL EQUIP.			
7	0.5	20/1	12	-	TOLL EQUIP.	8	0.5	20/1	12	-	TOLL EQUIP.			
9	0.5	20/1	12	-	TOLL COMM. CABINET	10	0.5	20/1	12	-	TOLL COMM. CABINET			
11	0.5	20/1	12	-	TOLL COMM. CABINET	12	0.5	20/1	12	-	TOLL COMM. CABINET			
13	0.5	20/1	12	-	TOLL COMM. CABINET	14	0.5	20/1	12	-	TOLL COMM. CABINET			
15	0.5	20/1	-	-	FUTURE	16	0.5	20/1	-	-	FUTURE			
17	0.5	20/1	-	-	FUTURE	18	0.5	20/1	-	-	FUTURE			
19	0.5	20/1	-	-	FUTURE	20	0.5	20/1	-	-	FUTURE			
21	0.5	20/1	-	-	FUTURE	22	0.5	20/1	-	-	FUTURE			
23	0.5	20/1	-	-	FUTURE	24	0.5	20/1	-	-	FUTURE			
25	0.5	20/1	12	3/4	SCADA PNL	26	0.5	20/1	-	-	FUTURE			
27	0.5	20/1	12	3/4	COMM. REC.	28	0.5	20/1	-	-	FUTURE			
29	0.5	20/1	-	-	FUTURE	30	0.5	20/1	-	-	FUTURE			
31	-	20/1	-	-	FUTURE	32	-	20/1	-	-	FUTURE			
33	-	20/1	-	-	SPARE	34	-	20/1	-	-	SPARE			
35	-	20/1	-	-	SPARE	36	-	20/1	-	-	SPARE			
37	-	20/1	-	-	SPARE	38	-	20/1	-	-	SPARE			
39	-	20/1	-	-	SPARE	40	-	-	-	-	-			
41	-	20/1	-	-	SPARE	42	-	30/2	10	3/4	SPD (5)			
TOTAL CONNECTED LOAD: 15.0 KVA														
TOTAL DEMAND LOAD: 15.0 KVA					SEE NOTES (1)(2)(3)(4)(6)(8)									

PANEL "MDP" LOAD SUMMARY	
CONTINUOUS LOADS	1.50 KVA
25% OF CONTINUOUS LOADS	0.38 KVA
NON-CONTINUOUS LOADS	25.60 KVA
TOTAL NEC DEMAND LOAD (KVA)	27.48 KVA
TOTAL NEC DEMAND LOAD @ 240V, 1Ø (AMPERES)	115 AMPERES

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA
DEPARTMENT OF TRANSPORTATION

ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: BUILDING - PANEL SCHEDULES AND LOAD SUMMARY	DRAWING NO. AE-131
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 48

GENERAL NOTES:


1. FOR ADDITIONAL REQUIREMENTS, SEE TSP 26 09 13 SCADA SYSTEMS.
2. ALL CONDUCTORS SHALL BE COPPER.
3. DATA WIRING AND POWER WIRING SHALL BE RUN IN SEPARATE CONDUITS.
4. THE CONTRACTOR INSTALLED SCADA ROUGH-IN SHALL BE INSPECTED BY THE DEPARTMENT PRIOR TO ACCEPTANCE.

REFERENCE NOTES:

- 1) PROVIDE LINE SIDE CURRENT AND VOLTAGE SENSING. ELECTRICAL CONTRACTOR SHALL FIELD INSTALL CLASS B CURRENT TRANSFORMERS WITH 0-5 AMP SECONDARY FOR EACH PHASE WITH CT SHORTING BLOCK CAT # CTSB-10. ELECTRICAL CONTRACTOR SHALL FIELD INSTALL VOLTAGE SENSING FOR EACH PHASE AND NEUTRAL WITH FUSED TERMINAL BLOCK CAT # VTFB-6.
- 2) PROVIDE CONTACTS TO MONITOR THE POSITION OF THE CIRCUIT BREAKER. AUXILIARY CONTACTS CLOSE WHEN THE BREAKER IS CLOSED AND OPEN WHEN THE BREAKER IS OPEN.
- 3) PROVIDE CURRENT TRANSDUCER TO MEASURE THE CURRENT IN THE BRANCH CIRCUIT OF EACH AIR CONDITIONER. VERIS INDUSTRIES HAWKEYE MODEL# 921 SPLIT-CORE.
- 4) PROVIDE POWER LOGIC BRANCH CIRCUIT MONITOR, FACTORY INSTALLED.
- 5) PROVIDE CONTROLLER CAPABLE OF REMOTELY OPERATING THE TOLLING SYSTEM BRANCH CIRCUIT BREAKERS IN THE CRITICAL POWER PANEL.
- 6) FINAL CONNECTION SHALL BE RUN OVERHEAD UTILIZING THE CABLE TRAY, THEN TO THE COMMUNICATION RACK BY THE DEPARTMENT.
- 7) PROVIDE AUXILIARY CONTACTS TO MONITOR THE POSITION OF THE ATS. CONTACTS ARE CLOSED WHEN THE ATS IS IN NORMAL POSITION AND OPEN WHEN ATS IS IN EMERGENCY POSITION.
- 8) PROVIDE NETWORK INTERFACE CARD IN THE UPS. CARD COMMUNICATES WITH THE NETWORK ROUTER VIA ETHERNET AND MONITORS THE UPS PARAMETERS, ALARMS, BY-PASS CONDITION AND BATTERY CONDITION.
- 9) PROVIDE MONITORING, PER MANUFACTURER'S SPECIFICATIONS, OF THE EXTERNAL UPS MAINTENANCE BYPASS SWITCH POSITION.
- 10) SCADA CONTROL PANEL. SEE SPECIFICATIONS SECTION 26 09 13.
- 11) PROVIDE SURGE PROTECTION DEVICE - DIN RAIL MOUNTED. TYPICAL OF 24. ALL EXTERIOR SCADA METALLIC WIRING RUNS ENTERING THE BUILDING SHALL BE CONNECTED FIRST TO A SPD, PRIOR TO ANY EQUIPMENT CONNECTION WITHIN THE TOLL EQUIPMENT BUILDING.
- 12) PROVIDE MOISTURE DETECTOR - FLOOR MOUNTED.
- 13) DOOR POSITION SWITCH. PRE-INSTALLED AS PART OF THE ACCESS CONTROL SYSTEM. MOUNTED ON THE SECURE SIDE OF THE DOOR.
- 14) PROVIDE TEMPERATURE AND HUMIDITY SENSOR, WALL MOUNTED AT +6 FT. ADJACENT TO THE HVAC THERMOSTAT.
- 15) PROVIDE FUEL TANK MONITOR - THE SCADA SYSTEM MONITORS FUEL TANK LEAK DETECTOR ALARM CONTACTS.
- 16) PROVIDE FUEL TANK LEAK ALARM.
- 17) PROVIDE ONE HIGH LEVEL FLOAT SWITCH AND ONE LOW LEVEL FLOAT SWITCH. HIGH LEVEL ALARM (90%) LOW LEVEL ALARM (30%).
- 18) PROVIDE ANALOG FUEL LEVEL SENSOR, OUTPUT SIGNAL 4-20 mA, +/- 2% ACCURACY, 2" NPT, NEMA 4X ALUMINUM HOUSING AND 12" LEAD LENGTH. THE SCADA SYSTEM MONITORS THE ANALOG FUEL LEVEL SENSOR.
- 19) PROVIDE GENERATOR CONTROLLER - COMMUNICATES WITH SCADA SYSTEM BY MODBUS RTU PROTOCOL TO MONITOR EMERGENCY POWER V, A, W, Hz, pf, ALL GENERATOR ALARMS, LOW BATTERY VOLTS, AND LOSS OF BATTERY CHARGER AC POWER. ALSO GENERATOR START/STOP CONTROL AND RUN RELAY.
- 20) 240 VAC VOLTAGE MONITOR RELAY CONNECTED TO THE LOAD SIDE OF THE FUSED SAFETY SWITCH FOR EACH AIR CONDITIONER. THE SCADA CONTROLLER WILL MONITOR THE POSITION OF THE RELAY CONTACTS. INSTALL VOLTAGE MONITOR ICM CONTROLS, CAT# ICM491. USE INSULATED TAP CONNECTORS EQUAL TO ILSCO CAT# PCT-4-4 TO TAP THE CONDUCTORS.
- 21) SPD WITH N.O. DRY CONTACTS. SEE TSP'S FOR REQUIREMENTS.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	SCADA SYSTEM BLOCK DIAGRAM NOTES	AE-132
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME:	SHEET NO.
							SR 429 WEKIVA PARKWAY SECTION 7A	49	

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



- LEGEND:**
- (J) JUNCTION BOX
 - 1A, 4C, PURPLE, ONE TYPE A CABLE AND FOUR TYPE C CONDUCTORS WITH PURPLE INSULATION.
 - (PB) PULL BOX
 - ~ CABLE NOT INSIDE CONDUIT
 - (#) REFERENCE NOTES

CABLE SCHEDULE	
CALLOUT	CABLE DESCRIPTION
A	BELDEN 88760 - 1 PR #18 AWG SHIELDED
B	CAROL C0957A 9 CONDUCTOR #24 AWG SHIELDED
C	#14 AWG THHN/THWN STRANDED COPPER WITH (1) #14 GND PER CONDUIT
D	CAT-5e 4 PAIR STRANDED, CMR CABLE, WITH RJ45 CONNECTORS
E	#12 AWG THHN/THWN STRANDED COPPER WITH (1) #12 GND PER CONDUIT

1 SCADA SYSTEM BLOCK DIAGRAM
AE-133 SCALE: N.T.S.

REFER TO DWG. AE-132 FOR REFERENCE NOTES.

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: SCADA SYSTEM BLOCK DIAGRAM		DRAWING NO. AE-133
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A		SHEET NO. 50
					SR 429	SEMINOLE	240200-2-52-01			

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

STATE OF FLORIDA
DEPARTMENT OF TRANSPORTATION

CONTRACT PLANS

FINANCIAL PROJECT ID 240200-2-52-01

(FEDERAL FUNDS)

SEMINOLE COUNTY (77320)

STATE ROAD NO. 429 (WEKIVA PARKWAY SECTION 7A)

INDEX OF TOLL FACILITIES-GANTRY PLANS

SHEET NO. DRAWING NO. SHEET DESCRIPTION

1	GG-001	Key Sheet
2	GG-002	Signature Sheet
STRUCTURAL PLANS		
3	GB-001	General Notes (1 OF 2)
3A	GB-001A	General Notes (2 OF 2)
4	GB-002	Plan - Ramp E Gantry
5	GB-003	Elevation - Ramp E Gantry
6	GB-004	Plan - Ramp F Gantry
7	GB-005	Elevation - Ramp F Gantry
8	GB-006	Report of Core Borings - Ramp E Gantry
9	GB-007	Report of Core Borings - Ramp F Gantry
10	GB-008	Drilled Shaft Installation Table and Notes
11	GB-009	Typical Section
12	GB-010	Gantry Details (1 of 2)
13	GB-011	Gantry Details (2 of 2)
14	GB-012	Equipment Support Arm Details (1 of 4)
15	GB-013	Equipment Support Arm Details (2 of 4)
16	GB-014	Equipment Support Arm Details (3 of 4)
17	GB-015	Equipment Support Arm Details (4 of 4)
18	GB-016	Right Upright Details
19	GB-017	Upright Wireway Mounting Details
20	GB-018	Table of Tolling Equipment Structure Variables
20A	GB-019	Gantry Design Soil Parameters

ELECTRICAL PLANS

21	GE-101	Electrical Symbols, Legend and Abbreviations
22	GE-102	Electrical General Notes
23	GE-111	Ramp E - Gantry Electrical Plan
24	GE-112	E6 Wireway Routing Details
25	GE-113	Wireway Installation Details (1 of 3)
26	GE-114	Wireway Installation Details (2 of 3)
27	GE-115	Wireway Installation Details (3 of 3)
28	GE-116	Gantry - Lightning Protection Details
29	GE-201	Electrical Symbol Legend and Abbreviations
30	GE-202	Electrical General Notes
31	GE-211	Ramp F - Gantry Electrical Plan
32	GE-212	E6 Wireway Routing Details
33	GE-213	Wireway Installation Details (1 of 3)
34	GE-214	Wireway Installation Details (2 of 3)
35	GE-215	Wireway Installation Details (3 of 3)
36	GE-216	Gantry - Lightning Protection Details

TOLL FACILITIES - GANTRY PLANS

**TOLL FACILITIES-GANTRY PLANS
ENGINEER OF RECORD:**


SCOTT L. MONTGOMERY, P.E.
PE No.: 42006
AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
Phone (813) 286-1711
CONTRACT NO. C-9855
VENDOR NO. F952661922
CERTIFICATE OF AUTHORIZATION NO. 00008115

FDOT PROJECT MANAGER:


KEVIN MOSS, P.E.

		DRAWING NO.
		GG-001
CONSTRUCTION CONTRACT NO.	FISCAL YEAR	SHEET NO.
T5626	18	1

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:




PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM Technical Services, Inc.,
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 SCOTT L. MONTGOMERY, P.E. NO. 42006

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.


TOLL FACILITIES - GANTRY PLANS

SHEET NO. DRAWING NO. SHEET DESCRIPTION

1	GG-001	Key Sheet
2	GG-002	Signature Sheet
3	GB-001	General Notes (1 OF 2)
3A	GB-001A	General Notes (2 OF 2)
4	GB-002	Plan - Ramp E Gantry
5	GB-003	Elevation - Ramp E Gantry
6	GB-004	Plan - Ramp F Gantry
7	GB-005	Elevation - Ramp F Gantry
10	GB-008	Drilled Shaft Installation Table and Notes
11	GB-009	Typical Section
12	GB-010	Gantry Details (1 of 2)
13	GB-011	Gantry Details (2 of 2)
14	GB-012	Equipment Support Arm Details (1 of 4)
15	GB-013	Equipment Support Arm Details (2 of 4)
16	GB-014	Equipment Support Arm Details (3 of 4)
17	GB-015	Equipment Support Arm Details (4 of 4)
18	GB-016	Right Upright Details
19	GB-017	Upright Wireway Mounting Details
20	GB-018	Table of Tolling Equipment Structure Variables
20A	GB-019	Gantry Design Soil Parameters



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:




PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS, INC.
 919 LAKE BALDWIN LANE
 ORLANDO, FL 32814
 CA NO. 00008115
 DANIEL C. STANFILL, P.E. NO. 42763

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.


TOLL FACILITIES - GANTRY PLANS

SHEET NO. DRAWING NO. SHEET DESCRIPTION

2	GG-002	Signature Sheet
8	GB-006	Report of Core Borings - Ramp E Gantry
9	GB-007	Report of Core Borings - Ramp F Gantry



THIS DOCUMENT HAS BEEN DIGITALLY SIGNED AND SEALED BY:



PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED. THE SIGNATURE MUST BE VERIFIED ON THE ELECTRONIC DOCUMENTS.
 AECOM Technical Services, Inc.,
 7650 W. COURTNEY CAMPBELL CAUSEWAY
 TAMPA, FL 33607-1462
 CA NO. 00008115
 PETER J. PASTORE, P.E. NO. 77103

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.

TOLL FACILITIES - GANTRY PLANS

SHEET NO. DRAWING NO. SHEET DESCRIPTION

2	GG-002	Signature Sheet
21	GE-101	Electrical Symbols, Legend and Abbreviations
22	GE-102	Electrical General Notes
23	GE-111	Ramp E - Gantry Electrical Plan
24	GE-112	E6 Wireway Routing Details
25	GE-113	Wireway Installation Details (1 of 3)
26	GE-114	Wireway Installation Details (2 of 3)
27	GE-115	Wireway Installation Details (3 of 3)
28	GE-116	Gantry - Lightning Protection Details
29	GE-201	Electrical Symbol Legend and Abbreviations
30	GE-202	Electrical General Notes
31	GE-211	Ramp F - Gantry Electrical Plan
32	GE-212	E6 Wireway Routing Details
33	GE-213	Wireway Installation Details (1 of 3)
34	GE-214	Wireway Installation Details (2 of 3)
35	GE-215	Wireway Installation Details (3 of 3)
36	GE-216	Gantry - Lightning Protection Details

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SIGNATURE SHEET (GANTRY PLANS)	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		GG-002
					SR 429	SEMINOLE	240200-2-52-01		2

GENERAL NOTES

CONSTRUCTION SPECIFICATIONS:

- Florida Department of Transportation Standard Specifications for Road and Bridge Construction (July 2017 Edition) and as amended by Contract Documents.

DESIGN SPECIFICATIONS:

- American Association of State Highway and Transportation Officials (AASHTO), Load and Resistance Factor Design (LRFD) Bridge Design Specifications (7th Edition) and subsequent interims.
- American Association of State Highway and Transportation Officials (AASHTO), "LRFD Specifications for Structural Supports for Highway Signs, Luminaries and Traffic Signals" (LRFDLTS-1, First Edition 2015) with interims thru 2017.
- The Aluminum Association Design Manual Specifications and Guidelines for Aluminum Structures (2000 Edition).
- FDOT "Plans Preparation Manual" (January 2017 Edition).
- FDOT Structures Manual dated January 2017 (Reference Introduction, Section I.6).
- AISC Manual of Steel Construction (Fourteenth Edition).
- Florida's Turnpike Enterprise "General Tolling Requirements" (GTR) dated June 2014.

DESIGN METHOD:

- Load Resistance Factored Design (LRFD).

DESIGN LOADINGS:

- Dead Loads:
 - Structural Steel = 490 PCF
 - Aluminum = 175 PCF
 - Concrete = 150 PCF
 - Tolling Equipment = Concentrated load of 55 lbs. at each equipment location.
 - Electrical/Data Conduits/Attachments = 200 PLF distributed to chords.
- Wind Loads:
 - AASHTO "LRFD Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals", Exposure C Category
 - Wind Speed (3-second gust) = 150 mph (700 Interval years)
 - Wind Pressure (Extreme I):
 - Upright = 26 PSF
 - Chords = 39 PSF
 - Mounting Pipes = 52 PSF
 - J-Arm = 62 PSF
 - Web Members = 67 PSF
 - Flat Member = 95 PSF
 - Provisional Sign = 54 PSF applied to 10'x12' Panel in each traffic direction centered over the lanes.

ALUMINUM:

- All aluminum materials shall meet the requirements of the Aluminum Association's Alloy 6061-T6 for tubes and also the following ASTM Specifications:
 - Sheets = 5052
 - Plates = B209
 - Extruded Tube, Bar, Rod and Shapes = B221
 - Structural Shapes = B308.
- Welding Rods shall meet the requirements of Aluminum Association Alloy No. 5556 Filler Wire.
- The proportioning of weld details and the operation of welding shall be in accordance with the Current Edition of the AWS Structural Welding Code D1.2-Aluminum.

REINFORCING STEEL:

- All Reinforcing Steel shall be ASTM A615, Grade 60.
- All dimensions pertaining to location of reinforcing steel are to centerline of bars except where clear dimension is noted to face of concrete.
- Reinforcing Steel detail dimensions are out-to-out of bars.
- Cover on Reinforcing Steel as follows, unless noted otherwise:
 - Substructure 6 in. Drilled Shafts
 - Substructure 3 in. External Formed Surfaces
 - Substructure 4 in. External Surfaces Cast Against Earth
- Concrete cover shown in the plans does not include reinforcement placement and fabrication tolerances unless shown as "minimum cover". See FDOT Specifications for Allowable Reinforcement Placement Tolerances.

DIMENSIONS AND ELEVATIONS:

- All dimensions are measured horizontally and vertically unless noted otherwise.
- All dimensions are measured at mean temperature of 70° F.
- Elevations are in feet, and are based on the North American Vertical Datum (NAVD) of 1988.

UTILITIES:

- For information, refer to the Roadway Utility Plans.
- Field verify utility locations before commencing with construction.
- Ensure that any existing utilities that are not to be relocated are not endangered or disturbed during construction. Ensure all active utilities are properly maintained within the construction limits.

MISCELLANEOUS:

- For electrical details, see Toll Facilities Electrical Drawings.
- For miscellaneous structures that have been completed and scheduled for acceptance; the CEI, Project Manager or the Project Administrator shall contact District Five Structures Maintenance Office at 386-740-3463 two weeks prior to completion of the project to schedule an inspection of structures including Cable Signs, Cantilever Signs, Truss Signs, High Mast Light Poles, ITS, Toll Gantry, DMS and Traffic Signal Mast Arms.

STAINLESS STEEL:

- ASTM A555, Type 316 for sheets. ASTM A240, Type 304L for plates. Type 316 for U-bolts. Structural shapes shall conform to ASTM A276, Type 316L.
- Welding shall comply with the current edition of the AWS Structural Welding Code D1.6-Stainless Steel.

CONCRETE:

- Concrete (unless noted otherwise):

FDOT CLASS	MINIMUM 28-DAY COMPRESSIVE STRENGTH (PSI)	LOCATION
IV (Drilled Shafts)	F'c = 4,000	Drilled Shafts & Upright In-Fill

- Provide 3/4" chamfers on all exposed edges, unless noted otherwise.
- Construction joints will be permitted only at locations indicated on plans. Additional construction joints or alterations to those shown shall require written approval of the engineer.

Tri-Chord Truss Ramp Gantry - Structure No's.

&

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: GENERAL NOTES (1 OF 2)	REF. DWG. NO. GB-001
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	3	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

GENERAL NOTES (CONTINUED)

STRUCTURAL STEEL:

1. Submit shop drawings for all work. Include:
 - a. Field verification of all upright heights.
 - b. Foundation elevations necessary to insure minimum vertical clearances as per traffic plans.
 - c. Anchor bolt orientation with respect to centerline of truss and the direction of traffic.
 - d. The method to be used to provide the required parabolic camber. (See Camber Diagram).
 - e. Equipment support elements.
 - f. Layout of the tolling equipment, field splices, W5x16 members, HSS 4.5" diameter pipe, and any other electrical equipment or structural member that could be in conflict with the toll equipment installation and operations.
2. Shop Fabrication, Assembly, Handling and Shipping:
 - a. Do not begin fabrication before receiving shop drawing approval.
 - b. Welding: Conform to American Welding Society Structural Welding Code (Steel) ANSI/AWS D1. 1 (current edition).
 - c. Shop assemble the entire structure after galvanizing and prior to shipment.
 - d. If necessary, disassemble and secure components for shipment.
 - e. No field welding shall be permitted.
 - f. No shop welded splices of main chords or uprights shall be permitted.
3. Gantry Structure Materials:
 - a. Upright and Chords (Steel Pipe): API -5L-X42 (42 ksi yield) or ASTM A500, Grade B (Min).
 - b. Steel Angles: ASTM A 709, Grade 36.
 - c. Steel Plates: ASTM A 709, Grade 36.
 - d. Steel I-Beams: ASTM A36 or ASTM A709, Grade 36.
 - e. Weld Metal: E70XX.
 - f. Structural Bolts, Nuts and Washers:
 - High Strength Bolts: ASTM A325 Type 1.
 - Nuts: ASTM A563 heavy hex nut, Grade DH, galvanized and lubricated.
 - Washers: ASTM F436 Type 1, one under turned element. Split lock washers are not permitted.
 - g. Anchor Bolts, Nuts and Washers:
 - Bolts: ASTM F1554, Grade 55, Saddles and other components shall be as noted in the plans.
 - Nuts: ASTM A563 Grade A heavy-hex nuts, five per bolt: two above the base plate, one under the base plate and two at the bolt bottom.
 - Plate Washers: ASTM A36 (2 per bolt).
 - h. Materials for J-Arms, U-Bolts, Saddles and other components shall be as noted in the plans.
4. Install all bolts, including anchor bolts, in accordance with the FDOT Specifications.
5. Bolt hole diameters: Equal to the bolt diameter plus 1/16".
6. Anchor bolt hole diameters: Equal to the bolt diameter plus 1/2".
7. Galvanization:
 - The anchor bolts, nuts and washers shall be hot-dip galvanized in accordance with ASTM Specifications F2329.
 - All other steel components shall be hot-dip galvanized in accordance with Section 962-9 of the Specifications.
8. Prior to erection, record the as-built anchor locations and provide to the Engineer.
9. Provide a parabolic camber with the maximum upward deflection as shown on the Camber Diagram.
10. Locate Chord splices a minimum of 3 truss panel lengths apart. Chord splices shall be an Alternate splice. Upright splices are not allowed.
11. Refer to FDOT Standard Index 11320 for additional Span Gantry Structure Details.

LIST OF FREQUENTLY USED ABBREVIATIONS

For additional abbreviations refer to Design Standards Index No. 001.


- | | |
|--------------------------------------|---|
| ASD - Allowable Stress Design | MVC - Minimum Vertical Clearance |
| B - Bottom | NF - Near Face |
| CJ - Construction Joint | OF - Outside Face |
| DJS - Deck Joint Seal | OFM - Owner Furnished Material |
| DVAS - Digital Video Auditing System | OPUS - Optical Profile Unifying System |
| EB - Eastbound | PMVC - Point of Actual Minimum Vertical Clearance |
| EF - Each Face | SBL - Slope Break Line |
| EOL - Edge of Lane | SDG - Structures Design Guidelines |
| ES - Each Side | SH or SHLD - Shoulder |
| EW - End Wall | SS - Stainless Steel |
| FB - Field Bend | T - Top |
| FF - Far Face | UNO - Unless Noted Otherwise |
| FFAS - Front Face of Approach Slab | VCAR - Vehicle Capture and Recognition Equipment |
| FFBW - Front Face of Backwall | VES - Violation Enforcement System |
| FFRW - Front Face of Retaining Wall | VSS - Video Surveillance System |
| GDR - Girder | WB - Westbound |
| IF - Inside Face | WL - Work Line |
| LME - Low Member Elevation | WP - Work Point |
| LVC - Length of Vertical Curve | |
| MHC - Minimum Horizontal Clearance | |

Tri-Chord Truss Ramp Gantry - Structure No's.

&

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: GENERAL NOTES (2 OF 2)	REF. DWG. NO. GB-001A
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	SHEET NO. 3A	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



CURVE RAMPE-1

PI Sta. = 615+43.76
 $\Delta = 14^\circ 12' 13''$ (LT)
 $D = 1^\circ 54' 35''$
 $T = 373.76'$
 $L = 743.70'$
 $R = 3,000.00'$
 $e = 0.039$
 PC Sta. = 611+70.00
 PT Sta. = 619+13.70

**HORIZONTAL ALIGNMENT
 ALONG B CONSTR. RAMP E**

PLAN
 (Wireways not shown for clarity)

NOTES

1. Legend:


- ⊕ = J Arm Number.
- A = Antenna
- O = Opus
- AO = Antenna/Opus
- FV = Front VCAR
- RV = Rear VCAR
- D = DVAS

⊕ Denotes approximate Location of Core Boring. See Drawing GB-006.

Tri-Chord Truss Ramp Gantry - Structure No.

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PLAN RAMP E GANTRY		GB-002
							SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: WEKIVA PARKWAY SECTION 7A		SHEET NO. 4	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




ELEVATION
 (Looking in Direction of Travel)
 (Truss web members and wireways not shown for clarity)

Tri-Chord Truss Ramp Gantry - Structure No.

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ELEVATION RAMP E GANTRY	REF. DWG. NO. GB-003
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	5	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



PLAN
(Wireways not shown for clarity)

NOTES

1. Legend:


- ⊕ = J Arm Number.
- A = Antenna
- O = Opus
- AO = Antenna/Opus
- FV = Front VCAR
- RV = Rear VCAR
- D = DVAS

⊙ Denotes approximate Location of Core Boring. See Drawing GB-007.

Tri-Chord Truss Ramp Gantry - Structure No.

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: PLAN RAMP F GANTRY	REF. DWG. NO. GB-004
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	6	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.





ELEVATION
 (Looking in Direction of Travel)
 (Truss web members and wireways not shown for clarity)

Tri-Chord Truss Ramp Gantry - Structure No.

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ELEVATION RAMP F GANTRY	REF. DWG. NO. GB-005
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	7	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



LEGEND

- GSE GROUND SURFACE ELEVATION (FT. NAVD88)
- N STANDARD PENETRATION RESISTANCE, BLOWS PER FOOT
- HA HAND AUGERED FOR UTILITY CLEARANCE
- 50/4" NUMBER OF BLOWS FOR 4 INCHES OF PENETRATION
- W/H WEIGHT OF HAMMER
- ▽+49.9 ESTIMATED SEASONAL HIGH GROUNDWATER ELEVATION (FT. NAVD88)
- ▽+45.9 ENCOUNTERED GROUNDWATER ELEVATION (FT. NAVD88) ON DATE DRILLED
- ◀100% PERCENT LOSS OF DRILLING FLUID
- ◁100% PERCENT RETURN OF DRILLING FLUID
- BT BORING TERMINATED AT DEPTH INDICATED
- 200= PERCENT PASSING NO. 200 U.S. STANDARD SIEVE
- MC= PERCENT NATURAL MOISTURE CONTENT
- LL= LIQUID LIMIT
- PI= PLASTICITY INDEX



GENERAL NOTES

SUBSURFACE CONDITIONS SHOWN ON THE BORINGS REPRESENT THE CONDITIONS ENCOUNTERED AT THE BORING LOCATIONS. ACTUAL CONDITIONS BETWEEN THE BORINGS MAY VARY FROM THOSE SHOWN. UNIFIED SOIL CLASSIFICATIONS SHOWN ON THE BORINGS ARE BASED ON VISUAL EXAMINATION AND THE LABORATORY TESTING SHOWN.

STANDARD PENETRATION TEST BORINGS WERE PERFORMED IN ACCORDANCE WITH ASTM D-1586. STANDARD PENETRATION RESISTANCES ARE SHOWN ON THE BORINGS AT THE TEST DEPTHS IN IN BLOWS PER FOOT UNLESS OTHERWISE NOTED.

THE BORING LOCATIONS WERE ESTABLISHED IN THE FIELD USING SUB-METER ACCURACY GPS UNIT (TRIMBLE GEO 7X). GROUND SURFACE ELEVATIONS ESTIMATED FROM PROJECT CROSS SECTIONS. BORING LOCATIONS REFERENCE THE RAMP F BASELINE.

BASED ON REVIEW OF THE U.S. GEOLOGICAL SURVEY MAP ENTITLED "POTENTIOMETRIC SURFACE OF THE UPPER FLORIDAN AQUIFER IN ST. JOHNS RIVER WATER MANAGEMENT DISTRICT AND VICINITY, FLORIDA, SEPTEMBER 2008" FOR THE PROJECT AREA, THE MAXIMUM ELEVATION OF THE ARTESIAN HEAD IS ESTIMATED TO BE +26 FT. NAVD88. THE CONTRACTOR SHALL BE PREPARED TO HANDLE ARTESIAN HEAD LEVELS UP TO +26 FT. NAVD88.

SPLIT SPOON SAMPLER:
 INSIDE DIAMETER: 1.375 IN.
 OUTSIDE DIAMETER: 2.0 IN.
 AVERAGE HAMMER DROP: 30 IN.
 HAMMER WEIGHT: 140 LBS.
 HAMMER TYPE: AUTOMATIC



CORRELATION OF STANDARD PENETRATION RESISTANCE WITH RELATIVE DENSITY AND CONSISTENCY OF SOIL

GRANULAR SOILS	AUTOMATIC HAMMER N VALUE (blows per foot)		RELATIVE DENSITY
	SANDS	0-3	3-8
NON-GRANULAR SOILS	AUTOMATIC HAMMER N VALUE (blows per foot)		CONSISTENCY
	SILTS, CLAYS, MUCK, PEAT	0-1 1-3 3-6 6-12 12-24 OVER 24	VERY SOFT SOFT FIRM STIFF VERY STIFF HARD

SECTION: 25
 TOWNSHIP: 19 SOUTH
 RANGE: 29 EAST

REVISIONS						GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS, INC. 919 Lake Baldwin Lane Orlando, FL 32814 T 407-898-1818 F 407-898-1837 Certificate of Authorization No. 5882 DANIEL C. STANFILL PE NO. 42763	DRAWN BY: SKR CHECKED BY: CGB 71571 DESIGNED BY: CGB 71571 CHECKED BY: DCS 42763	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: REPORT OF SPT BORINGS RAMP F GANTRY	REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		PROJECT NAME:
						SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY (SR 429) SECTION 7A	SHEET NO. 8		

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



LEGEND

- GSE GROUND SURFACE ELEVATION (FT. NAVD88)
- N STANDARD PENETRATION RESISTANCE, BLOWS PER FOOT
- HA HAND AUGERED FOR UTILITY CLEARANCE
- ▽ ESTIMATED SEASONAL HIGH GROUNDWATER ELEVATION (FT. NAVD88)
- ▽ ENCOUNTERED GROUNDWATER ELEVATION (FT. NAVD88) ON DATE DRILLED
- BT BORING TERMINATED AT DEPTH INDICATED
- 200= PERCENT PASSING NO. 200 U.S. STANDARD SIEVE
- MC= PERCENT NATURAL MOISTURE CONTENT
- LL= LIQUID LIMIT
- PI= PLASTICITY INDEX



GENERAL NOTES

SUBSURFACE CONDITIONS SHOWN ON THE BORINGS REPRESENT THE CONDITIONS ENCOUNTERED AT THE BORING LOCATIONS. ACTUAL CONDITIONS BETWEEN THE BORINGS MAY VARY FROM THOSE SHOWN. UNIFIED SOIL CLASSIFICATIONS SHOWN ON THE BORINGS ARE BASED ON VISUAL EXAMINATION AND THE LABORATORY TESTING SHOWN.

STANDARD PENETRATION TEST BORINGS WERE PERFORMED IN ACCORDANCE WITH ASTM D-1586. STANDARD PENETRATION RESISTANCES ARE SHOWN ON THE BORINGS AT THE TEST DEPTHS IN IN BLOWS PER FOOT UNLESS OTHERWISE NOTED.

THE BORING LOCATIONS WERE ESTABLISHED IN THE FIELD USING SUB-METER ACCURACY GPS UNIT (TRIMBLE GEO 7X). GROUND SURFACE ELEVATIONS ESTIMATED FROM PROJECT CROSS SECTIONS. BORING LOCATIONS REFERENCE THE RAMP E BASELINE.

BASED ON REVIEW OF THE U.S. GEOLOGICAL SURVEY MAP ENTITLED "POTENTIOMETRIC SURFACE OF THE UPPER FLORIDAN AQUIFER IN ST. JOHNS RIVER WATER MANAGEMENT DISTRICT AND VICINITY, FLORIDA, SEPTEMBER 2008" FOR THE PROJECT AREA, THE MAXIMUM ELEVATION OF THE ARTESIAN HEAD IS ESTIMATED TO BE +26 FT. NAVD88. THE CONTRACTOR SHALL BE PREPARED TO HANDLE ARTESIAN HEAD LEVELS UP TO +26 FT. NAVD88.

SPLIT SPOON SAMPLER:
 INSIDE DIAMETER: 1.375 IN.
 OUTSIDE DIAMETER: 2.0 IN.
 AVERAGE HAMMER DROP: 30 IN.
 HAMMER WEIGHT: 140 LBS.
 HAMMER TYPE: AUTOMATIC

CORRELATION OF STANDARD PENETRATION RESISTANCE WITH RELATIVE DENSITY AND CONSISTENCY OF SOIL

AUTOMATIC HAMMER		
GRANULAR SOILS	N VALUE (blows per foot)	RELATIVE DENSITY
SANDS	0-3	VERY LOOSE
	3-8	LOOSE
	8-24	MEDIUM DENSE
	24-40	DENSE
	OVER 40	VERY DENSE
AUTOMATIC HAMMER		
NON-GRANULAR SOILS	N VALUE (blows per foot)	CONSISTENCY
SILTS, CLAYS, MUCK, PEAT	0-1	VERY SOFT
	1-3	SOFT
	3-6	FIRM
	6-12	STIFF
	12-24	VERY STIFF
	OVER 24	HARD

SECTION: 25
 TOWNSHIP: 19 SOUTH
 RANGE: 29 EAST

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

GEOTECHNICAL AND ENVIRONMENTAL CONSULTANTS, INC.
 919 Lake Baldwin Lane
 Orlando, FL 32814
 T 407-898-1818 F 407-898-1837
 Certificate of Authorization No. 5882
DANIEL C. STANFILL PE NO. 42763

DRAWN BY: SKR
 CHECKED BY: CGB 71571
 DESIGNED BY: CGB 71571
 CHECKED BY: DCS 42763

STATE OF FLORIDA
 DEPARTMENT OF TRANSPORTATION

ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE: **REPORT OF SPT BORINGS RAMP E GANTRY**

PROJECT NAME: **WEKIVA PARKWAY (SR 429) SECTION 7A**


REF. DWG. NO.: GB-007

SHEET NO.: 9


DRILLED SHAFT DATA TABLE				
LOCATION		UPRIGHT	TOP OF SHAFT ELEVATION	MINIMUM TIP ELEVATION
STRUCTURE NUMBER	SITE		FT.	FT.
	Ramp E Gantry	Left Upright	73.000	34.000
		Right Upright	69.000	30.000
	Ramp F Gantry	Left Upright	62.500	23.500
		Right Upright	62.500	23.500

NOTES

1. Drilled shafts shall be installed in accordance with Section 455 of the Specifications.
2. For Additional Notes, see Drawing GB-001.
3. The drilled shafts shall be installed to meet the criteria set forth in the Drilled Shaft Data Table.
4. The minimum tip elevations shown represent the highest tip elevation necessary to satisfy lateral stability loading requirements. Any revisions made to the tip elevation shall be submitted to the Engineer of Record, and concurred with by the Turnpike.
5. For Anchor Bolt size and pattern, see Drawing GB-018.
6. If vertical shaft reinforcement is required to be spliced, reinforcement shall be spliced by mechanical couplers capable of developing 125% of yield strength of the bars being spliced. If couplers are required, a 6" minimum cover shall be maintained within the length of the coupler. Couplers shall be staggered 2'-0" between vertical bars. Proposed couplers shall be submitted for approval by the Engineer. No splices will be allowed in the top 20 feet of the shafts.
7. All gantry drilled shafts shall have Cross-Hole Sonic Logging (CSL) testing performed. The CSL tubes shall be installed and testing shall be performed in accordance with the Specifications.
8. The Contractor shall verify locations of all utilities and notify all involved Utility Companies 2 full business days prior to excavation, shaft drilling or construction and shall be responsible for making its own determination to avoid damage. Any required relocation of existing utilities shall be done by others. The Contractor shall ensure that active utilities are properly maintained during construction.
9. Before the concrete shaft is poured, coordinate with the electrical contractor who is responsible for installing the lighting protection system. For lighting protection conductors and grounding details, see "Electrical Plans".
10. Contractor shall install drilled shafts after grade has been brought to within one foot of final grade.
11. For horizontal alignment along \mathcal{R} Ramp E, see Drawing GB-002.
12. For location of Core Borings, see Drawings GB-006 & GB-007.
13. Layers of dense sand may be encountered at this site. Such materials may make shaft excavation and/or temporary casing installation difficult. The Contractor shall expect to encounter these types of materials at all shaft locations and shall use specialized equipment and/or procedures as necessary to facilitate shaft excavation and/or temporary casing installation. When temporary casing is used, the casing tip shall be reinforced and the casing thickness shall be adequate to prevent casing damage/deformation during installation through hard layers.
14. The cost of the drilled shaft and excavation shall be included in Pay Item No. 735-74-1 and 735-74-2.



FOUNDATION LAYOUT - RAMP E





FOUNDATION LAYOUT - RAMP F

Tri-Chord Truss Ramp Gantry - Structure No's. &

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: DRILLED SHAFT INSTALLATION TABLE AND NOTES		REF. DWG. NO. GB-008
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME: WEKIVA PARKWAY SECTION 7A		SHEET NO. 10
							SR 429	SEMINOLE	240200-2-52-01				

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



- NOTES**
1. For Detail "A", See Drawing GB-010.
 2. Length of each HSS4.500 shall be equal to the W5x16 support member spacing plus three inches. See Drawings GB-003 and GB-005.

TYPICAL SECTION

Tri-Chord Truss Ramp Gantry - Structure No's. &


REVISIONS						DRAWN BY: JLS 12-14	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: TYPICAL SECTION	REF. DWG. NO. GB-009
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
						CHECKED BY: HSW 3-17	SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	11
						DESIGNED BY: HSW 3-17					
						CHECKED BY: NJG 3-17					

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
C.A. No. 8115
Scott L. Montgomery, P.E. No. 42006

7/26/2017 10:03:07 AM

s:\projects\brgstruct\cadd\projects\proj\dotv8\24020025201\struct\AECOM\Gantry\B1TypicalSection01.dgn MODEL= Sheet 1

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



DETAIL "A"


NOTES

1. For View A-A and Sections B-B, C-C & D-D, See Drawing GB-011.
2. Fabricate angle using bent plate or larger angle with legs clipped to plan dimensions.


Tri-Chord Truss Ramp Gantry - Structure No's. &

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID	GANTRY DETAILS (1 OF 2)		GB-010
								SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A		SHEET NO.
											12		


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




VIEW A-A



SECTION E-E
(J-Arm Mounting Bracket Assembly)




SECTION C-C




SECTION B-B


(Wireways not shown for clarity)



SECTION D-D



DETAIL 1



TRI-CHORD PIPE TO W5x16 CONNECTION DETAIL

Tri-Chord Truss Ramp Gantry - Structure No's. &


REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
C.A. No. 8115
Scott L. Montgomery, P.E. No. 42006


DRAWN BY: JLS 12-14	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
CHECKED BY: HSW 3-17	ROAD NO.	COUNTY	FINANCIAL PROJECT ID
DESIGNED BY: HSW 3-17	SR 429	SEMINOLE	240200-2-52-01
CHECKED BY: NJG 3-17			

SHEET TITLE: GANTRY DETAILS (2 OF 2)	REF. DWG. NO. GB-011
PROJECT NAME: WEKIVA PARKWAY SECTION 7A	SHEET NO. 13


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.



TOLL EQUIPMENT J-ARM



VIEW A-A





CONNECTION PLATE DETAIL

Note: For notes, see Drawing GB-015.

Tri-Chord Truss Ramp Gantry - Structure No's. &



REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: EQUIPMENT SUPPORT ARM DETAILS (1 OF 4)	REF. DWG. NO. GB-012
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	14	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.





HSS4.500 PIPE TO J-ARM PLATE SADDLE DETAIL
(2 Per J-Arm)

- NOTES:
 1. Break all edges.
 2. Clean and degrease part.
 3. Saddle to be galvanized steel.




HSS4.500 PIPE TO W5x16 SADDLE DETAIL
(2 Per Mounting Pipe)

- NOTES:
 1. Break all edges.
 2. Clean and degrease part.
 3. Saddle to be galvanized steel.



J-ARM PIPE TO J-ARM PLATE SADDLE DETAIL
(2 Per J-Arm)

- NOTES:
 1. Break all edges.
 2. Clean and degrease part.
 3. Saddle to be Aluminum-6061-T6.




SADDLE ISOMETRIC VIEW

Note: All dimensions are in inches, unless noted otherwise.

Tri-Chord Truss Ramp Gantry - Structure No's. &

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: EQUIPMENT SUPPORT ARM DETAILS (2 OF 4)	REF. DWG. NO. GB-013
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	15	

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




PLAN VIEW

END VIEW

SIDE VIEW

TRI-CHORD PIPE TO W5x16 U-BOLT DETAIL

NOTE: U-Bolts to be galvanized ASTM A307 GRADE A steel.
(2 Per W5x16 Connection)




PLAN VIEW

END VIEW

SIDE VIEW

HSS4.500 PIPE TO J-ARM PLATE U-BOLT DETAIL

NOTE: U-Bolts to be 316 Stainless Steel and threads to be coated with a suitable anti-gall compound.
(2 Per J-Arm)




PLAN VIEW

END VIEW

SIDE VIEW

HSS4.500 PIPE TO W5x16 U-BOLT DETAIL

NOTE: U-Bolts to be galvanized steel.
(2 Per Mounting Pipe)



PLAN VIEW

END VIEW

SIDE VIEW

J-ARM PLATE U-BOLT DETAIL

NOTE: U-Bolts to be 316 Stainless Steel and threads to be coated with a suitable anti-gall compound.
(2 Per J-Arm)

Note: All dimensions are in inches, unless noted otherwise.

Tri-Chord Truss Ramp Gantry - Structure No's.

&

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION


AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
C.A. No. 8115
Scott L. Montgomery, P.E. No. 42006

DRAWN BY: JLS 12-14	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
CHECKED BY: HSW 3-17	ROAD NO.	COUNTY	FINANCIAL PROJECT ID
DESIGNED BY: HSW 3-17	SR 429	SEMINOLE	240200-2-52-01
CHECKED BY: NJG 3-17			

SHEET TITLE: EQUIPMENT SUPPORT ARM DETAILS (3 OF 4)	REF. DWG. NO. GB-014
PROJECT NAME: WEKIVA PARKWAY SECTION 7A	SHEET NO. 16

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

J-ARM NOTES




END CAP FOR PIPE 2½", SCHEDULE 40

NOTE: End cap to be Aluminum-6061-T6. Chamfer all edges ¼" x ¼".
(1 Per J-Arm)

- The J-arm design shall accommodate all of the requirements set forth in these Tri-Chord Truss Ramp Gantry Plans.
- All J-arm U-Bolts shall be furnished with self-locking nuts and a saddle. U-Bolt nuts shall be torqued to a snug-tight condition.
- For Toll Equipment mounting locations, see Drawings GB-002 & GB-004.
- All Toll Equipment J-arms and required hardware shall be Provided by the Contractor. All J-arms shall be identical with exception of the tolerances dictated herein.
- The proportioning of weld details and the operation of welding shall be in accordance with the American Welding Society Structural Welding Code - Aluminum (AWS D1.2) (Current Edition). Welding Rods shall meet the requirements of Aluminum Association Alloy No. 5556 Filler Wire.
- Post weld cleaning, remove splash and soot.
- The J-arm material shall meet ASTM B429, Alloy 6061-T6 and meet Specification Section 965-2 Certification and Mill Analysis. The J-arms shall have an outside diameter of 2.875 inches with an ovality tolerance of +/- 0.015 inches along the straight sections of the arm (ANSI H35.2) and +/- 0.057 inches along the curved arm section (Pipe Fabrication Institute Standard ES-24). The final diameters in the major and minor axes (x and y planes) shall be 2.875 inches ± 0.029 inches in the straight section and ± 0.057 inches in the curved section.
- J-arm roundness must be checked at the fabrication facility before shipping to the jobsite in accordance with the Producer's Quality Control Plan. The Turnpike may check for J-arm roundness at any time. Provide material testing reports (MTRs) that show the material meets ASTM B429, Alloy 6061-T6. There must be traceability between the MTRs and the material actually used for the J-arms. The Turnpike may test the J-arms for Yield and Tensile strength at any time per FDOT Specification 6-1.2.4.
- The J-arm fabricator shall be an approved fabricator of aluminum products per FDOT Specification Sections 105-3.
- The J-Arm fabricator shall provide a letter to the Turnpike stating that the fabricator is currently equipped/capable of fabricating the J-Arms based on the criteria defined in these plans. This letter shall be provided at least one month in advance of the provisions below for the sample arm. The Turnpike will not accept J-Arms from fabricators that cannot comply with the design and tolerance criteria. The Turnpike reserves the right to visit and inspect the fabrication facility, methods, and materials at any time.
- Each J-arm fabricator shall provide a sample arm to the Turnpike for review and approval prior to fabricating any J-arms for the project. The entire fabrication process of the sample J-arm shall be observed by the Turnpike and/or its representatives. If the sample J-arm does not meet the contract requirements, the Turnpike will not accept J-arms from the vendor fabricator supplying the sample until the design and tolerance criteria are met for a sample arm. Acceptance of the sample arm by the Turnpike does not constitute acceptance of all J-arms provided subsequently for the project. The Turnpike may measure all J-arms for conformance to design and tolerance criteria and reject any J-arms that do not meet the design and tolerance criteria. Sample J-arm(s) that meet criteria may be used as production J-arms.
- The above stated requirements for a letter and a sample J-arm are applicable for each J-arm fabricator.
- Shop drawings from one fabricator shall not be used by another fabricator.
- The point of attachment of the J-arms to the mounting pipes shall be in the upper straight section of the J-arm and shall meet the criteria defined in these plans.
- Five spare J-arms and all associated required J-arm attachment hardware (U-bolts, pipe saddles, mounting plates, self-locking nuts, etc.) per gantry shall be provided to the Turnpike and delivered to the Turnpike's Central Repair Depot at Turnpike Milepost 99. The contractor shall provide two weeks advance notice prior to delivering the spare items.
- Six spare horizontal support pipes and complete set of attachment hardware (U-bolts, pipe saddles, mounting plates, self-locking nuts, etc.) per gantry shall be provided to the Turnpike and delivered to the Turnpike's Central Repair Depot at Turnpike Milepost 99. The contractor shall provide two weeks advance notice prior to delivering the spare items.
- For specifics concerning J-arms, see Drawings GB-012 thru GB-015.

Note: All dimensions are in inches, unless noted otherwise.



LOCKING NUTS


NOTE: Locking nuts to be 316 Stainless Steel.
(2 Per U-Bolt)

Tri-Chord Truss Ramp Gantry - Structure No's.


&

REVISIONS						DRAWN BY: JLS 12-14	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: EQUIPMENT SUPPORT ARM DETAILS (4 OF 4)	REF. DWG. NO. GB-015
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: WEKIVA PARKWAY SECTION 7A	SHEET NO. 17	
AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006						kathy.compton 7/26/2017 10:03:11 AM s:\projects\brgstruct\cadd\projects\proj\dotv81\24020025201\struct\AECOM\Gantry\B1MiscDetSuptArm04.dgn			MODEL= Sheet 1		

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




HANDHOLE DETAIL



**SECTION A-A
(Thru Handrail)**

NOTES

1. Concrete in-fill shall extend to outside edge of base plate, down to top of pedestal. Top of in-fill shall slope downward to drain pipe.
2. Handhole Frame shall be ASTM A709, Grade 36 min.
3. Handhole Cover shall be ASTM A1011, Grade 50 min.
4. Stainless Steel screws shall be AISI Type 316.
5. Terminate 1" Ø PVC Pipe with 90° elbow that extends beyond the edge of the base plate, positioned between anchor bolts and directed toward the gutter line.




ELEVATION RIGHT UPRIGHT


Tri-Chord Truss Ramp Gantry - Structure No's. &

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 10-15 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: RIGHT UPRIGHT DETAILS	REF. DWG. NO. GB-016
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
								SR 429	SEMINOLE	240200-2-52-01		


THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




ELEVATION - LEFT UPRIGHT



SECTION A-A



SECTION B-B



ANGLE DETAIL

TABLE OF VARIABLES			
STRUCTURE LOCATION		UPRIGHT	TOP OF MEMBER ELEVATION 'A'
STRUCTURE NUMBER	SITE		
	Ramp E Gantry	Left Upright	91.083
	Ramp F Gantry	Left Upright	81.417

REVISIONS					
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 C.A. No. 8115
 Scott L. Montgomery, P.E. No. 42006

DRAWN BY: JLS 12-14
 CHECKED BY: HSW 3-17
 DESIGNED BY: HSW 3-17
 CHECKED BY: NJG 3-17

STATE OF FLORIDA
 DEPARTMENT OF TRANSPORTATION

ROAD NO. SR 429 COUNTY SEMINOLE FINANCIAL PROJECT ID 240200-2-52-01

SHEET TITLE: UPRIGHT WIREWAY MOUNTING DETAILS

PROJECT NAME: WEKIVA PARKWAY SECTION 7A

REF. DWG. NO. GB-017

SHEET NO. 19

Tri-Chord Truss Ramp Gantry - Structure No's. &

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

SPAN TOLLING EQUIPMENT STRUCTURE DATA TABLE

Table Date 01-01-11

STRUCTURE LOCATION	STATION	DIMENSIONS					PNLS	MEMBER SIZES					SPLICE		
		A	B	C	D	E		F (CHORD)	G (WEB)	H (LEFT UPRIGHT)	J (RIGHT UPRIGHT)	K (CAMBER)	SA	SB	SC
		ft	ft	ft	#	in		O. D. x Wall Thk. (in)	Angle (in)	O. D. x Wall Thk. (in)	O. D. x Wall Thk. (in)	in	Angle (in)	#	in
RAMP E	615+80.00	48.000	20.510	24.510	8	54	5.563 x 0.258	4 x 4 x 1/2	24.000 x 0.562	24.000 x 0.562	1/2	N/A	N/A	N/A	
RAMP F	712+00.00	48.000	21.344	21.344	8	54	5.563 x 0.258	4 x 4 x 1/2	24.000 x 0.562	24.000 x 0.562	1/2	N/A	N/A	N/A	

SPAN TOLLING EQUIPMENT STRUCTURE DATA TABLE (CONT.)

Table Date 01-01-11

STRUCTURE LOCATION	ALTERNATE SPLICE						GUSSET PLATES																		
	PA	PB	PC	PD	PE	PF	GA	GB	GC	GD	GE	GF	GG	GH	GJ	GK	GL								
	in	in	in	in	in	#	in	in	ft	in	ft	in	ft	in	ft	in	ft	in	ft	in	ft	in	in		
RAMP E	1.25	2	1/4	1/4	1	8	1/2	7/8	1	4 1/4	0	7 3/4	1	3 3/4	0	6 1/2	2	2 1/4	1	1 3/4	0	9 1/2	1	3 1/4	1/8
RAMP F	1.25	2	1/4	1/4	1	8	1/2	7/8	1	4 1/4	0	7 3/4	1	3 3/4	0	6 1/2	2	2 1/4	1	1 3/4	0	9 1/2	1	3 1/4	1/8

SPAN TOLLING EQUIPMENT STRUCTURE DATA TABLE (CONT.)

Table Date 01-01-11

STRUCTURE LOCATION	LEFT UPRIGHT CONNECTION								RIGHT UPRIGHT CONNECTION							
	LA	LB	LC	LD	LE	LF	LG	LH	RA	RB	RC	RD	RE	RF	RG	RH
	in	#	in	in	in	in	in	in	in	#	in	in	in	in	in	in
RAMP E	7/8	8	1/2	1/2	3/16	3/16	3/16	3/16	7/8	8	1/2	1/2	3/16	3/16	3/16	3/16
RAMP F	7/8	8	1/2	1/2	3/16	3/16	3/16	3/16	7/8	8	1/2	1/2	3/16	3/16	3/16	3/16

NOTES:

1. Work these Data Tables with Index 11320.
2. Design Wind Speed = 150 mph
3. Upright wall thickness given is a minimum dimension.
4. Erection is the Contractor's responsibility.
To facilitate erection, the Contractor should consider using two vertical lift points, each located near a panel point approximately 20 to 25% of the truss length from each end.
5. Coordinate Location of Chord splices with Toll Equipment and Supports.

FOUNDATION NOTES:

1. For soil parameter assumptions and design values, see Drawing GB-019.

SPAN TOLLING EQUIPMENT STRUCTURE DATA TABLE (CONT.)

Table Date 01-01-11

STRUCTURE LOCATION	LEFT BASE CONNECTION										RIGHT BASE CONNECTION									
	BA	BB	BC	BD	BE	BF	BG	BH	BJ		CA	CB	CC	CD	CE	CF	CG	CH	CJ	
	in	#	in	in	ft	in	in	in	in	in	in	#	in	ft	in	in	in	in	in	
RAMP E	1 3/4	12	2	1/2	1	10	5/16	5/16	5/16	5/16	1 3/4	12	2	1/2	1	10	5/16	5/16	5/16	5/16
RAMP F	1 3/4	12	2	1/2	1	10	5/16	5/16	5/16	5/16	1 3/4	12	2	1/2	1	10	5/16	5/16	5/16	5/16

SPAN TOLLING EQUIPMENT STRUCTURE DATA TABLE (CONT.)

Table Date 07-01-14

STRUCTURE LOCATION	LEFT DRILLED SHAFT								RIGHT DRILLED SHAFT									
	DA		DB		DC		DD	DE	DF	FA		FB		FC		FD	FE	FF
	ft	in	ft	in	# / size	#	in	in	ft	in	ft	in	# / size	#	in	in	in	
RAMP E	34	0	4	6	15 / #11	31	12	48	34	0	4	6	15 / #11	31	12	48		
RAMP F	34	0	4	6	15 / #11	31	12	48	34	0	4	6	15 / #11	31	12	48		

Tri-Chord Truss Ramp Gantry - Structure No's.

&

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: CER 12-14 CHECKED BY: HSW 3-17 DESIGNED BY: HSW 3-17 CHECKED BY: NJG 3-17	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:		REF. DWG. NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID	TABLE OF TOLLING EQUIPMENT STRUCTURE VARIABLES		GB-018
								SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME:		SHEET NO.
									WEKIVA PARKWAY SECTION 7A		20		

RAMP E (Sta. 615+80.00)			
Layer No.	FILL	1	2
Soil Type	Cohesionless	Cohesionless	Cohesionless
Layer Top Elevation (ft)	---	+65	+47
Layer Bottom Elevation (ft)	---	+47	+32
Layer Thickness (ft)	---	18	15
Average N-Value, N_{avg} (bpf)	20	12	37
Corrected N-Value, N_{60} (bpf)	20	9	33
Lateral Properties			
Recommended Lateral Soil Model	Sand (Reese)	Sand (Reese)	Sand (Reese)
Total Unit Weight, γ (pcf)	115	102	122
Angle of Internal Friction, Φ (degrees)	32	29	33
Subgrade Modulus, K (pci)	80	30	90
Axial/Torsional Properties			
Recommended Axial Soil Model	Drilled Shaft Sand	Drilled Shaft Sand	Drilled Shaft Sand
Recommended Torsional Soil Model	Hyperbolic	Hyperbolic	Hyperbolic
Shear Modulus, G (ksi)	1.07	0.52	1.70
Poisson's Ratio, ν	0.30	0.20	0.35
Angle of Internal Friction, Φ (degrees)	32	29	33
Youngs Modulus, E (psf)	400,000	180,000	660,000
Concrete Ultimate Unit Skin Friction, T_r (psf)	760	342	1254
Tip Model			
Recommended Tip Soil Model	Drilled Shaft Sand	Drilled Shaft Sand	Drilled Shaft Sand
Shear Modulus, G (ksi)	1.07	0.52	1.70
Poisson's Ratio, ν	0.30	0.20	0.35
Uncorrected N-value (bpf)	20	12	37

RAMP F (Sta. 712+00.00)			
Layer No.	FILL	1	2
Soil Type	Cohesionless	Cohesionless	Cohesionless
Layer Top Elevation (ft)	---	+57	+30
Layer Bottom Elevation (ft)	---	+30	+4
Layer Thickness (ft)	---	27	26
Average N-Value, N_{avg} (bpf)	20	14	2
Corrected N-Value, N_{60} (bpf)	20	12	2
Lateral Properties			
Recommended Lateral Soil Model	Sand (Reese)	Sand (Reese)	Sand (Reese)
Total Unit Weight, γ (pcf)	115	107	92
Angle of Internal Friction, Φ (degrees)	32	30	26
Subgrade Modulus, K (pci)	80	60	15
Axial/Torsional Properties			
Recommended Axial Soil Model	Drilled Shaft Sand	Drilled Shaft Sand	Drilled Shaft Sand
Recommended Torsional Soil Model	Hyperbolic	Hyperbolic	Hyperbolic
Shear Modulus, G (ksi)	1.07	0.67	0.13
Poisson's Ratio, ν	0.30	0.25	0.10
Angle of Internal Friction, Φ (degrees)	32	30	26
Youngs Modulus, E (psf)	400,000	240,000	40,000
Concrete Ultimate Unit Skin Friction, T_r (psf)	760	456	76
Tip Model			
Recommended Tip Soil Model	Drilled Shaft Sand	Drilled Shaft Sand	Drilled Shaft Sand
Shear Modulus, G (ksi)	1.07	0.67	0.13
Poisson's Ratio, ν	0.30	0.25	0.10
Uncorrected N-value (bpf)	20	14	2

FOUNDATION NOTES:

- Foundation design based on soil borings performed by Geotechnical and Environmental Consultants, Inc. See Report of Core Borings, Drawings GB-006 & GB-007.



Tri-Chord Truss Ramp Gantry - Structure No's. &

REVISIONS						AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 C.A. No. 8115 Scott L. Montgomery, P.E. No. 42006	DRAWN BY: JLS 10-15 CHECKED BY: HSW 3-17 DESIGNED BY: CGB 12-14 CHECKED BY: DCS 12-14	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: GANTRY DESIGN SOIL PARAMETERS	REF. DWG. NO. GB-019
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION			ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
							SR 429	SEMINOLE	240200-2-52-01	WEKIVA PARKWAY SECTION 7A	20A	

ELECTRICAL SYMBOL LEGEND:

SYMBOL	DESCRIPTION
	125V, 20A NEMA L5-20R, DUPLEX RECEPTACLE. 'WP' INDICATES WEATHERPROOF WITH LOCKABLE METAL WHILE-IN-USE COVER. 'GFI' INDICATES GROUND FAULT INTERRUPTER.
	PAN TILT ZOOM CAMERA.
	WIREWAY, TYPE AND LENGTH AS INDICATED ON PLANS.
	FLEXIBLE WIREWAY FITTINGS.
	90° ELBOW FOR HORIZONTAL AND VERTICAL WIREWAY CONNECTION.
	45° ELBOW.
	90° ELBOW.
	GROUNDING ROD UON.
	DEVICE OR EQUIPMENT AS NOTED.
	REFERENCE NOTES.
	E6 READER.

GENERAL SYMBOL LEGEND:



ABBREVIATIONS:

A	AMPS
AASHTO	AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS
AC	AIR CONDITIONING [UNIT]
AFF	ABOVE FINISH FLOOR
AFG	ABOVE FINISH GRADE
AL, ALUM.	ALUMINUM
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS
ATS	AUTOMATIC TRANSFER SWITCH
AVI	AUTOMATIC VEHICLE IDENTIFICATION
AWG	AMERICAN WIRE GAUGE
BCU	BATTERY CHARGER UNIT
BLDG.	BUILDING
BPS	BYPASS SWITCH
C	CONDUIT
CCTV	CLOSED CIRCUIT TELEVISION
CKT.	CIRCUIT
COMP	COMPUTER
CU	COPPER
COMM.	COMMUNICATION
DEP	DEPARTMENT OF ENVIRONMENTAL PROTECTION
DIA.	DIAMETER
DN	DOWN
DVAS	DIGITAL VIDEO AUDITING SYSTEM
DWG.	DRAWING
E6	ENCOMPASS 6 MULTIPROTOCOL READER
EC	ELECTRICAL CONTRACTOR
ENG.	ENGINE
ETC	ELECTRONIC TOLL COLLECTION
ETC.	ET CETERA
EQUIP.	EQUIPMENT
EPA	ENVIRONMENTAL PROTECTION AGENCY
EPO	EMERGENCY POWER OFF
EXT.	EXTERIOR
FOC	FIBER OPTIC CABLE
FT	FOOT; FEET
FTE	FLORIDA'S TURNPIKE ENTERPRISE
FTL	FEED THROUGH LUGS
FTM	FUEL TANK MONITOR
FUT	FUTURE
GA	GAUGE
GAL.	GALLON
GEC	GROUNDING ELECTRODE CONDUCTOR
GFI	GROUND FAULT INTERRUPTER
GND	GROUND
HID	HIGH INTENSITY DISCHARGE
HP	HORSEPOWER
HZ	HORIZONTAL, HERTZ
I.C.	INTERRUPTING CAPACITY
I.D.	IDENTIFICATION
IN.	INCHES
JB	JUNCTION BOX
KA	KILOAMPERES
KVA	KILOVOLT AMPERES
KW	KILOWATT
LED	LIGHT EMITTING DIODE
LFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT
LN CTR	LANE CONTROLLER
LOC.	LOCATION
LLC	LEAD LAG CONTROLLER
LP	LIGHTNING PROTECTION
LTG	LIGHTING
MAX.	MAXIMUM
MCB	MAIN CIRCUIT BREAKER
MTS	MANUAL TRANSFER SWITCH
MIN.	MINIMUM
ML	MAINLINE
M.L.O.	MAIN LUGS ONLY
MOT	MAINTENANCE OF TRAFFIC
MTD	MOUNTED
N	NEUTRAL
NB	NORTHBOUND
N.C.	NORMALLY CLOSED
NEC	NATIONAL ELECTRICAL CODE
NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
NIC	NOT IN CONTRACT
NO.	NUMBER
N.O.	NORMALLY OPEN

ABBREVIATIONS CONT:


N.T.S.	NOT TO SCALE
N3R	NEMA 3R
OC	ON CENTER
OPUS	OPTICAL PROFILE UNIFYING SYSTEM
ORT	OPEN ROAD TOLLING
Ø	PHASE
P	POLE
PCB	POLYCHLORINATED BIPHENYL
PNL	PANEL
PVC	POLYVINYL CHLORIDE
RECEPT.	RECEPTACLE
RGS	RIGID GALVANIZED STEEL
RMS	ROOT MEAN SQUARED
SB	SOUTHBOUND
SCADA	SUPERVISORY CONTROL & DATA ACQUISITION
SCH.	SCHEDULE
SCP	SCADA CONTROL PANEL
SCTE	SOCIETY OF CABLE TELECOMMUNICATIONS ENGINEERS
SD	SQUARE D
SER	SERVICE ENTRANCE RATED
SPD	SURGE PROTECTIVE DEVICE
SPEC(S)	SPECIFICATION(S)
S.P.S.T.	SINGLE POLE SINGLE THROW
S.S.	STAINLESS STEEL
STP	SHIELDED TWISTED PAIR
SQ.	SQUARE
STFE	STATE TOLL FACILITY ENGINEER
SYMM.	SYMMETRICAL
T.E.C.	TOLL EQUIPMENT CONTRACTOR
T&H	TEMPERATURE AND HUMIDITY SENSOR
T.O.	TOLL OPERATIONS
TSP	TECHNICAL SPECIAL PROVISIONS
TYP.	TYPICAL
UL	UNDERWRITERS LABORATORIES
UON	UNLESS OTHERWISE NOTED
UPS	UNINTERRUPTIBLE POWER SUPPLY
V	VOLTS
VAC	VOLTS ALTERNATING CURRENT
VCAR	VEHICLE CAPTURE AND RECOGNITION SYSTEM
VDAC	VEHICLE DETECTION AND CLASSIFICATION UNIT
VES	VIOLATION ENFORCEMENT SYSTEM
VSS	VIDEO SURVEILLANCE SYSTEM
W	WIRE; WATT
W/	WITH
WP	WEATHERPROOF (NEMA 3R)
XFMR	TRANSFORMER

REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ELECTRICAL SYMBOL LEGEND AND ABBREVIATIONS		DRAWING NO. GE-101
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		SHEET NO.
						SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A	

ELECTRICAL GENERAL NOTES:

1. FEED ALL RECEPTACLES AND DEVICES WITH (2) #12, (1) #12 GND IN 3/4" C, UON.
2. PROVIDE AN EQUIPMENT GROUNDING CONDUCTOR IN ALL FEEDER AND BRANCH CIRCUIT RACEWAYS.
3. ALL 120V, 20A CIRCUIT HOMERUNS OVER 50FT. SHALL BE #10 CU MINIMUM, UON.
4. ALL 120V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #8 CU MINIMUM, UON.
5. ALL 240V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #10 CU. MINIMUM, UON.
6. ALL 240V, 20A CIRCUIT HOMERUNS OVER 300FT. SHALL BE #8 CU MINIMUM, UON.
7. PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT AND RACEWAYS WITH LABELING AT EACH END.
8. THE USE OF ANY PROCESS INVOLVING ASBESTOS OR PCB, AND THE INSTALLATION OF ANY PRODUCT, INSULATION, COMPOUND OR MATERIAL CONTAINING OR INCORPORATING ASBESTOS OR PCB, IS PROHIBITED. PROVIDE A COMPLETE AND PROPERLY OPERATING ELECTRICAL SYSTEM WITHOUT THE USE OF ASBESTOS OR PCB.
9. CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID. SUBMISSION OF A BID WILL BE CONSTRUED AS EVIDENCE THAT SUCH EXAMINATION HAS BEEN MADE AND LATER CLAIMS FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WILL NOT BE RECOGNIZED.
10. INCLUDE THE TRANSPORT AND DISPOSAL OR RECYCLING OF ALL WASTE MATERIALS GENERATED BY THIS PROJECT IN ACCORDANCE WITH ALL RULES, REGULATIONS AND GUIDELINES APPLICABLE.
 - A) COMPLY FULLY WITH FLORIDA STATUTE 403.7186 REGARDING MERCURY CONTAINING DEVICES AND LAMPS.
 - B) TRANSPORT AND DISPOSE OF LAMPS, BALLASTS AND OTHER MATERIALS IN ACCORDANCE WITH ALL DEP AND EPA GUIDELINES.
 - C) PROVIDE WRITTEN CERTIFICATION THAT ALL MATERIALS WERE RECYCLED OR DISPOSED OF PROPERLY PER THE GUIDELINES NOTED ABOVE.
11. LOCATE EXISTING UTILITIES AND PROTECT THEM FROM DAMAGE.
12. PHASE WORK AS REQUIRED BY MOT PLANS.
13. UNDERGROUND CONDUIT SHALL BE PVC SCH. 80, UON. UNDERGROUND CONDUIT SHALL TRANSITION TO RGS CONDUIT WITH PVC TO RGS CONDUIT FITTINGS. CONDUIT SHALL BE RGS ABOVE GRADE THROUGH AND INCLUDING THE FIRST 90 DEGREE FITTING UNDERGROUND UON. APPLY 2-COAT BITUMASTIC COATING TO DIRECT BURIED PORTION OF RGS CONDUIT, UP TO AND INCLUDING 6" ABOVE FINAL GRADE. REFER TO TSP FOR FURTHER INFORMATION.
14. TOLL EQUIPMENT AND ALL WIRING/CABLING FOR TOLL EQUIPMENT WILL BE FURNISHED AND INSTALLED BY T.E.C., UON.
15. UNDERGROUND CONDUITS SHALL BE INSTALLED A MINIMUM OF 36" BELOW GRADE.
16. EXPOSED EXTERIOR CONDUIT SHALL BE RGS THROUGH AND INCLUDING THE FIRST 90' BEND INSTALLED UNDERGROUND. TRANSITIONS BETWEEN RGS AND PVC CONDUIT SHALL BE MADE WITH A RGS TO PVC CONDUIT FITTING.
17. EQUIPMENT SPECIFIED WITH CATALOG NUMBERS OR PART NUMBERS SHALL NOT BE SUBSTITUTED UNLESS "OR EQUAL" IS INDICATED.
18. PLASTIC END CAPS SHALL BE INSTALLED ON ENDS OF ALL UNISTRUT.
19. ALL LIQUID-TIGHT, FLEXIBLE CONDUIT SHALL BE METALLIC.
20. AC OR DC ELECTRICAL CIRCUITS OR WIRING THAT OPERATES AT 25 VOLTS OR GREATER SHALL NOT BE INSTALLED AND/OR LOCATED WITHIN 5 FEET OF ANY TRAFFIC DETECTION LOOP OR LOOP PULL BOX.
21. REFER TO TECHNICAL SPECIAL PROVISIONS FOR ADDITIONAL REQUIREMENTS.
22. OUTLET AND DEVICE JUNCTION BOXES INSTALLED OUTDOORS SHALL BE MANUFACTURED FROM GALVANIZED CAST IRON WITH THREADED HUBS, UON. REFER TO TSP SECTION 26 05 33 FOR DETAILS.


REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	ELECTRICAL GENERAL NOTES	GE-102
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A



1 RAMP E - GANTRY ELECTRICAL PLAN - TRANSORE (INFINITY) SYSTEM
 GE-111 SCALE: 3/16" = 1'-0"


REFERENCE NOTES:

- 1 TOLL EQUIPMENT CABLING PROVIDED BY T.E.C.
- 2 REFER TO DETAILS ON GE-114 FOR CONDUIT MOUNTING.
- 3 REFER TO TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE ON GE-115 FOR ADDITIONAL INFORMATION.
- 4 6"x6" FIBERGLASS WIREWAY (SEE TSP 26 05 34 FOR RATING). MOUNT WIREWAY TO TOLL EQUIPMENT STRUCTURE AND SUPPORTS WITH THE COVER FACING UP. POWER CIRCUITING SHALL BE PROVIDED WITH GROUND WIRES IN THE POWER WIREWAY. SEE TSP FOR DETAILS.
- 5 PROVIDE 8.25"x8.25" CLOSURE PLATE TO SEAL THE END OF WIREWAY RUN, #10 GAUGE, 316 STAINLESS STEEL.
- 6 PROVIDE 12GA 1-5/8" x 1-5/8" HOT-DIPPED GALVANIZED UNISTRUT AT 3'-0" MAXIMUM SPACING ALONG THE ENTIRE LENGTH OF WIREWAYS. CONNECT UNISTRUT TO BOTH STRUCTURAL ANGLES THAT PARALLEL THE HORIZONTAL WIREWAY RUNS.
- 7 PROVIDE COUPLING FROM RGS CONDUIT TO LIQUID TIGHT FLEXIBLE METAL CONDUIT.
- 8 PROVIDE (1) POWER AND (1) DATA 1-1/2" CONDUIT FROM EACH RESPECTIVE WIREWAY TO THE CCTV CAMERA. CCTV CAMERA AND CAMERA CABLES PROVIDED BY SECURITY CONTRACTOR.
- 9 CONDUITS ARE ROUTED ONE ON TOP OF EACH OTHER. REFER TO GE-114.
- 10 PROVIDE RECEPTACLE IN A 4" BOX INSIDE A NEMA 4 ENCLOSURE. ENCLOSURE SHALL BE HOFFMAN #A884PHC WITH ALUMINUM BACKPLANE HOFFMAN #A8PBAL OR APPROVED EQUAL. PROVIDE 120V SPD INSIDE ENCLOSURE. REFER TO TSP SECTION 26 43 13 FOR REQUIREMENTS. MOUNT ENCLOSURE TO A STRUCTURAL MEMBER A MAXIMUM OF 10' FROM PTZ CAMERA. CAMERA WILL BE PROVIDED AND INSTALLED BY THE SECURITY CONTRACTOR. COORDINATE EXACT LOCATION WITH DEPARTMENT PRIOR TO ROUGH IN.
- 11 PROVIDE FIBERGLASS CUT-OFF FITTINGS (SEE TSP 26 05 34 FOR RATING), WITH LENGTHS UP TO 24". SHORTEN BODY TO DESIRED LENGTH AND BOND FLANGE TO BODY.
- 12 PROVIDE 90° FIBERGLASS ELBOW TO CONNECT HORIZONTAL AND VERTICAL WIREWAYS. ELBOW SHALL MAINTAIN NEMA RATING (AS SPECIFIED IN TSP) IN THE ORIENTATION SHOWN.
- 13 PROVIDE 45° FIBERGLASS ELBOW. SEE TSP 26 05 34 FOR RATING.
- 14 PROVIDE FLEXIBLE FITTINGS (SEE TSP 26 05 34 FOR RATING) TO COMPENSATE FOR MISALIGNMENT, STRETCH LENGTH RANGE FROM 3 1/2" TO 12", HYPALON BELLOW WITH STAINLESS STEEL FLANGES.
- 15 PROVIDE 12GA, HOT-DIPPED GALVANIZED, 1-5/8" WIDTH SERIES UNISTRUT, HEIGHT VARIES TO SUPPORT AND CONNECT TO WIREWAYS.
- 16 E6 ANTENNA CABLES.




REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	RAMP E - GANTRY ELECTRICAL PLAN	GE-111
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 23


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




2 E6 WIREWAY LAYOUT DETAIL
 GE-112 SCALE: 3/8" = 1'-0"



4 E6 WIREWAY LAYOUT DETAIL - TOP VIEW
 GE-112 SCALE: 1/4" = 1'-0"



1 E6 WIREWAY LAYOUT DETAIL
 GE-112 SCALE: 1/4" = 1'-0"






3 E6 WIREWAY LAYOUT DETAIL
 GE-112 SCALE: 3/4" = 1'-0"

GENERAL NOTES:

1. DEBURR & FILE UNISTRUT AND MOUNTING HARDWARE TO ELIMINATE SHARP EDGES.
2. TERMINATE UNISTRUT WITH PLASTIC END CAPS.

REFERENCE NOTES:

1. PRE-DRILLED STRUCTURAL SUPPORT FABRICATED AS PART OF GANTRY COLUMN.
2. VERTICALLY MOUNTED 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT SECURED TO STRUCTURAL MEMBERS VIA PRE-DRILLED HOLES.
3. PROVIDE 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT TO SUPPORT HORIZONTAL WIREWAY. THE UNISTRUT SHALL BE MOUNTED HORIZONTALLY AND SECURED TO VERTICALLY MOUNTED UNISTRUT CHANNEL. PROVIDE 90° UNISTRUT FITTINGS RATED FOR A MINIMUM UNIFORM LOAD OF 500 LBS.
4. PROVIDE 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT BEHIND ENCLOSURE TO SUPPORT ENCLOSURE. PROVIDE A 1-1/2" GAP BETWEEN BUILDING AND ENCLOSURE TO ALLOW WATER TO DRAIN BEHIND ENCLOSURE.
5. PROVIDE 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT TO SUPPORT WIREWAY. UNISTRUT SHALL BE SECURED TO THE BOTTOM OF WIREWAY. REFER TO DETAIL 2 ON DRAWING GE-115.
6. PROVIDE BRACED SINGLE BRACKET RATED FOR A MINIMUM UNIFORM LOAD OF 924 LBS TO SUPPORT WIREWAY. COOPER B-LINE CAT NO. B494-30 OR EQUAL.
7. PROVIDE 24" X 20" X 10" NEMA TYPE 4X, ALUMINUM ENCLOSURE, CONTINUOUS HINGE DOOR WITH CLAMPS AND LOCKABLE HASP. HOFFMAN CATALOG #A24H2010ALLP OR APPROVED EQUIVALENT.
8. PROVIDE BOX CONNECTOR ON THE INSIDE OF THE ENCLOSURE TO ENSURE A WATER TIGHT SEAL BETWEEN WIREWAY AND ENCLOSURE. HOFFMAN CATALOG #F66WBF6 OR APPROVED EQUIVALENT.
9. 6" X 6" FIBERGLASS WIREWAY, UL LISTED FOR VERTICAL AND HORIZONTAL INSTALLATION. REFER TO TSP 26 05 34 FOR ADDITIONAL REQUIREMENTS.
10. PROVIDE FLEXIBLE FITTING TO COMPENSATE FOR MISALIGNMENT, STRETCH LENGTH RANGE FROM 3-1/2" TO 12", HYPALON BELLOW WITH STAINLESS STEEL FLANGES.
11. 6" HDPE SLEEVE CAST IN PLACE DURING FABRICATION OF CONCRETE WALL. CONDUIT SLEEVE SHALL HAVE STANDARD 2" HEIGHT, FULL PERIMETER WATER STOP.
12. PROVIDE WALL PENETRATION MECHANICAL PIPE SEAL TO CREATE PERMANENT WATERTIGHT SEAL BETWEEN CONDUIT AND CONDUIT SLEEVE. PIPE SEAL SHALL BE INSTALLED FLUSH WITH EXTERIOR WALL. REFER TO TSP 26 05 33 FOR ADDITIONAL REQUIREMENTS.
13. PROVIDE 4" SCHEDULE 80 PVC END BELL. SOLVENT CEMENT WELD END BELL TO 4" SCHEDULE 80 PVC CONDUIT.
14. PROVIDE 4" SCHEDULE 80 PVC CONDUIT SECURED WITH CONDUIT SEAL.
15. PROVIDE 4" PVC SCHEDULE 80 FITTING FOR ADAPTING PVC CONDUIT TO THREADED METALLIC CONDUIT HUB.
16. PROVIDE 4" WATERTIGHT, THREADED RIGID CONDUIT HUB FOR CONNECTION TO ENCLOSURE.
17. PROVIDE 1-5/8" WIDTH, HOT-DIPPED GALVANIZED UNISTRUT TO SUPPORT WIREWAY. WIREWAY SHALL BE LOOSELY SECURED TO UNISTRUT WITH GALVANIZED STEEL STRAP TO ALLOW APPROXIMATELY 1/4" FREE MOVEMENT OF WIREWAY IN HORIZONTAL AND VERTICAL DIRECTIONS.
18. 6" X 6" FIBERGLASS CUT-OFF FITTING, WITH LENGTH UP TO 24". SHORTEN BODY TO DESIRED LENGTH AND BOND FLANGE TO BODY.
19. PROVIDE CORROSION-RESISTANT, UL LISTED, TYPE 4X RATING VENT DRAIN IN BOTTOM OF ENCLOSURE.



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	
E6 WIREWAY ROUTING DETAILS	
PROJECT NAME:	
SR 429 WEKIVA PARKWAY SECTION 7A	

DRAWING NO.
GE-112
SHEET NO.
24

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.


GENERAL NOTES:

- UNISTRUT & MOUNTING HARDWARE SHALL BE DEBURRED & FILED SMOOTH TO REMOVE ROUGH EDGES.
- PROVIDE PLASTIC END CAPS FOR UNISTRUT SUPPORTS.
- PROVIDE TELESCOPING FITTINGS, MOUNTING HARDWARE AND ACCESSORIES TO PROVIDE A COMPLETE RACEWAY SYSTEM.
- UNISTRUT LESS THAN 20' SHALL BE CONTINUOUS WITHOUT SPLICES.
- PROVIDE UNISTRUT SUPPORTS AS REQUIRED TO SUPPORT THE NONMETALLIC WIREWAYS IN ACCORDANCE WITH NEC ARTICLE 378.


REFERENCE NOTES:

- 12"x12", NEMA 3R, UL 870 & UL50 LISTED WIRE TROUGH, 12 GAUGE PLATED STEEL WITH ANSI 61 GRAY POLYESTER POWDER PAINT FINISH INSIDE AND OUT. REFER TO SITE PLAN FOR CONDUIT ROUTING.
- 6"x6" FIBERGLASS WIREWAY, UL LISTED FOR VERTICAL INSTALLATION. REFER TO TSP 26 05 34 FOR DETAILS.
- 1-5/8" WIDTH, HEIGHT VARIES, VERTICALLY MOUNTED UNISTRUT SECURED TO STRUCTURAL MEMBERS VIA PRE-DRILLED HOLES. EC TO PROVIDE MOUNTING HARDWARE TO SECURE WIREWAY TO UNISTRUT.
- PROVIDE 90° ELBOW (REFER TO TSP 26 05 34 FOR RATING) TO CONNECT HORIZONTAL AND VERTICAL WIREWAYS. ELBOW SHALL MAINTAIN NEMA RATING IN THE ORIENTATION SHOWN.
- 1-5/8" x 1-5/8" UNISTRUT MOUNTED 6" FROM WIREWAY JOINTS.
- REFER TO SITE PLAN FOR CONDUIT SIZES, QUANTITIES & ROUTING.


- PROVIDE SUPPORT (NOT SHOWN) FOR WIREWAY.
- REFER TO DETAIL 3 ON THIS SHEET FOR WIRE TROUGH AND CONDUIT MOUNTING.
- PROVIDE TIN PLATED COPPER GROUND BUS. PROVIDE BONDING BUSHINGS ON ALL CONDUIT CONNECTIONS TO THE WIRE TROUGH AND POWER WIREWAY ABOVE. BOND BUSHINGS TO GND BUS WITH STRANDED #8 CU BOND. ALL EQUIPMENT GROUNDING CONDUCTORS SHALL BE BONDED TO THE GND BUS.
- PROVIDE 6"x6" FIBERGLASS CUT-OFF FITTING (REFER TO TSP 26 05 34 FOR RATING), WITH LENGTHS UP TO 24". SHORTEN BODY TO DESIRED LENGTH AND BOND FLANGE TO BODY.



1 WIREWAY - SECTION
GE-113 SCALE: 1/4" = 1'-0"



2 WIREWAY - SECTION
GE-113 SCALE: 1/4" = 1'-0"




3 WIRE TROUGH MOUNTING DETAIL
GE-113 SCALE: N.T.S.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
Peter J. Pastore, P.E. No. 77103


STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	DRAWING NO.
WIREWAY INSTALLATION DETAILS (1 OF 3)	GE-113
PROJECT NAME:	SHEET NO.
SR 429 WEKIVA PARKWAY SECTION 7A	25




1 CGB CABLE FITTING DETAIL
GE-114 SCALE: N.T.S.


- GENERAL NOTES:**
- COORDINATE CGB FITTING WITH CABLE SIZES INDICATED IN TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE.
 - CGB TYPE (WATER TIGHT) CABLE FITTINGS SHALL BE INSTALLED AT THE END OF ALL GANTRY MOUNTED RIGID CONDUIT AND LIQUID TIGHT FLEXIBLE METAL CONDUITS WHERE THE TOLL EQUIPMENT AND CCTV CABLES EMERGE FROM THE CONDUITS. THE CGB TYPE FITTINGS SHALL BE PROPERLY SIZED FOR THE DIAMETER OF THE TOLL EQUIPMENT CABLE INSTALLED IN EACH CONDUIT. THE CGB TYPE FITTING SHALL HAVE MANUAL ADJUSTABLE DIAMETER TO ALLOW THE CABLES TO BE FREELY PULLED THROUGH THE FITTING WITHOUT "GRABBING" THE CABLE DURING INSTALLATION AND PROVIDING A WEATHER TIGHT SEAL AFTER CABLES HAVE BEEN PULLED (BY MANUALLY TIGHTENING THE GLAND NUT). COUPLINGS AND REDUCERS SHALL BE PROVIDED BETWEEN THE CONDUITS AND CGB FITTINGS TO ENABLE THE USE OF CGB FITTINGS THAT ALLOW FOR PROPER WATER TIGHT SEALING AROUND CABLES. WATER-TIGHT FITTINGS OTHER THAN CGB TYPE WITH TAPERED NEOPRENE BUSHING AND CABLE CLAMP WILL NOT BE ACCEPTED. THE CGB FITTINGS FOR CONDUITS SERVING THE ANTENNAS SHALL ACCOMMODATE TWO CABLES. SUBMIT SAMPLES OF CGB FITTING FOR SINGLE AND DUAL CABLES TO THE DEPARTMENT FOR APPROVAL PRIOR TO PROCUREMENT.




2 WIREWAY MOUNTING DETAIL
GE-114 SCALE: N.T.S.



5 UNISTRUT MOUNTING DETAIL
GE-114 SCALE: N.T.S.



3 CONDUIT ROUTING DETAIL (TYPICAL U.O.N.)
GE-114 SCALE: N.T.S.



4 CONDUIT ROUTING DETAIL (TYPICAL U.O.N.)
GE-114 SCALE: N.T.S.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	
WIREWAY INSTALLATION DETAILS (2 OF 3)	
PROJECT NAME:	
SR 429 WEKIVA PARKWAY SECTION 7A	

DRAWING NO.
GE-114
SHEET NO.
26


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE					
EQUIPMENT/DEVICE	DATA		POWER		CABLE MINIMUM BENDING RADIUS
	CONDUIT DIAMETER	CABLE DIAMETER	CONDUIT DIAMETER	CABLE DIAMETER	
PTZ	1 1/2"	0.30"	1 1/2"	0.30"	4.0"
CCTV	1 1/2"	0.40"	COMBINED WITH DATA		4.0"
OPUS	1 1/2"	0.40"	COMBINED WITH DATA		4.0"
VCAR	1 1/2"	(3) 0.30"	1 1/2"	0.30"	4.0"
DVAS	1 1/2"	0.30"	1 1/2"	0.30"	4.0"
ANTENNA	1 1/2"	0.59"	N/A		6.0"
ANTENNA /OPUS	ANTENNA	1 1/2"	N/A		6.0"
	OPUS	1 1/2"	COMBINED WITH DATA		4.0"

GENERAL NOTES:

- CONTRACTOR MUST COORDINATE SIZE AND QUANTITY OF CONDUIT WITH TURNPIKE TOLL OPERATIONS PRIOR TO INSTALLATION TO ENSURE REQUIREMENTS HAVE NOT CHANGED.

1 TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE
GE-115 SCALE: NTS




2 WIREWAY SECURING DETAIL
GE-115 SCALE: N.T.S.

GENERAL NOTES:


- UNISTRUT & MOUNTING HARDWARE SHALL BE DEBURRED & FILED SMOOTH TO REMOVE ROUGH EDGES.
- PROVIDE PLASTIC END CAPS FOR UNISTRUT SUPPORTS.

REFERENCE NOTES:

- 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT. VERTICALLY MOUNTED AND SECURED TO STRUCTURAL MEMBERS VIA PRE-DRILLED HOLES.
- 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT. MOUNTED ON EACH SIDE OF WIREWAY JOINTS. REFER TO DETAIL 2 ON THIS SHEET.



3 COLUMN UNISTRUT DETAIL
GE-115 SCALE: N.T.S.




4 COLUMN UNISTRUT DETAIL
GE-115 SCALE: N.T.S.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION


AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	DRAWING NO.
WIREWAY INSTALLATION DETAILS (3 OF 3)	GE-115
PROJECT NAME:	SHEET NO.
SR 429 WEKIVA PARKWAY SECTION 7A	27



1 GANTRY COLUMN GND SPADE CONNECTION DETAIL
 GE-116 SCALE: N.T.S.



2 GANTRY COLUMN GROUNDING DETAIL
 GE-116 SCALE: N.T.S.

GENERAL NOTE:
 1. GROUND EACH GANTRY COLUMN.
 2. REFER TO TSP SECTION 26 41 13 FOR UNDERGROUND LIGHTNING PROTECTION CONDUCTOR.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01



SHEET TITLE: GANTRY - LIGHTNING PROTECTION DETAILS	DRAWING NO. GE-116
PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 28

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

ELECTRICAL SYMBOL LEGEND:

SYMBOL	DESCRIPTION
	125V, 20A NEMA L5-20R, DUPLEX RECEPTACLE. 'WP' INDICATES WEATHERPROOF WITH LOCKABLE METAL WHILE-IN-USE COVER. 'GFI' INDICATES GROUND FAULT INTERRUPTER.
	PAN TILT ZOOM CAMERA.
	WIREWAY, TYPE AND LENGTH AS INDICATED ON PLANS.
	FLEXIBLE WIREWAY FITTINGS.
	90° ELBOW FOR HORIZONTAL AND VERTICAL WIREWAY CONNECTION.
	45° ELBOW.
	90° ELBOW.
	GROUNDING ROD UON.
	DEVICE OR EQUIPMENT AS NOTED.
	REFERENCE NOTES.
	E6 READER.

GENERAL SYMBOL LEGEND:



ABBREVIATIONS:

A	AMPS
AASHTO	AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS
AC	AIR CONDITIONING [UNIT]
AFF	ABOVE FINISH FLOOR
AFG	ABOVE FINISH GRADE
AL, ALUM.	ALUMINUM
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS
ATS	AUTOMATIC TRANSFER SWITCH
AVI	AUTOMATIC VEHICLE IDENTIFICATION
AWG	AMERICAN WIRE GAUGE
BCU	BATTERY CHARGER UNIT
BLDG.	BUILDING
BPS	BYPASS SWITCH
C	CONDUIT
CCTV	CLOSED CIRCUIT TELEVISION
CKT.	CIRCUIT
COMP	COMPUTER
CU	COPPER
COMM.	COMMUNICATION
DEP	DEPARTMENT OF ENVIRONMENTAL PROTECTION
DIA.	DIAMETER
DN	DOWN
DVAS	DIGITAL VIDEO AUDITING SYSTEM
DWG.	DRAWING
E6	ENCOMPASS 6 MULTIPROTOCOL READER
EC	ELECTRICAL CONTRACTOR
ENG.	ENGINE
ETC	ELECTRONIC TOLL COLLECTION
ETC.	ET CETERA
EQUIP.	EQUIPMENT
EPA	ENVIRONMENTAL PROTECTION AGENCY
EPO	EMERGENCY POWER OFF
EXT.	EXTERIOR
FOC	FIBER OPTIC CABLE
FT	FOOT; FEET
FTE	FLORIDA'S TURNPIKE ENTERPRISE
FTL	FEED THROUGH LUGS
FTM	FUEL TANK MONITOR
FUT	FUTURE
GA	GAUGE
GAL.	GALLON
GEC	GROUNDING ELECTRODE CONDUCTOR
GFI	GROUND FAULT INTERRUPTER
GND	GROUND
HID	HIGH INTENSITY DISCHARGE
HP	HORSEPOWER
HZ	HORIZONTAL, HERTZ
I.C.	INTERRUPTING CAPACITY
I.D.	IDENTIFICATION
IN.	INCHES
JB	JUNCTION BOX
KA	KILOAMPERES
KVA	KILOVOLT AMPERES
KW	KILOWATT
LED	LIGHT EMITTING DIODE
LFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT
LN CTR	LANE CONTROLLER
LOC.	LOCATION
LLC	LEAD LAG CONTROLLER
LP	LIGHTNING PROTECTION
LTG	LIGHTING
MAX.	MAXIMUM
MCB	MAIN CIRCUIT BREAKER
MTS	MANUAL TRANSFER SWITCH
MIN.	MINIMUM
ML	MAINLINE
M.L.O.	MAIN LUGS ONLY
MOT	MAINTENANCE OF TRAFFIC
MTD	MOUNTED
N	NEUTRAL
NB	NORTHBOUND
N.C.	NORMALLY CLOSED
NEC	NATIONAL ELECTRICAL CODE
NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
NIC	NOT IN CONTRACT
NO.	NUMBER
N.O.	NORMALLY OPEN

ABBREVIATIONS CONT:

N.T.S.	NOT TO SCALE
N3R	NEMA 3R
OC	ON CENTER
OPUS	OPTICAL PROFILE UNIFYING SYSTEM
ORT	OPEN ROAD TOLLING
Ø	PHASE
P	POLE
PCB	POLYCHLORINATED BIPHENYL
PNL	PANEL
PVC	POLYVINYL CHLORIDE
RECEPT.	RECEPTACLE
RGS	RIGID GALVANIZED STEEL
RMS	ROOT MEAN SQUARED
SB	SOUTHBOUND
SCADA	SUPERVISORY CONTROL & DATA ACQUISITION
SCH.	SCHEDULE
SCP	SCADA CONTROL PANEL
SCTE	SOCIETY OF CABLE TELECOMMUNICATIONS ENGINEERS
SD	SQUARE D
SER	SERVICE ENTRANCE RATED
SPD	SURGE PROTECTIVE DEVICE
SPEC(S)	SPECIFICATION(S)
S.P.S.T.	SINGLE POLE SINGLE THROW
S.S.	STAINLESS STEEL
STP	SHIELDED TWISTED PAIR
SQ.	SQUARE
STFE	STATE TOLL FACILITY ENGINEER
SYMM.	SYMMETRICAL
T.E.C.	TOLL EQUIPMENT CONTRACTOR
T&H	TEMPERATURE AND HUMIDITY SENSOR
T.O.	TOLL OPERATIONS
TSP	TECHNICAL SPECIAL PROVISIONS
TYP.	TYPICAL
UL	UNDERWRITERS LABORATORIES
UON	UNLESS OTHERWISE NOTED
UPS	UNINTERRUPTIBLE POWER SUPPLY
V	VOLTS
VAC	VOLTS ALTERNATING CURRENT
VCAR	VEHICLE CAPTURE AND RECOGNITION SYSTEM
VDAC	VEHICLE DETECTION AND CLASSIFICATION UNIT
VES	VIOLATION ENFORCEMENT SYSTEM
VSS	VIDEO SURVEILLANCE SYSTEM
W	WIRE; WATT
W/	WITH
WP	WEATHERPROOF (NEMA 3R)
XFMR	TRANSFORMER


REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE: ELECTRICAL SYMBOL LEGEND AND ABBREVIATIONS		DRAWING NO. GE-201
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	PROJECT NAME:		SHEET NO.
						SR 429	SEMINOLE	240200-2-52-01	SR 429 WEKIVA PARKWAY SECTION 7A	

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.

ELECTRICAL GENERAL NOTES:

1. FEED ALL RECEPTACLES AND DEVICES WITH (2) #12, (1) #12 GND IN 3/4" C, UON.
2. PROVIDE AN EQUIPMENT GROUNDING CONDUCTOR IN ALL FEEDER AND BRANCH CIRCUIT RACEWAYS.
3. ALL 120V, 20A CIRCUIT HOMERUNS OVER 50FT. SHALL BE #10 CU MINIMUM, UON.
4. ALL 120V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #8 CU MINIMUM, UON.
5. ALL 240V, 20A CIRCUIT HOMERUNS OVER 150FT. SHALL BE #10 CU. MINIMUM, UON.
6. ALL 240V, 20A CIRCUIT HOMERUNS OVER 300FT. SHALL BE #8 CU MINIMUM, UON.
7. PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT AND RACEWAYS WITH LABELING AT EACH END.
8. THE USE OF ANY PROCESS INVOLVING ASBESTOS OR PCB, AND THE INSTALLATION OF ANY PRODUCT, INSULATION, COMPOUND OR MATERIAL CONTAINING OR INCORPORATING ASBESTOS OR PCB, IS PROHIBITED. PROVIDE A COMPLETE AND PROPERLY OPERATING ELECTRICAL SYSTEM WITHOUT THE USE OF ASBESTOS OR PCB.
9. CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID. SUBMISSION OF A BID WILL BE CONSTRUED AS EVIDENCE THAT SUCH EXAMINATION HAS BEEN MADE AND LATER CLAIMS FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WILL NOT BE RECOGNIZED.
10. INCLUDE THE TRANSPORT AND DISPOSAL OR RECYCLING OF ALL WASTE MATERIALS GENERATED BY THIS PROJECT IN ACCORDANCE WITH ALL RULES, REGULATIONS AND GUIDELINES APPLICABLE.
 - A) COMPLY FULLY WITH FLORIDA STATUTE 403.7186 REGARDING MERCURY CONTAINING DEVICES AND LAMPS.
 - B) TRANSPORT AND DISPOSE OF LAMPS, BALLASTS AND OTHER MATERIALS IN ACCORDANCE WITH ALL DEP AND EPA GUIDELINES.
 - C) PROVIDE WRITTEN CERTIFICATION THAT ALL MATERIALS WERE RECYCLED OR DISPOSED OF PROPERLY PER THE GUIDELINES NOTED ABOVE.
11. LOCATE EXISTING UTILITIES AND PROTECT THEM FROM DAMAGE.
12. PHASE WORK AS REQUIRED BY MOT PLANS.
13. UNDERGROUND CONDUIT SHALL BE PVC SCH. 80, UON. UNDERGROUND CONDUIT SHALL TRANSITION TO RGS CONDUIT WITH PVC TO RGS CONDUIT FITTINGS. CONDUIT SHALL BE RGS ABOVE GRADE THROUGH AND INCLUDING THE FIRST 90 DEGREE FITTING UNDERGROUND UON. APPLY 2-COAT BITUMASTIC COATING TO DIRECT BURIED PORTION OF RGS CONDUIT, UP TO AND INCLUDING 6" ABOVE FINAL GRADE. REFER TO TSP FOR FURTHER INFORMATION.
14. TOLL EQUIPMENT AND ALL WIRING/CABLING FOR TOLL EQUIPMENT WILL BE FURNISHED AND INSTALLED BY T.E.C., UON.
15. UNDERGROUND CONDUITS SHALL BE INSTALLED A MINIMUM OF 36" BELOW GRADE.
16. EXPOSED EXTERIOR CONDUIT SHALL BE RGS THROUGH AND INCLUDING THE FIRST 90' BEND INSTALLED UNDERGROUND. TRANSITIONS BETWEEN RGS AND PVC CONDUIT SHALL BE MADE WITH A RGS TO PVC CONDUIT FITTING.
17. EQUIPMENT SPECIFIED WITH CATALOG NUMBERS OR PART NUMBERS SHALL NOT BE SUBSTITUTED UNLESS "OR EQUAL" IS INDICATED.
18. PLASTIC END CAPS SHALL BE INSTALLED ON ENDS OF ALL UNISTRUT.
19. ALL LIQUID-TIGHT, FLEXIBLE CONDUIT SHALL BE METALLIC.
20. AC OR DC ELECTRICAL CIRCUITS OR WIRING THAT OPERATES AT 25 VOLTS OR GREATER SHALL NOT BE INSTALLED AND/OR LOCATED WITHIN 5 FEET OF ANY TRAFFIC DETECTION LOOP OR LOOP PULL BOX.
21. REFER TO TECHNICAL SPECIAL PROVISIONS FOR ADDITIONAL REQUIREMENTS.
22. OUTLET AND DEVICE JUNCTION BOXES INSTALLED OUTDOORS SHALL BE MANUFACTURED FROM GALVANIZED CAST IRON WITH THREADED HUBS, UON. REFER TO TSP SECTION 26 05 33 FOR DETAILS.


REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	ELECTRICAL GENERAL NOTES	GE-202
						SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A



1 RAMP F - GANTRY ELECTRICAL PLAN - TRANSORE (INFINITY) SYSTEM
 GE-211 SCALE: 3/16" = 1'-0"


REFERENCE NOTES:

- 1 TOLL EQUIPMENT CABLING PROVIDED BY T.E.C.
- 2 REFER TO DETAILS ON GE-214 FOR CONDUIT MOUNTING.
- 3 REFER TO TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE ON GE-215 FOR ADDITIONAL INFORMATION.
- 4 6"x6" FIBERGLASS WIREWAY (SEE TSP 26 05 34 FOR RATING). MOUNT WIREWAY TO TOLL EQUIPMENT STRUCTURE AND SUPPORTS WITH THE COVER FACING UP. POWER CIRCUITING SHALL BE PROVIDED WITH GROUND WIRES IN THE POWER WIREWAY. SEE TSP FOR DETAILS.
- 5 PROVIDE 8.25"x8.25" CLOSURE PLATE TO SEAL THE END OF WIREWAY RUN, #10 GAUGE, 316 STAINLESS STEEL.
- 6 PROVIDE 12GA 1-5/8" x 1-5/8" HOT-DIPPED GALVANIZED UNISTRUT AT 3'-0" MAXIMUM SPACING ALONG THE ENTIRE LENGTH OF WIREWAYS. CONNECT UNISTRUT TO BOTH STRUCTURAL ANGLES THAT PARALLEL THE HORIZONTAL WIREWAY RUNS.
- 7 PROVIDE COUPLING FROM RGS CONDUIT TO LIQUID TIGHT FLEXIBLE METAL CONDUIT.
- 8 PROVIDE (1) POWER AND (1) DATA 1-1/2" CONDUIT FROM EACH RESPECTIVE WIREWAY TO THE CCTV CAMERA. CCTV CAMERA AND CAMERA CABLES PROVIDED BY SECURITY CONTRACTOR.
- 9 CONDUITS ARE ROUTED ONE ON TOP OF EACH OTHER. REFER TO GE-214.
- 10 PROVIDE RECEPTACLE IN A 4" BOX INSIDE A NEMA 4 ENCLOSURE. ENCLOSURE SHALL BE HOFFMAN #A884PHC WITH ALUMINUM BACKPLANE HOFFMAN #A8PBAL OR APPROVED EQUAL. PROVIDE 120V SPD INSIDE ENCLOSURE. REFER TO TSP SECTION 26 43 13 FOR REQUIREMENTS. MOUNT ENCLOSURE TO A STRUCTURAL MEMBER A MAXIMUM OF 10' FROM PTZ CAMERA. CAMERA WILL BE PROVIDED AND INSTALLED BY THE SECURITY CONTRACTOR. COORDINATE EXACT LOCATION WITH DEPARTMENT PRIOR TO ROUGH IN.
- 11 PROVIDE FIBERGLASS CUT-OFF FITTINGS (SEE TSP 26 05 34 FOR RATING), WITH LENGTHS UP TO 24". SHORTEN BODY TO DESIRED LENGTH AND BOND FLANGE TO BODY.
- 12 PROVIDE 90° FIBERGLASS ELBOW TO CONNECT HORIZONTAL AND VERTICAL WIREWAYS. ELBOW SHALL MAINTAIN NEMA RATING (AS SPECIFIED IN TSP) IN THE ORIENTATION SHOWN.
- 13 PROVIDE 45° FIBERGLASS ELBOW. SEE TSP 26 05 34 FOR RATING.
- 14 PROVIDE FLEXIBLE FITTINGS (SEE TSP 26 05 34 FOR RATING) TO COMPENSATE FOR MISALIGNMENT, STRETCH LENGTH RANGE FROM 3 1/2" TO 12", HYPALON BELLOW WITH STAINLESS STEEL FLANGES.
- 15 PROVIDE 12GA, HOT-DIPPED GALVANIZED, 1-5/8" WIDTH SERIES UNISTRUT, HEIGHT VARIES TO SUPPORT AND CONNECT TO WIREWAYS.
- 16 E6 ANTENNA CABLES.




REVISIONS				AECOM Technical Services, Inc. 7650 West Courtney Campbell Causeway Tampa, FL 33607-1462 No. 8115 Peter J. Pastore, P.E. No. 77103	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			SHEET TITLE:	DRAWING NO.
DATE	DESCRIPTION	DATE	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID	RAMP F - GANTRY ELECTRICAL PLAN	GE-211
					SR 429	SEMINOLE	240200-2-52-01	PROJECT NAME: SR 429 WEKIVA PARKWAY SECTION 7A	SHEET NO. 31


NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




2 E6 WIREWAY LAYOUT DETAIL
 GE-212 SCALE: 3/8" = 1'-0"



4 E6 WIREWAY LAYOUT DETAIL - TOP VIEW
 GE-212 SCALE: 1/4" = 1'-0"



1 E6 WIREWAY LAYOUT DETAIL
 GE-212 SCALE: 1/4" = 1'-0"






3 E6 WIREWAY LAYOUT DETAIL
 GE-212 SCALE: 3/4" = 1'-0"

GENERAL NOTES:

1. DEBURR & FILE UNISTRUT AND MOUNTING HARDWARE TO ELIMINATE SHARP EDGES.
2. TERMINATE UNISTRUT WITH PLASTIC END CAPS.

REFERENCE NOTES:

- 1 PRE-DRILLED STRUCTURAL SUPPORT FABRICATED AS PART OF GANTRY COLUMN.
- 2 VERTICALLY MOUNTED 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT SECURED TO STRUCTURAL MEMBERS VIA PRE-DRILLED HOLES.
- 3 PROVIDE 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT TO SUPPORT HORIZONTAL WIREWAY. THE UNISTRUT SHALL BE MOUNTED HORIZONTALLY AND SECURED TO VERTICALLY MOUNTED UNISTRUT CHANNEL. PROVIDE 90° UNISTRUT FITTINGS RATED FOR A MINIMUM UNIFORM LOAD OF 500 LBS.
- 4 PROVIDE 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT BEHIND ENCLOSURE TO SUPPORT WIREWAY. PROVIDE A 1-1/2" GAP BETWEEN BUILDING AND ENCLOSURE TO ALLOW WATER TO DRAIN BEHIND ENCLOSURE.
- 5 PROVIDE 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT TO SUPPORT WIREWAY. UNISTRUT SHALL BE SECURED TO THE BOTTOM OF WIREWAY. REFER TO DETAIL 2 ON DRAWING GE-215.
- 6 PROVIDE BRACED SINGLE BRACKET RATED FOR A MINIMUM UNIFORM LOAD OF 924 LBS TO SUPPORT WIREWAY. COOPER B-LINE CAT NO. B494-30 OR EQUAL.
- 7 PROVIDE 24" X 20" X 10" NEMA TYPE 4X, ALUMINUM ENCLOSURE, CONTINUOUS HINGE DOOR WITH CLAMPS AND LOCKABLE HASP. HOFFMAN CATALOG #A24H2010ALLP OR APPROVED EQUIVALENT.
- 8 PROVIDE BOX CONNECTOR ON THE INSIDE OF THE ENCLOSURE TO ENSURE A WATER TIGHT SEAL BETWEEN WIREWAY AND ENCLOSURE. HOFFMAN CATALOG #F66WBF6 OR APPROVED EQUIVALENT.
- 9 6" X 6" FIBERGLASS WIREWAY, UL LISTED FOR VERTICAL AND HORIZONTAL INSTALLATION. REFER TO TSP 26 05 34 FOR ADDITIONAL REQUIREMENTS.
- 10 PROVIDE FLEXIBLE FITTING TO COMPENSATE FOR MISALIGNMENT, STRETCH LENGTH RANGE FROM 3-1/2" TO 12", HYPALON BELLOW WITH STAINLESS STEEL FLANGES.
- 11 6" HDPE SLEEVE CAST IN PLACE DURING FABRICATION OF CONCRETE WALL. CONDUIT SLEEVE SHALL HAVE STANDARD 2" HEIGHT, FULL PERIMETER WATER STOP.
- 12 PROVIDE WALL PENETRATION MECHANICAL PIPE SEAL TO CREATE PERMANENT WATERTIGHT SEAL BETWEEN CONDUIT AND CONDUIT SLEEVE. PIPE SEAL SHALL BE INSTALLED FLUSH WITH EXTERIOR WALL. REFER TO TSP 26 05 33 FOR ADDITIONAL REQUIREMENTS.
- 13 PROVIDE 4" SCHEDULE 80 PVC END BELL. SOLVENT CEMENT WELD END BELL TO 4" SCHEDULE 80 PVC CONDUIT.
- 14 PROVIDE 4" SCHEDULE 80 PVC CONDUIT SECURED WITH CONDUIT SEAL.
- 15 PROVIDE 4" PVC SCHEDULE 80 FITTING FOR ADAPTING PVC CONDUIT TO THREADED METALLIC CONDUIT HUB.
- 16 PROVIDE 4" WATERTIGHT, THREADED RIGID CONDUIT HUB FOR CONNECTION TO ENCLOSURE.
- 17 PROVIDE 1-5/8" WIDTH, HOT-DIPPED GALVANIZED UNISTRUT TO SUPPORT WIREWAY. WIREWAY SHALL BE LOOSELY SECURED TO UNISTRUT WITH GALVANIZED STEEL STRAP TO ALLOW APPROXIMATELY 1/4" FREE MOVEMENT OF WIREWAY IN HORIZONTAL AND VERTICAL DIRECTIONS.
- 18 6" X 6" FIBERGLASS CUT-OFF FITTING, WITH LENGTH UP TO 24". SHORTEN BODY TO DESIRED LENGTH AND BOND FLANGE TO BODY.
- 19 PROVIDE CORROSION-RESISTANT, UL LISTED, TYPE 4X RATING VENT DRAIN IN BOTTOM OF ENCLOSURE.



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	
E6 WIREWAY ROUTING DETAILS	
PROJECT NAME:	
SR 429 WEKIVA PARKWAY SECTION 7A	

DRAWING NO.
GE-212
SHEET NO.
32

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.


GENERAL NOTES:

- UNISTRUT & MOUNTING HARDWARE SHALL BE DEBURRED & FILED SMOOTH TO REMOVE ROUGH EDGES.
- PROVIDE PLASTIC END CAPS FOR UNISTRUT SUPPORTS.
- PROVIDE TELESCOPING FITTINGS, MOUNTING HARDWARE AND ACCESSORIES TO PROVIDE A COMPLETE RACEWAY SYSTEM.
- UNISTRUT LESS THAN 20' SHALL BE CONTINUOUS WITHOUT SPLICES.
- PROVIDE UNISTRUT SUPPORTS AS REQUIRED TO SUPPORT THE NONMETALLIC WIREWAYS IN ACCORDANCE WITH NEC ARTICLE 378.


REFERENCE NOTES:

- 12"x12", NEMA 3R, UL 870 & UL50 LISTED WIRE TROUGH, 12 GAUGE PLATED STEEL WITH ANSI 61 GRAY POLYESTER POWDER PAINT FINISH INSIDE AND OUT. REFER TO SITE PLAN FOR CONDUIT ROUTING.
- 6"x6" FIBERGLASS WIREWAY, UL LISTED FOR VERTICAL INSTALLATION. REFER TO TSP 26 05 34 FOR DETAILS.
- 1-5/8" WIDTH, HEIGHT VARIES, VERTICALLY MOUNTED UNISTRUT SECURED TO STRUCTURAL MEMBERS VIA PRE-DRILLED HOLES. EC TO PROVIDE MOUNTING HARDWARE TO SECURE WIREWAY TO UNISTRUT.
- PROVIDE 90° ELBOW (REFER TO TSP 26 05 34 FOR RATING) TO CONNECT HORIZONTAL AND VERTICAL WIREWAYS. ELBOW SHALL MAINTAIN NEMA RATING IN THE ORIENTATION SHOWN.
- 1-5/8" x 1-5/8" UNISTRUT MOUNTED 6" FROM WIREWAY JOINTS.
- REFER TO SITE PLAN FOR CONDUIT SIZES, QUANTITIES & ROUTING.


- PROVIDE SUPPORT (NOT SHOWN) FOR WIREWAY.
- REFER TO DETAIL 3 ON THIS SHEET FOR WIRE TROUGH AND CONDUIT MOUNTING.
- PROVIDE TIN PLATED COPPER GROUND BUS. PROVIDE BONDING BUSHINGS ON ALL CONDUIT CONNECTIONS TO THE WIRE TROUGH AND POWER WIREWAY ABOVE. BOND BUSHINGS TO GND BUS WITH STRANDED #8 CU BOND. ALL EQUIPMENT GROUNDING CONDUCTORS SHALL BE BONDED TO THE GND BUS.
- PROVIDE 6"x6" FIBERGLASS CUT-OFF FITTING (REFER TO TSP 26 05 34 FOR RATING), WITH LENGTHS UP TO 24". SHORTEN BODY TO DESIRED LENGTH AND BOND FLANGE TO BODY.



1 WIREWAY - SECTION
GE-213 SCALE: 1/4" = 1'-0"



2 WIREWAY - SECTION
GE-213 SCALE: 1/4" = 1'-0"



3 WIRE TROUGH MOUNTING DETAIL
GE-213 SCALE: N.T.S.


REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01


SHEET TITLE:	DRAWING NO.
WIREWAY INSTALLATION DETAILS (1 OF 3)	GE-213
PROJECT NAME:	SHEET NO.
SR 429 WEKIVA PARKWAY SECTION 7A	33

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.




1 CGB CABLE FITTING DETAIL
GE-214 SCALE: N.T.S.


- GENERAL NOTES:**
- COORDINATE CGB FITTING WITH CABLE SIZES INDICATED IN TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE.
 - CGB TYPE (WATER TIGHT) CABLE FITTINGS SHALL BE INSTALLED AT THE END OF ALL GANTRY MOUNTED RIGID CONDUIT AND LIQUID TIGHT FLEXIBLE METAL CONDUITS WHERE THE TOLL EQUIPMENT AND CCTV CABLES EMERGE FROM THE CONDUITS. THE CGB TYPE FITTINGS SHALL BE PROPERLY SIZED FOR THE DIAMETER OF THE TOLL EQUIPMENT CABLE INSTALLED IN EACH CONDUIT. THE CGB TYPE FITTING SHALL HAVE MANUAL ADJUSTABLE DIAMETER TO ALLOW THE CABLES TO BE FREELY PULLED THROUGH THE FITTING WITHOUT "GRABBING" THE CABLE DURING INSTALLATION AND PROVIDING A WEATHER TIGHT SEAL AFTER CABLES HAVE BEEN PULLED (BY MANUALLY TIGHTENING THE GLAND NUT). COUPLINGS AND REDUCERS SHALL BE PROVIDED BETWEEN THE CONDUITS AND CGB FITTINGS TO ENABLE THE USE OF CGB FITTINGS THAT ALLOW FOR PROPER WATER TIGHT SEALING AROUND CABLES. WATER-TIGHT FITTINGS OTHER THAN CGB TYPE WITH TAPERED NEOPRENE BUSHING AND CABLE CLAMP WILL NOT BE ACCEPTED. THE CGB FITTINGS FOR CONDUITS SERVING THE ANTENNAS SHALL ACCOMMODATE TWO CABLES. SUBMIT SAMPLES OF CGB FITTING FOR SINGLE AND DUAL CABLES TO THE DEPARTMENT FOR APPROVAL PRIOR TO PROCUREMENT.




2 WIREWAY MOUNTING DETAIL
GE-214 SCALE: N.T.S.



5 UNISTRUT MOUNTING DETAIL
GE-214 SCALE: N.T.S.



3 CONDUIT ROUTING DETAIL (TYPICAL U.O.N.)
GE-214 SCALE: N.T.S.



4 CONDUIT ROUTING DETAIL (TYPICAL U.O.N.)
GE-214 SCALE: N.T.S.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
7650 West Courtney
Campbell Causeway
Tampa, FL 33607-1462
No. 8115
Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:
WIREWAY INSTALLATION DETAILS (2 OF 3)
PROJECT NAME:
SR 429 WEKIVA PARKWAY SECTION 7A


DRAWING NO.
GE-214
SHEET NO.
34

TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE					
EQUIPMENT/DEVICE	DATA		POWER		CABLE MINIMUM BENDING RADIUS
	CONDUIT DIAMETER	CABLE DIAMETER	CONDUIT DIAMETER	CABLE DIAMETER	
PTZ	1 1/2"	0.30"	1 1/2"	0.30"	4.0"
CCTV	1 1/2"	0.40"	COMBINED WITH DATA		4.0"
OPUS	1 1/2"	0.40"	COMBINED WITH DATA		4.0"
VCAR	1 1/2"	(3) 0.30"	1 1/2"	0.30"	4.0"
DVAS	1 1/2"	0.30"	1 1/2"	0.30"	4.0"
ANTENNA	1 1/2"	0.59"	N/A		6.0"
ANTENNA /OPUS	ANTENNA	1 1/2"	N/A		6.0"
	OPUS	1 1/2"	COMBINED WITH DATA		4.0"

GENERAL NOTES:

- CONTRACTOR MUST COORDINATE SIZE AND QUANTITY OF CONDUIT WITH TURNPIKE TOLL OPERATIONS PRIOR TO INSTALLATION TO ENSURE REQUIREMENTS HAVE NOT CHANGED.

1 TOLL EQUIPMENT CONDUIT/CABLE SCHEDULE
 GE-215 SCALE: NTS




2 WIREWAY SECURING DETAIL
 GE-215 SCALE: N.T.S.

GENERAL NOTES:


- UNISTRUT & MOUNTING HARDWARE SHALL BE DEBURRED & FILED SMOOTH TO REMOVE ROUGH EDGES.
- PROVIDE PLASTIC END CAPS FOR UNISTRUT SUPPORTS.

REFERENCE NOTES:

- 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT. VERTICALLY MOUNTED AND SECURED TO STRUCTURAL MEMBERS VIA PRE-DRILLED HOLES.
- 1-5/8" WIDTH SERIES, HOT-DIPPED GALVANIZED UNISTRUT. MOUNTED ON EACH SIDE OF WIREWAY JOINTS. REFER TO DETAIL 2 ON THIS SHEET.



3 COLUMN UNISTRUT DETAIL
 GE-215 SCALE: N.T.S.




4 COLUMN UNISTRUT DETAIL
 GE-215 SCALE: N.T.S.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION


AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	DRAWING NO.
WIREWAY INSTALLATION DETAILS (3 OF 3)	GE-215
PROJECT NAME:	SHEET NO.
SR 429 WEKIVA PARKWAY SECTION 7A	35



1 GANTRY COLUMN GND SPADE CONNECTION DETAIL
 GE-216 SCALE: N.T.S.



2 GANTRY COLUMN GROUNDING DETAIL
 GE-216 SCALE: N.T.S.

GENERAL NOTE:
 1. GROUND EACH GANTRY COLUMN.
 2. REFER TO TSP SECTION 26 41 13 FOR UNDERGROUND LIGHTNING PROTECTION CONDUCTOR.

REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

AECOM Technical Services, Inc.
 7650 West Courtney
 Campbell Causeway
 Tampa, FL 33607-1462
 No. 8115
 Peter J. Pastore, P.E. No. 77103

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
SR 429	SEMINOLE	240200-2-52-01

SHEET TITLE:	DRAWING NO.
GANTRY - LIGHTNING PROTECTION DETAILS	GE-216
PROJECT NAME:	SHEET NO.
SR 429 WEKIVA PARKWAY SECTION 7A	36

NOTICE: THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61G15-23.004, F.A.C.